

MATERIAL SAFETY DATA SHEET STAN-TONE VC-27516 DARK BLUE MICA

Version Number 1.1 Revision Date 04/04/2004 Page 1 of 7 Print Date 11/14/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	STAN-TONE VC-27516 DARK BLUE MICA
Product code	:	CC00039067
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Carbon black	1333-86-4	1 - 5
Titanium dioxide	13463-67-7	1 - 5
Mica	12001-26-2	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation Ingestion Eyes Skin	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Particulates, like other inert materials can be mechanically irritating. Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET STAN-TONE VC-27516 DARK BLUE MICA

Version Number 1.1 Revision Date 04/04/2004 Page 2 of 7 Print Date 11/14/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits	
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Autoignition temperature	: Not applicable
Suitable extinguishing media	: Carbon dioxide blanket, water spray, dry powder, foamnone.
Suitable extinguishing media	. Carbon dioxide blanket, water spray, dry powder, foannione.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unuqual Fire/Explosion	: May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under
Unusual Fire/Explosion Hazards	fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. Processing fume



MATERIAL SAFETY DATA SHEET STAN-TONE VC-27516 DARK BLUE MICA

Version Number 1.1 Revision Date 04/04/2004 Page 3 of 7 Print Date 11/14/2011

Storage	:	condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials. Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXI	POSUI	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required. If dusty conditions occur wear appropriate respiratory protection.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Carbon black	3.5 mg/m3	Time Weighted Average	Total dust. as carbon	ACGIH
		(TWA):	black	
	3.5 mg/m3	PEL:	Total dust. as carbon	OSHA Z1
			black	
Mica	20 mppcf	PEL:	Total dust.	OSHA
	3 mg/m3	Time Weighted Average	Respirable fraction.	ACGIH
		(TWA):		
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color Odor Melting point/range Boiling Point: Solid
powder, granular
BLUE
Very faint
Not determined
Not applicable

Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density pH Not applicable
Not determined
Not determined
Not applicable
Not applicable
Not applicable



MATERIAL SAFETY DATA SHEET STAN-TONE VC-27516 DARK BLUE MICA

Version Number 1.1 Revision Date 04/04/2004

Page 4 of 7 Print Date 11/14/2011

Water solubility : Insoluble **10. STABILITY AND REACTIVITY** Stability : Stable. Hazardous Polymerization Will not occur. : Conditions to avoid To avoid thermal decomposition, do not overheat. Keep away from : oxidizing agents and open flame. Incompatible Materials : Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen Hazardous decomposition : (NOx), hydrogen chloride (HCl), other hazardous materials, and products smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
12001-26-2	Mica	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Additional Health Hazard Information:

MATERIAL SAFETY DATA SHEET STAN-TONE VC-27516 DARK BLUE MICA

Version Number 1.1 Revision Date 04/04/2004 Page 5 of 7 Print Date 11/14/2011

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). The IARC 2B listing only pertains to airborne, unbound carbon black particles of respirable size. Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

12. ECOLOGICAL INFORMATION

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Adverse ecological impact is not known or expected under normal use.
Bioaccumulation Potential	: No data available
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Not regulated for transportation.
IMO / IMDG (maritime)	: Not regulated for transportation.
	15. REGULATORY INFORMATION
	13. REGULATORT INFORMATION
US Regulations:	13. REGULATORT INFORMATION
US Regulations: OSHA Status	: Classified as hazardous based on components.

PolyOne

MATERIAL SAFETY DATA SHEET STAN-TONE VC-27516 DARK BLUE MICA

Version Number 1.1 Revision Date 04/04/2004 Page 6 of 7 Print Date 11/14/2011

Inventory.			
JS. EPA CERCLA Hazardous Substances (40 CFR 302)			
Not applicable			
California Proposition : WARNING! This pro 65 California to cause car	ncer.	hemical know	n to the Sta
SARA Title III Section 302 Extremely Hazardous Substanc	ce		
Not applicable			
SARA Title III Section 313 Toxic Chemicals:			
Chemical Name	CAS-No.	Weight	%
COPPER COMPOUNDS	29719-96-8	7.83	-
National Pollutant Release Inventory (NPRI)			
	CAS-No.	Weight %	NPRI ID#
Chemical Name Aluminum	CAS-No. 7429-90-5	Weight % 0.48	NPRI ID#
Chemical Name Aluminum Chromium hydroxide (Cr(OH)3)	7429-90-5 1308-14-1	0.48 0.16	12 68
Chemical Name Aluminum Chromium hydroxide (Cr(OH)3) Copper, [C,C,C-trichloro-29H,31H-phthalocyaninato(2-)-N2	7429-90-5	0.48	12
Chemical Name Aluminum Chromium hydroxide (Cr(OH)3) Copper,	7429-90-5 1308-14-1	0.48 0.16	12 68
Chemical Name Aluminum Chromium hydroxide (Cr(OH)3) Copper, [C,C,C-trichloro-29H,31H-phthalocyaninato(2-)-N2 9,N30,N31,N32]- Misc00005- Misc Zinc Cpd's WHMIS Classification : D2A WHMIS Ingredient Disclosure List CAS-No. 1333-86-4 29719-96-8	7429-90-5 1308-14-1 29719-96-8	0.48 0.16 7.83	12 68 70
Chemical Name Aluminum Chromium hydroxide (Cr(OH)3) Copper, [C,C,C-trichloro-29H,31H-phthalocyaninato(2-)-N2 9,N30,N31,N32]- Misc00005- Misc Zinc Cpd's WHMIS Classification : D2A WHMIS Ingredient Disclosure List CAS-No. 1333-86-4	7429-90-5 1308-14-1 29719-96-8 Not Available	0.48 0.16 7.83 0.12	12 68 70 241



MATERIAL SAFETY DATA SHEET STAN-TONE VC-27516 DARK BLUE MICA

Version Number 1.1 Revision Date 04/04/2004 Page 7 of 7 Print Date 11/14/2011

China IECS	: Not determined
Europe EINECS	: Not determined
Japan ENCS	: Not determined
Korea KECI	: Not determined
Philippines PICCS	: Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.