MATERIAL SAFETY DATA SHEET STAN-TONE VCP-12995 FOLKSTONE

Version Number 1.1 Revision Date 10/25/2006

Page 1 of 6 Print Date 11/24/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).	
STAN-TONE VCP-12995 FOLKSTONE	
CC00039076	
Mixture	
Mixture	
Industrial Applications	
:	 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident). STAN-TONE VCP-12995 FOLKSTONE CC00039076 Mixture Mixture

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	60 - 100

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation Ingestion Eyes Skin	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Particulates, like other inert materials can be mechanically irritating. Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

PolyOne.

MATERIAL SAFETY DATA SHEET STAN-TONE VCP-12995 FOLKSTONE

Version Number 1.1 Revision Date 10/25/2006 Page 2 of 6 Print Date 11/24/2011

	4. FIRST AID MEASURES	
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cas doubt seek medical advice.	es of
Ingestion	: Do not induce vomiting without medical advice. When sympton persist or in all cases of doubt seek medical advice.	ns
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for least 15 minutes. If eye irritation persists, seek medical attention	
Skin	: Wash off with soap and plenty of water. If skin irritation persists medical attention.	seel
	5. FIRE-FIGHTING MEASURES	
Flash point	: Not applicable	
F 1		
Flammable Limits	. Not applicable	
Upper explosion limit	: Not applicable : Not applicable	
Lower explosion limit		
Autoignition temperature	: Not relevant	
Suitable extinguishing media	: Carbon dioxide blanket, water spray, dry powder, foamnone.	
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.	tive
Unusual Fire/Explosion Hazards	: May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) u fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), o of nitrogen (NOx), other hazardous materials, and smoke are all possible.	
	. ACCIDENTAL RELEASE MEASURES	
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.	
Environmental precautions	: Should not be released into the environment. The product should be allowed to enter drains, water courses or the soil.	1 not
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material plastic, cardboard or metal containers for disposal. Refer to Section of this MSDS for proper disposal methods.	
	7. HANDLING AND STORAGE	
Handling	: Take measures to prevent the build up of electrostatic charge. He only in areas with appropriate exhaust ventilation. Processing fu	

PolyOne.

MATERIAL SAFETY DATA SHEET STAN-TONE VCP-12995 FOLKSTONE

Version Number 1.1 Revision Date 10/25/2006 Page 3 of 6 Print Date 11/24/2011

Storage :	:	condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials. Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXPOSU	JR	E CONTROLS / PERSONAL PROTECTION
Respiratory protection :	:	No personal respiratory protective equipment normally required. If dusty conditions occur wear appropriate respiratory protection.
Eye/Face Protection :	•	Safety glasses with side-shields.
Hand protection :		Protective gloves.
Skin and body protection :	:	Long sleeved clothing.
Additional Protective : Measures	:	Safety shoes.
General Hygiene : Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures :	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	20 mg/m3	Short Term Exposure Limit	as Ti	MX OEL
		(STEL):		

Form	: Solid	Evaporation rate	: Not applicable
Appearance	: powder, granular	Specific Gravity:	: Not determined
Color	: WHITE	Bulk density	: Not determined
Odor	: Very faint	Vapor pressure	: Not applicable
Melting point/range	: Not determined	Vapour density	: Not applicable
Boiling Point:	: Not applicable	pH	: Not applicable
Water solubility	: Insoluble		
	10. STABILITY ANI	D REACTIVITY	
Stability	: Stable.		

PolvOne

MATERIAL SAFETY DATA SHEET STAN-TONE VCP-12995 FOLKSTONE

Version Number 1.1 Revision Date 10/25/2006 Page 4 of 6 Print Date 11/24/2011

Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	To avoid thermal decomposition, do not overheat. Keep away from oxidizing agents and open flame.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Adverse ecological impact is not known or expected under normal use.
Bioaccumulation Potential	:	No data available

PolyOne

MATERIAL SAFETY DATA SHEET STAN-TONE VCP-12995 FOLKSTONE

Version Number 1.1 Revision Date 10/25/2006 Page 5 of 6 Print Date 11/24/2011

Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Not regulated for transportation.
IMO / IMDG (maritime)	: Not regulated for transportation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	is Substances (40 CFR 302)
Not applicable	
California Propositior 65	i : Not applicable
SARA Title III Section 302 E	Extremely Hazardous Substance
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regula

MATERIAL SAFETY DATA SHEET STAN-TONE VCP-12995 FOLKSTONE

Version Number 1.1 Revision Date 10/25/2006 Page 6 of 6 Print Date 11/24/2011

SARA Title III Section 313 Toxic Chemicals: Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation Canadian Regulations: National Pollutant Release Inventory (NPRI) Not applicable WHMIS Classification : Not controlled. DSL All components of this product are on the Canadian Domestic · Substances List (DSL) or are exempt. National Inventories: Australia AICS Not determined China IECS Not determined ÷ Europe EINECS Not determined • Japan ENCS Not determined : Korea KECI Not determined ٠ Philippines PICCS Not determined :

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.