#### MATERIAL SAFETY DATA SHEET STAN-TONE VCP-15483 BLACK

Version Number 1.2 Revision Date 04/05/2004

Page 1 of 6 Print Date 11/14/2011

#### **1. PRODUCT AND COMPANY IDENTIFICATION** POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012 Product Stewardship (770) 271-5902 Telephone : **Emergency telephone** CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure : number or accident). : STAN-TONE VCP-15483 BLACK Product name : CC00039122 Product code Chemical Name : Mixture CAS-No. : Mixture Product Use : Industrial Applications

#### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Carbon black	1333-86-4	10 - 30

#### 3. HAZARDS IDENTIFICATION

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation Ingestion Eyes Skin	<ul> <li>Resin particles, like other inert materials, can be mechanically irritating</li> <li>May be harmful if swallowed.</li> <li>Particulates, like other inert materials can be mechanically irritating.</li> <li>Experience shows no unusual dermatitis hazard from routine handling.</li> </ul>
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES



## MATERIAL SAFETY DATA SHEET STAN-TONE VCP-15483 BLACK

ion Number 1.2 sion Date 04/05/2004	Page 2 Print Date 11/14/2
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
-	
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not relevant</li> </ul>
Suitable extinguishing media	: Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of

*PolyOne* 

## MATERIAL SAFETY DATA SHEET STAN-TONE VCP-15483 BLACK

Version Number 1.2 Revision Date 04/05/2004 Page 3 of 6 Print Date 11/14/2011

		these materials.	
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.	
8. EXPOS	UR	E CONTROLS / PERSONAL PROTECTION	
Respiratory protection	:	No personal respiratory protective equipment normally required. If dusty conditions occur wear appropriate respiratory protection.	
Eye/Face Protection	:	Safety glasses with side-shields.	
Hand protection	:	Protective gloves.	
Skin and body protection	:	Long sleeved clothing.	
Additional Protective Measures	:	Safety shoes.	
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.	
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.	

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Carbon black	3.5 mg/m3	Time Weighted Average (TWA):	Total dust. as carbon black	ACGIH
	3.5 mg/m3	PEL:	Total dust. as carbon black	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES	

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- powder, granular
  BLACK
  Very faint
  Not determined
  Not applicable
  Insoluble

: Solid

Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density pH

- Not applicable
  Not determined
  Not applicable
  Not applicable
  Not applicable
- : Not applicable
- 10. STABILITY AND REACTIVITY

Stability

: Stable.

Hazardous Polymerization

: Will not occur.



## MATERIAL SAFETY DATA SHEET STAN-TONE VCP-15483 BLACK

Version Number 1.2 Revision Date 04/05/2004 Page 4 of 6 Print Date *11/14/2011* 

Conditions to avoid	:	To avoid thermal decomposition, do not overheat. Keep away from oxidizing agents and open flame.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

#### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

#### Additional Health Hazard Information:

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). The IARC 2B listing only pertains to airborne, unbound carbon black particles of respirable size. Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

	12. ECOLOGICAL INFORMATION	
Persistence and degradability	Not readily biodegradable.	
Environmental Toxicity	Adverse ecological impact is not known or expected under normal	use.

PolyOne.

### MATERIAL SAFETY DATA SHEET STAN-TONE VCP-15483 BLACK

Version Number 1.2 Revision Date 04/05/2004 Page 5 of 6 Print Date 11/14/2011

	: No data available
Bioaccumulation Potential	
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Not regulated for transportation.
IMO / IMDG (maritime)	: Not regulated for transportation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
	All company of this and duct and listed on an ensure the TSCA
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
TSCA Status US. EPA CERCLA Hazardous	Inventory.
	Inventory.
US. EPA CERCLA Hazardous	Inventory.
US. EPA CERCLA Hazardous	Inventory.
US. EPA CERCLA Hazardous Not applicable California Proposition	Inventory. Substances (40 CFR 302) : WARNING! This product contains a chemical known to the State of California to cause cancer.
US. EPA CERCLA Hazardous Not applicable California Proposition 65	Inventory. Substances (40 CFR 302) : WARNING! This product contains a chemical known to the State of California to cause cancer.
US. EPA CERCLA Hazardous Not applicable California Proposition 65 SARA Title III Section 302 Ex	Inventory. Substances (40 CFR 302) : WARNING! This product contains a chemical known to the State of California to cause cancer. tremely Hazardous Substance
US. EPA CERCLA Hazardous Not applicable California Proposition 65 SARA Title III Section 302 Ex Not applicable	Inventory. Substances (40 CFR 302) : WARNING! This product contains a chemical known to the State of California to cause cancer. tremely Hazardous Substance

## MATERIAL SAFETY DATA SHEET STAN-TONE VCP-15483 BLACK

Version Number 1.2 Revision Date 04/05/2004 Page 6 of 6 Print Date 11/14/2011

Not applicable Canadian Regulations:

National Pollutant Release Inventory (NPRI) Chemical Name CAS-No. Weight % NPRI ID# Misc00005- Misc Zinc Cpd's Not Available 0.12 241 WHMIS Classification : D2A WHMIS Ingredient Disclosure List CAS-No. 1333-86-4 DSL All components of this product are on the Canadian Domestic : Substances List (DSL) or are exempt. National Inventories: Australia AICS Not determined • China IECS Not determined : Europe EINECS Not determined : Japan ENCS Not determined : Korea KECI Not determined · Not determined **Philippines PICCS** : **16. OTHER INFORMATION** 

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.