MATERIAL SAFETY DATA SHEET 522817 RED PE

Version Number 1.2 Revision Date 01/15/2013

Page 1 of 8 Print Date 1/15/2013

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	522817 RED PE
Product code	:	CC01020221
Chemical Name	:	Mixture
CAS-No.	:	Mixture

: Mixture Product Use **Industrial Applications** :

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Benzenesulfonic acid, 5-chloro-2-[(2-	5160-02-1	10 - 30
hydroxy-1-naphthalenyl)azo]-4-methyl-,		
barium salt (2:1)		
Rutile (TiO2)	1317-80-2	0.1 - 1
Silica, amorphous, precipitated and gel	112926-00-8	1 - 5
Zinc stearate	557-05-1	1 - 5
Mica	12001-26-2	5 - 10
Titanium dioxide	13463-67-7	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the enduser (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

: Inhalation, Ingestion, Skin contact **Routes of Exposure:**

Acute exposure

Inhalation

: Resin particles, like other inert materials, can be mechanically irritating.



MATERIAL SAFETY DATA SHEET **522817 RED PE**

 May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating teyes. Experience shows no unusual dermatitis hazard from routine handling Refer to Section 11 for Toxicological Information. None known. 4. FIRST AID MEASURES Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice. Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice. Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
 Resin particles, like other inert materials, are mechanically irritating teyes. Experience shows no unusual dermatitis hazard from routine handling Refer to Section 11 for Toxicological Information. None known. 4. FIRST AID MEASURES Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice. Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice. Rinse immediately with plenty of water, also under the eyelids, for a second se
 Experience shows no unusual dermatitis hazard from routine handling Refer to Section 11 for Toxicological Information. None known. 4. FIRST AID MEASURES Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice. Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice. Rinse immediately with plenty of water, also under the eyelids, for a
 None known. 4. FIRST AID MEASURES Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice. Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice. Rinse immediately with plenty of water, also under the eyelids, for a
 4. FIRST AID MEASURES Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice. Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice. Rinse immediately with plenty of water, also under the eyelids, for a
 Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice. Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice. Rinse immediately with plenty of water, also under the eyelids, for a
 overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice. Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice. Rinse immediately with plenty of water, also under the eyelids, for a
persist or in all cases of doubt seek medical advice.Rinse immediately with plenty of water, also under the eyelids, for a
: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
5. FIREFIGHTING MEASURES
: not applicable
: not applicable
: not applicable
: not applicable
: Carbon dioxide blanket, Water spray, Dry powder, Foam.
: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen
(NOx), other hazardous materials, and smoke are all possible.
ACCIDENTAL RELEASE MEASURES
: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
:



MATERIAL SAFETY DATA SHEET **522817 RED PE**

ersion Number 1.2 evision Date 01/15/2013		Page 3 o Print Date 1/15/20
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXI	OSU	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

PolyOne.

MATERIAL SAFETY DATA SHEET **522817 RED PE**

Version Number 1.2 Revision Date 01/15/2013 Page 4 of 8 Print Date 1/15/2013

Components	Value	Exposure time	Exposure type	List:
Mica	3 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
	3 mg/m3	Recommended exposure limit (REL):	Respirable.	NIOSH
	3 mg/m3	Time Weighted Average (TWA):	Respirable dust.	OSHA Z1A
	3 mg/m3	Time Weighted Average (TWA):		MX OEL
Rutile (TiO2)	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL
Silica, amorphous, precipitated and gel	6 mg/m3	Time Weighted Average (TWA):		OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	0.8 mg/m3	Time Weighted Average (TWA):		Z3
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL
Zinc stearate	5 mg/m3	Recommended exposure limit (REL):	Respirable.	NIOSH
	10 mg/m3	Recommended exposure limit (REL):	Total	NIOSH
	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	5 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
	10 mg/m3	Time Weighted Average (TWA):		ACGIH

P<u>olyOne</u>

MATERIAL SAFETY DATA SHEET 522817 RED PE

Version Number 1.2 Revision Date 01/15/2013

Page 5 of 8 Print Date 1/15/2013

9	. PHYSICAL AND CHEN	MICAL PROPERTIES	
Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility	 solid pellets RED very faint Not determined not applicable insoluble 	Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH	Not establishednot applicable
	10. STABILITY AN	D REACTIVITY	
Stability	: The product is stab	ble if stored and handled as	s prescribed.
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	: Keep away from or decomposition, do	xidizing agents and open f not overheat.	lame. To avoid thermal
Incompatible Materials	: Incompatible with	strong acids and oxidizing	g agents.
Hazardous decomposition products		O2), carbon monoxide (CC dous materials, and smoke	· · ·

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
5160-02-1	Benzenesulfonic acid, 5- chloro-2-[(2-hydroxy-1- naphthalenyl)azo]-4- methyl-, barium salt (2:1)	Irritant	Eyes, Skin.
112926-00-8	Silica, amorphous, precipitated and gel	Irritant	Respiratory system, Eyes.
557-05-1	Zinc stearate	Systemic effects	Eyes, Skin, Respiratory system.
12001-26-2	Mica	Systemic effects	Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
557-05-1	Zinc stearate	Oral LD50	> 10 gm/kg	rat

PolyOne

MATERIAL SAFETY DATA SHEET **522817 RED PE**

Version Number 1.2 Revision Date 01/15/2013 Page 6 of 8 Print Date 1/15/2013

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1317-80-2	Rutile (TiO2)	no	2B	no
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product Contaminated packaging	 Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Refer to specific regulation.
IMO/IMDG (maritime)	: Refer to specific regulation.

PolyOne.

MATERIAL SAFETY DATA SHEET **522817 RED PE**

Version Number 1.2 Revision Date 01/15/2013

	Page 7 of 8
Print Date	1/15/2013

S Regulations: OSHA Status TSCA Status S. EPA CERCLA Hazardous S	 Classified as haz All components TSCA Inventory 	ardous based of			
TSCA Status	: All components	ardous based of			
			n compon	ents.	
US. EPA CERCLA Hazardous S	•		are listed	on or exem	pt from the
	Substances (40 CFR 3	02)			
not applicable					
California Proposition 65	: WARNING! Th California to cau		ains a che	emical know	n to the Stat
SARA Title III Section 302 Extre					
	emely Hazardous Sub	ostance			
	-		ct is Not	Applicable (under this re
Unless specific chemicals are ide SARA Title III Section 313 Toxi Unless specific chemicals are ide Chemical Name BARIUM COMPOUNDSBAR	entified under this sec ic Chemicals: entified under this sec	ction, this produ ction, this produ CAS	<u>ct is Not</u>		under this re
Unless specific chemicals are ide SARA Title III Section 313 Toxi Unless specific chemicals are ide Chemical Name	entified under this sec ic Chemicals: entified under this sec	ction, this produ ction, this produ CAS	<u>ct is Not .</u> -No. 02-1	Applicable v	under this re percent 30.00
Unless specific chemicals are ide SARA Title III Section 313 Toxi Unless specific chemicals are ide Chemical Name BARIUM COMPOUNDSBAR [EXCEPT BASO4]	entified under this sec ic Chemicals: entified under this sec RIUM COMPOUND	ction, this produ ction, this produ CAS S 5160-	<u>ct is Not .</u> -No. 02-1	Applicable weight 10.00 - 1.00 - 5	under this re percent 30.00

PolyOne

MATERIAL SAFETY DATA SHEET 522817 RED PE

Version Number 1.2 Revision Date 01/15/2013

Page 8 of 8 Print Date 1/15/2013

12001-26-2 557-05-1		
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:		
Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Listed
Japan ENCS	:	Listed
Korea KECI	:	Listed
Philippines PICCS	:	Listed
16. OTHER INFORMATION		

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.