

## INDUSTRIAL YELLOW

Version Number 1.0
Revision Date 02/25/2019

Page 1 of 19 Print Date 02/26/2019

# SAFETY DATA SHEET

#### **INDUSTRIAL YELLOW**

# **Section 1. Identification**

GHS product identifier : INDUSTRIAL YELLOW

Chemical name: MixtureCAS number: MixtureOther means of identification: CC01053921Product type: liquid

Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Industrial applications. Plastics.

Supplier's details : POLYONE CORPORATION

ColorMatrix Group Inc.

680 North Rocky River Drive, Berea, Ohio, 44017-1628, USA

+1 216 622 0100

Emergency telephone number (with hours of operation)

CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or

accident).

# Section 2. Hazards identification

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard

Communication Standard (29 CFR 1910.1200).

Classification of the substance or

mixture

SKIN IRRITATION - Category 2 SKIN SENSITIZATION - Category 1

#### **GHS** label elements



# INDUSTRIAL YELLOW

Version Number 1.0 Page 2 of 19 Revision Date 02/25/2019 Print Date 02/26/2019

Hazard pictograms

❖

Signal word : Warning

**Hazard statements** : Causes skin irritation.

May cause an allergic skin reaction.

**Precautionary statements** 

**General** : Not applicable.

**Prevention**: Wear protective gloves. Avoid breathing vapor. Wash hands

thoroughly after handling. Contaminated work clothing must not be

allowed out of the workplace.

**Response** : IF ON SKIN: Wash with plenty of soap and water. Wash

contaminated clothing before reuse. If skin irritation or rash occurs:

Get medical attention.

**Storage** : Not applicable.

**Disposal** : Dispose of contents and container in accordance with all local,

regional, national and international regulations.

**Supplemental label elements** : None known. **Hazards not otherwise classified** : None known.

# Section 3. Composition/information on ingredients

Substance/mixture: MixtureChemical name: MixtureOther means of identification: CC01053921

## CAS number/other identifiers

Ingredient name	%	CAS number
Titanium dioxide	25 - 50	13463-67-7
Miscellaneous Compounds Distillates, petroleum, hydrotreated middle	10 - 25	Not available.
Distillates (petroleum), hydrotreated light	10 - 25	64742-47-8



# INDUSTRIAL YELLOW

 Version Number 1.0
 Page 3 of 19

 Revision Date 02/25/2019
 Print Date 02/26/2019

Bis (1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	3 - 5	41556-26-7
Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidinyl ester	1 - 3	82919-37-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

# Section 4. First aid measures

## **Description of necessary first aid measures**

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the
,		upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	:	Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get



#### INDUSTRIAL YELLOW

Version Number 1.0 Page 4 of 19 Revision Date 02/25/2019 Print Date 02/26/2019

medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

**Skin contact**: Causes skin irritation. May cause an allergic skin reaction.

**Ingestion**: No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

**Eye contact**: Adverse symptoms may include the following:

pain or irritation

watering

redness

**Inhalation** : No specific data.

**Skin contact**: Adverse symptoms may include the following:

irritation redness

**Ingestion** : No specific data.

#### Indication of immediate medical attention and special treatment needed, if necessary

**Notes to physician**: In case of inhalation of decomposition products in a fire, symptoms

may be delayed. The exposed person may need to be kept under

medical surveillance for 48 hours.

**Specific treatments** : No specific treatment.

**Protection of first-aiders**: No action shall be taken involving any personal risk or without

suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

# Section 5. Firefighting measures

#### Extinguishing media



## INDUSTRIAL YELLOW

Version Number 1.0 Revision Date 02/25/2019 Page 5 of 19 Print Date 02/26/2019

Suitable extinguishing media Unsuitable extinguishing media In case of fire, use water spray (fog), foam, dry chemical or CO<sub>2</sub>.

None known.

Specific hazards arising from the chemical

In a fire or if heated, a pressure increase will occur and the container may burst. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway,

sewer or drain.

Hazardous thermal decomposition products

Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides

halogenated compounds metal oxide/oxides

Special protective actions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any

personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated

in positive pressure mode.

# Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without

suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is

inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialized clothing is required to deal with the spillage, take note

of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil,

waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment

if released in large quantities.

#### Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with



#### INDUSTRIAL YELLOW

Version Number 1.0 Revision Date 02/25/2019 Page 6 of 19 Print Date 02/26/2019

Large spill

water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

## Precautions for safe handling

**Protective measures** 

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

# Section 8. Exposure controls/personal protection



## INDUSTRIAL YELLOW

 Version Number 1.0
 Page 7 of 19

 Revision Date 02/25/2019
 Print Date 02/26/2019

#### **Control parameters**

#### Occupational exposure limits

Ingredient name	Exposure limits
Titanium dioxide	OSHA PEL 1989 (1989-03-01) TWA 10 mg/m3 Form: Total dust OSHA PEL (1993-06-30) TWA 15 mg/m3 Form: Total dust ACGIH TLV (1996-05-18) TWA 10 mg/m3
Miscellaneous Compounds Distillates, petroleum, hydrotreated middle	None.
Distillates (petroleum), hydrotreated light	ACGIH TLV (2003-01-01) Absorbed through skin. TWA 200 mg/m3 (Calculated as total hydrocarbon vapor)
Bis (1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	None.
Decanedioic acid, methyl 1,2,2,6,6- pentamethyl-4-piperidinyl ester	None.

**Appropriate engineering controls** : Good general ventilation should be sufficient to control worker

exposure to airborne contaminants.

**Environmental exposure controls**: Emissions from ventilation or work process equipment should be

checked to ensure they comply with the requirements of

environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be

necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

**Hygiene measures**: Wash hands, forearms and face thoroughly after handling chemical

products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations

and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used

when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a

higher degree of protection: chemical splash goggles.



#### INDUSTRIAL YELLOW

Version Number 1.0 Revision Date 02/25/2019 Page 8 of 19 Print Date 02/26/2019

#### **Skin protection**

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved

standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves

cannot be accurately estimated.

**Body protection**: Personal protective equipment for the body should be selected based

on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks

involved and should be approved by a specialist before handling this

product.

**Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that

meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper

fitting, training, and other important aspects of use.

# Section 9. Physical and chemical properties

#### **Appearance**

Physical state liquid [liquid] Color YELLOW Odor Faint odor. **Odor threshold** Not available. Not available. pН **Melting point** Not available. **Boiling point** Not available. Flash point Not available. **Burning time** Not available. **Burning rate** Not available. Not available. **Evaporation rate** Not available. Flammability (solid, gas)

Lower and upper explosive : Lower: Not available. (flammable) limits : Upper: Not available.

Vapor pressure: Not available.Vapor density: Not available.Relative density: Not available.



## INDUSTRIAL YELLOW

Version Number 1.0 Page 9 of 19 Revision Date 02/25/2019 Print Date 02/26/2019

**Solubility** : Not available. **Solubility in water** : insoluble in water.

Partition coefficient: n-

octanol/water

Auto-ignition temperature: Not available.Decomposition temperature: Not available.SADT: Not available.

Viscosity : Dynamic: Not available.

Kinematic: Not available.

# Section 10. Stability and reactivity

**Reactivity** : No specific test data related to reactivity available for this product or

its ingredients.

Not available.

Chemical stability : Stable under recommended storage and handling conditions (see

Section 7).

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will

not occur.

**Conditions to avoid** : Keep away from extreme heat and oxidizing agents.

**Incompatible materials** : Keep away from strong acids.

Oxidizer.

**Hazardous decomposition** 

products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F). Do not use this pigment in polymers at temperatures over 200°C (392°F). Decomposition of diarylide pigments in polymers at temperatures over 200°C (392°F) may produce trace amounts of monoazo dyes, which in turn can decompose to produce aromatic amines. The amount and type of degradation products formed depend on the dwell time, formulation and processing conditions as well as temperature. As conditions become more severe, as when temperatures move into the 240-300°C (464-572°F) range, trace quantities of 3,3'-dichlorobenzidine can be generated. 3,3'dichlorobenzidine is classified as a suspect carcinogen by NTP and IARC, is classified as Acute Toxicity category 4 and Carcinogen Category 1B according to 1272/2008EC (CLP), and is regulated by OSHA as a suspect carcinogen. In order to avoid the generation of and exposure to 3,3'-dichlorobenzidine, do not use diarylide pigments in polymers when temperatures exceed 200°C (392°F). Handle with care. Organic dusts have the potential to be explosive with static

spark or flame initiation.



# INDUSTRIAL YELLOW

 Version Number 1.0
 Page 10 of 19

 Revision Date 02/25/2019
 Print Date 02/26/2019

# Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Information on toxicological effects**

### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure	
Titanium dioxide					
Remarks - Oral:	No applicable toxic	city data			
	LC50 Inhalation	Rat - Male	6.82 Mg/l	4 h	
	LD50 Dermal	Rabbit	> 5,000 mg/kg	-	
Miscellaneous Compounds Dis	stillates, petroleum, l	nydrotreated middle			
Remarks - Oral:	No applicable toxic	city data			
Remarks - Inhalation:	No applicable toxic	city data			
Remarks - Dermal:	No applicable toxic	city data			
Distillates (petroleum), hydroti	eated light				
Remarks - Oral:	No applicable toxic	city data			
Remarks - Inhalation:	No applicable toxic	No applicable toxicity data			
Remarks - Dermal:	No applicable toxicity data				
Bis (1,2,2,6,6-pentamethyl-4-p	yl-4-piperidinyl) sebacate				
Remarks - Oral:	No applicable toxicity data				
Remarks - Inhalation:	No applicable toxicity data				
Remarks - Dermal:	No applicable toxicity data				
Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidinyl ester					
Remarks - Oral:	No applicable toxic	city data			
Remarks - Inhalation:	No applicable toxic	city data			
Remarks - Dermal:	No applicable toxicity data				
C/C	. M'	•			

**Conclusion/Summary** : Mixture.Not fully tested.

#### **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium dioxide	Skin - Mild	Human		72 hrs	-
	irritant				

Conclusion/Summary

Skin:Mixture.Not fully tested.Eyes:Mixture.Not fully tested.Respiratory:Mixture.Not fully tested.

#### Sensitization



INDUSTRIAL YELLOW

Version Number 1.0 Page 11 of 19 Revision Date 02/25/2019 Print Date 02/26/2019

Conclusion/Summary

Skin: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

**Mutagenicity** 

Conclusion/Summary : Mixture.Not fully tested.

**Carcinogenicity** 

**Conclusion/Summary**: Mixture.Not fully tested.

Classification

Product/ingredient	OSHA	IARC	NTP
name			
Titanium dioxide		2B	

#### **Reproductive toxicity**

**Conclusion/Summary** : Mixture.Not fully tested.

**Teratogenicity** 

**Conclusion/Summary** : Mixture.Not fully tested.

#### **Specific target organ toxicity (single exposure)**

Not available.

#### Specific target organ toxicity (repeated exposure)

Not available.

**Aspiration hazard** 

Product/ingredient name	Result
Miscellaneous Compounds Distillates, petroleum,	ASPIRATION HAZARD - Category 1
hydrotreated middle	
Distillates (petroleum), hydrotreated light	ASPIRATION HAZARD - Category 1

**Information on likely routes of** :

exposure

Not available.

### Potential acute health effects

Eye contact
Inhalation
No known significant effects or critical hazards.
No known significant effects or critical hazards.

**Skin contact**: Causes skin irritation. May cause an allergic skin reaction.



## INDUSTRIAL YELLOW

 Version Number 1.0
 Page 12 of 19

 Revision Date 02/25/2019
 Print Date 02/26/2019

**Ingestion**: No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:

pain or irritation

watering

redness

**Inhalation** : No specific data.

**Skin contact** : Adverse symptoms may include the following:

irritation redness

**Ingestion** : No specific data.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### **Short term exposure**

Potential immediate effects : Not available.
Potential delayed effects : Not available.

**Long term exposure** 

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Potential chronic health effects

**Conclusion/Summary** : Mixture.Not fully tested.

General : Once sensitized, a severe allergic reaction may occur when

subsequently exposed to very low levels.

Carcinogenicity: No known significant effects or critical hazards.Mutagenicity: No known significant effects or critical hazards.Teratogenicity: No known significant effects or critical hazards.Developmental effects: No known significant effects or critical hazards.Fertility effects: No known significant effects or critical hazards.

# Numerical measures of toxicity

#### **Acute toxicity estimates**

Route	ATE value
Inhalation (vapors)	88.7 mg/l
Route	ATE value



# INDUSTRIAL YELLOW

Version Number 1.0 Revision Date 02/25/2019 Page 13 of 19 Print Date 02/26/2019

Inhalation (dusts and mists)	9.961 mg/l
------------------------------	------------

# Section 12. Ecological information

# **Toxicity**

Product/ingredient name	Result	Species	Exposure	
Titanium dioxide				
	Acute LC50 > 1,000 Mg/l Marine	Fish - Fish	96 h	
	water			
Remarks - Acute - Fish:	Acute			
	Acute LC50 3 Mg/l Fresh water	Aquatic invertebrates.	48 h	
		Crustaceans		
Remarks - Acute - Aquatic	Acute			
invertebrates.:				
	Acute LC50 6.5 Mg/l Fresh water	Aquatic invertebrates.	48 h	
		Daphnia		
Remarks - Acute - Aquatic	Acute			
invertebrates.:				
Remarks - Acute - Aquatic	No applicable toxicity data			
plants:				
Remarks - Chronic - Fish:	No applicable toxicity data			
Remarks - Chronic -	No applicable toxicity data			
Aquatic invertebrates.:				
	stillates, petroleum, hydrotreated midd	lle		
Remarks - Acute - Fish:	No applicable toxicity data			
Remarks - Acute - Aquatic	No applicable toxicity data			
invertebrates.:				
Remarks - Acute - Aquatic	No applicable toxicity data			
plants:				
Remarks - Chronic - Fish:	No applicable toxicity data			
Remarks - Chronic -	No applicable toxicity data			
Aquatic invertebrates.:				
Distillates (petroleum), hydroti				
	Acute LC50 2.2 Mg/l Fresh water	Fish - Fish	96 h	
Remarks - Acute - Fish:	Acute			
Remarks - Acute - Aquatic	No applicable toxicity data			
invertebrates.:				
Remarks - Acute - Aquatic	No applicable toxicity data			
plants:				
Remarks - Chronic - Fish:	No applicable toxicity data			



# INDUSTRIAL YELLOW

Version Number 1.0 Revision Date 02/25/2019 Page 14 of 19 Print Date 02/26/2019

Remarks - Chronic -	No applicable toxicity data
Aquatic invertebrates.:	The applicable tokietty data
Bis (1,2,2,6,6-pentamethyl-4-p	ineridinyl) sebacate
Remarks - Acute - Fish:	No applicable toxicity data
Remarks - Acute - Aquatic	No applicable toxicity data
invertebrates.:	
Remarks - Acute - Aquatic	No applicable toxicity data
plants:	
Remarks - Chronic - Fish:	No applicable toxicity data
Remarks - Chronic -	No applicable toxicity data
Aquatic invertebrates.:	
Decanedioic acid, methyl 1,2,2	2,6,6-pentamethyl-4-piperidinyl ester
Remarks - Acute - Fish:	No applicable toxicity data
Remarks - Acute - Aquatic	No applicable toxicity data
invertebrates.:	
Remarks - Acute - Aquatic	No applicable toxicity data
plants:	
Remarks - Chronic - Fish:	No applicable toxicity data
Remarks - Chronic -	No applicable toxicity data
Aquatic invertebrates.:	·
INDUSTRIAL YELLOW	
Remarks - Acute - Aquatic	Dangerous for the environment: May cause long term adverse effects in the aquatic
invertebrates.:	environment.
G 1 ' /G	Decree Confidence in the Management of the Confidence in the Confi

Conclusion/Summary

: Dangerous for the environment: May cause long term adverse effects

in the aquatic environment.

## Persistence and degradability

Conclusion/Summary : Not available.

**Conclusion/Summary** : Dangerous for the environment: May cause long term adverse effects

in the aquatic environment.

#### **Bioaccumulative potential**

Not available.

## **Mobility in soil**

Soil/water partition coefficient

(KOC)

Not available.

Other adverse effects : No known significant effects or critical hazards.



#### INDUSTRIAL YELLOW

Version Number 1.0 Page 15 of 19 Revision Date 02/25/2019 Print Date 02/26/2019

# Section 13. Disposal considerations

**Disposal methods** 

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

# **Section 14. Transport information**

U.S.DOT 49CFR Ground/Air/Water : Not regulated for transportation.

International Air ICAO/IATA

UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate), 9,

PGIII, Marine Pollutant

International Water IMO/IMDG

UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate), 9,

PGIII, Marine Pollutant

# Section 15. Regulatory information

U.S. Federal regulations : United States - TSCA 12(b) - Chemical export notification: None

of the components are listed.

United States - TSCA 4(a) - Final Test Rules: Not listed
United States - TSCA 4(a) - ITC Priority list: Not listed
United States - TSCA 4(a) - Proposed test rules: Not listed
United States - TSCA 4(f) - Priority risk review: Not listed
United States - TSCA 5(a)2 - Final significant new use rules: Not



#### INDUSTRIAL YELLOW

Version Number 1.0 Revision Date 02/25/2019

Page 16 of 19 Print Date 02/26/2019

listed

United States - TSCA 5(a)2 - Proposed significant new use rules:

Not listed

United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined

United States - TSCA 8(a) - Preliminary assessment report (PAIR): Not listed

United States - TSCA 8(c) - Significant adverse reaction (SAR):

Not listed

United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority

pollutants: Listed Rutile, antimony chromium buff

United States - EPA Clean water act (CWA) section 311 -

Hazardous substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Flammable substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Toxic substances: Not listed

**United States - Department of commerce - Precursor chemical:** 

Not listed

Listed

Clean Air Act Section 112(b)

Hazardous Air Pollutants (HAPs)

Clean Air Act Section 602 Class I

**Substances** 

Clean Air Act Section 602 Class II

**Substances** 

**DEA List I Chemicals (Precursor** 

Chemicals)

**DEA List II Chemicals (Essential** 

Chemicals)

Not listed Not listed

Not listed

Not listed

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

SARA 311/312

Classification SKIN IRRITATION - Category 2

SKIN SENSITIZATION - Category 1



# INDUSTRIAL YELLOW

 Version Number 1.0
 Page 17 of 19

 Revision Date 02/25/2019
 Print Date 02/26/2019

#### Composition/information on ingredients

Name	%	Classification
Titanium dioxide	>= 25 - <= 50	CARCINOGENICITY - Category 2
Miscellaneous Compounds	>= 10 - <= 25	Immediate (acute) health hazard
Distillates, petroleum,		
hydrotreated middle		
Distillates (petroleum),	>= 10 - <= 25	FLAMMABLE LIQUIDS - Category 3
hydrotreated light		ACUTE TOXICITY - inhalation - Category 4
		SKIN IRRITATION - Category 2
		ASPIRATION HAZARD - Category 1
Bis (1,2,2,6,6-pentamethyl-	>= 3 - <= 5	SKIN SENSITIZATION - Category 1
4-piperidinyl) sebacate		
Decanedioic acid, methyl	>= 1 - <= 3	SKIN SENSITIZATION - Category 1
1,2,2,6,6-pentamethyl-4-		
piperidinyl ester		

#### **SARA 313**

	Product name	CAS number	%
Form R - Reporting	Aluminum oxide	1344-28-1	1 - 3
requirements			
Supplier notification	Aluminum oxide	1344-28-1	1 - 3

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

**State regulations** 

Massachusetts: None of the components are listed.New York: None of the components are listed.New Jersey: The following components are listed:

Titanium dioxide Aluminum oxide

**Pennsylvania**: The following components are listed:

Titanium dioxide

Aluminum oxide

# California Prop. 65



#### INDUSTRIAL YELLOW

Version Number 1.0 Page 18 of 19
Revision Date 02/25/2019 Print Date 02/26/2019

**WARNING:** This product can expose you to Titanium dioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Titanium dioxide	No.	No.

United States inventory (TSCA 8b) : All components are listed or exempted.

**Canada inventory** : All components are listed or exempted.

#### **International regulations**

#### **Inventory list**

AustraliaAll components are listed or exempted.CanadaAll components are listed or exempted.ChinaAll components are listed or exempted.Europe inventoryAll components are listed or exempted.

Japan : Not determined.

New Zealand: All components are listed or exempted.Philippines: All components are listed or exempted.Republic of Korea: All components are listed or exempted.

Taiwan : Not determined.
Turkey : Not determined.

**United States** : All components are listed or exempted.

# **Section 16. Other information**

#### **Hazardous Material Information System (U.S.A.)**

Health	/	2
Flammability		0
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.



# INDUSTRIAL YELLOW

Version Number 1.0 Page 19 of 19 Revision Date 02/25/2019 Print Date 02/26/2019

**History** 

Date of printing: 02/26/2019Date of issue/Date of revision: 02/25/2019Date of previous issue: 00/00/0000

Version : 1.0

**Key to abbreviations** : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of

Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine

pollution)

UN = United Nations

**References** : Not available.

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.