

MATERIAL SAFETY DATA SHEET

BLUE

Version Number 1.0 Revision Date 04/09/2002 Page 1 of 5 Print Date 11/4/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name Product code Chemical Name CAS-No. Product Use	: : : :	BLUE CC10000401 Mixture Mixture Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See Sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

BLUE

sion Date 04/09/2002	Print Date 11/4/2
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, dry powder, foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption



MATERIAL SAFETY DATA SHEET

BLUE

sion Date 04/09/2002				Print Date 11/4/2	
	a	nd contamination. Keep in	a dry, cool place.		
8. 1	EXPOSURE	CONTROLS / PERSON	AL PROTECTION		
Respiratory protection	: N	: No personal respiratory protective equipment normally required			
Eye/Face Protection	: S	: Safety glasses with side-shields.			
Hand protection	: P	: Protective gloves.			
Skin and body protection	: L	: Long sleeved clothing.			
Additional Protective Measures	: S	: Safety shoes.			
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.				
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
Exposure limit(s)					
Components	Value	Exposure time	Exposure ty	pe List:	
Titanium dioxide	10 mg/m3	Time Weighted Averag (TWA):		1	
Titanium dioxide	15 mg/m3	PEL:	Total dust	. OSHA Z1	
	9. PHYSIC	CAL AND CHEMICAL I	PROPERTIES		
Form	: Solid	l Ev	aporation rate	: Not applicable.	
Appearance	: Pelle		ecific Gravity	: Not determined	
Color	: BLU		lk density	: Not established	
Odor	: Very		Vapor pressure : Not applicabl		
Melting point/range			Vapor density : Not applicabl		
Boiling Point: Water solubility	: Not a : Insol	applicable pH uble	l	: Not applicable	
	10. \$	STABILITY AND REAC	TIVITY		
	: S	table.			
Stability					
Stability Hazardous Polymerizatio		Vill not occur.			
-	n : W : K	Vill not occur. Leep away from oxidizing a ecomposition, do not overl		e. To avoid thermal	



MATERIAL SAFETY DATA SHEET

BLUE

Version Number 1.0 Revision Date 04/09/2002 Page 4 of 5 Print Date 11/4/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ		
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.		
	12. ECOLOGIO	CAL INFORMATION	1		
Persistence and degrad	ability : Not readily b	iodegradable.			
Environmental Toxicity		 Chemicals are not readily available as they are bound within the matrix of the polymer. Chemicals are not readily available as they are bound within the matrix of the polymer. 			
Bioaccumulation Poten					
Additional advice	: No data avail	able.			
	13. DISPOSAL	CONSIDERATIONS	5		
Product Contaminated packagir	possible, recy generator of v classification applicable fee ng : Recycling is p has the respon and disposal	 Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. 			
	14. TRANSPO	RT INFORMATION			
U.S. D.O.T. / CA T.D. Classification (Non-bui ground)	G. : Not regulated	: Not regulated for transportation.			
ICAO/IATA	: Not regulated for transportation.				
IMO / IMDG	: Not regulated	l for transportation.			
	15 DECULATO	ORY INFORMATION	AT .		

MATERIAL SAFETY DATA SHEET



BLUE Version Number 1.0 Page 5 of 5 Print Date 11/4/2011 Revision Date 04/09/2002 US Regulations: **OSHA Status** : Classified as hazardous based on components. **TSCA Status** All components of this product are listed on the TSCA inventory or are : exempt. California Proposition : This product does not contain a substance listed by California Prop 65. 65 Canadian Regulations: WHMIS Classification : D2B DSL : Listed. National Inventories: Australia AICS : Not determined. China IECS Listed. : **Europe EINECS** Not determined. : Japan ENCS Not determined. : Korea KECI Not determined. · Philippines PICCS : Listed.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.