

MATERIAL SAFETY DATA SHEET

030RD393

Version Number 1.1 Revision Date 12/19/2003 Page 1 of 6 Print Date 11/13/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	030RD393
Product code	:	CC10000484
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Quartz	14808-60-7	0.1 - 1
Calcium carbonate	1317-65-3	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Particulates, like other inert materials can be mechanically irritating. Excessive inhalation of product vapors, especially during heating or processing, may be irritating to respiratory system.
Ingestion	: May be harmful if swallowed.
Eyes	: Particulates, like other inert materials can be mechanically irritating.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET **030RD393**

Version Number 1.1 Revision Date 12/19/2003 Page 2 of 6 Print Date 11/13/2011

Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures Unusual Fire/Explosion	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen
Hazards	(NOx), other hazardous materials, and smoke are all possible. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



MATERIAL SAFETY DATA SHEET **030RD393**

sion Date 12/19/2003			Print D	Page 3 ate 11/13/2				
Handling		ake measures to prevent the l nly in areas with appropriate		arge Heat				
Storage		eep containers dry and tightl nd contamination. Keep in a		absorption				
8. F	EXPOSURE	CONTROLS / PERSONAI	L PROTECTION					
Respiratory protection	: N	o personal respiratory protec	tive equipment normally r	equired.				
Eye/Face Protection	: S	afety glasses with side-shield	ls.					
Hand protection	: P	rotective gloves.						
Skin and body protection	: L	ong sleeved clothing.						
Additional Protective Measures	: S	afety shoes.						
General Hygiene Considerations		andle in accordance with goo Vash hands before breaks and		afety practic				
Engineering measures				: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
	-		5					
Exposure limit(s)			5					
	Value	Exposure time		List:				
Exposure limit(s) Components Calcium carbonate		Exposure time PEL:	Exposure type Respirable fraction.					
	Value 5 mg/m3 15 mg/m3		Exposure type	OSHA Z				
Components	5 mg/m3	PEL:	Exposure type Respirable fraction.	OSHA Z				
Components Calcium carbonate	5 mg/m3 15 mg/m3 0.05	PEL: PEL: Time Weighted Average	Exposure type Respirable fraction. Total dust.	OSHA Z OSHA Z ACGIH				
Components Calcium carbonate	5 mg/m3 15 mg/m3 0.05 mg/m3	PEL: PEL: Time Weighted Average (TWA):	Exposure type Respirable fraction. Total dust. Respirable fraction.	OSHA Z OSHA Z ACGIH OSHA Z				
Components Calcium carbonate	5 mg/m3 15 mg/m3 0.05 mg/m3 5 mg/m3 15 mg/m3	PEL: PEL: Time Weighted Average (TWA): PEL:	Exposure type Respirable fraction. Total dust. Respirable fraction. Respirable fraction. Total dust.	OSHA Z OSHA Z ACGIH OSHA Z				
Components Calcium carbonate Quartz	5 mg/m3 15 mg/m3 0.05 mg/m3 5 mg/m3 15 mg/m3	PEL: PEL: Time Weighted Average (TWA): PEL: PEL: CAL AND CHEMICAL PR	Exposure type Respirable fraction. Total dust. Respirable fraction. Respirable fraction. Total dust.	OSHA Z OSHA Z ACGIH OSHA Z				
Components Calcium carbonate Quartz Form	5 mg/m3 15 mg/m3 0.05 mg/m3 5 mg/m3 15 mg/m3 9. PHYSIC	PEL: PEL: Time Weighted Average (TWA): PEL: PEL: CAL AND CHEMICAL PR	Exposure type Respirable fraction. Total dust. Respirable fraction. Respirable fraction. Total dust. OPERTIES oration rate : Not	OSHA Z OSHA Z ACGIH OSHA Z OSHA Z				
Components Calcium carbonate Quartz Form Appearance	5 mg/m3 15 mg/m3 0.05 mg/m3 5 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : RED	PEL: PEL: Time Weighted Average (TWA): PEL: PEL: CAL AND CHEMICAL PR t Evap ts Speci Bulk	Exposure type Respirable fraction. Total dust. Respirable fraction. Respirable fraction. Total dust. OPERTIES oration rate : Not ific Gravity: : Not density : Not	OSHA Z OSHA Z ACGIH OSHA Z OSHA Z				
Components Calcium carbonate Quartz Form Appearance Color Odor	5 mg/m3 15 mg/m3 0.05 mg/m3 5 mg/m3 15 mg/m3 9. PHYSIC : Solic : Pelle : RED : Very	PEL: PEL: Time Weighted Average (TWA): PEL: PEL: CAL AND CHEMICAL PR I Evap ts Speci Bulk faint Vapo	Exposure type Respirable fraction. Total dust. Respirable fraction. Respirable fraction. Total dust. OPERTIES oration rate : Not ific Gravity: : Not density : Not or pressure : Not	OSHA Z OSHA Z ACGIH OSHA Z OSHA Z OSHA Z				
Components Calcium carbonate Quartz Quartz Form Appearance Color Odor Melting point/range	5 mg/m3 15 mg/m3 0.05 mg/m3 5 mg/m3 15 mg/m3 9. PHYSIO : Solici : Pelle : RED : Very : Not of	PEL: PEL: Time Weighted Average (TWA): PEL: PEL: CAL AND CHEMICAL PR t Evap ts Speci Bulk faint Vapo determined Vapo	Exposure type Respirable fraction. Total dust. Respirable fraction. Respirable fraction. Total dust. OPERTIES oration rate : Not ific Gravity: : Not density : Not or pressure : Not wordensity : Not	OSHA ZI OSHA ZI ACGIH OSHA ZI OSHA ZI OSHA ZI applicable determined established applicable applicable				
Components Calcium carbonate Quartz Quartz Form Appearance Color Odor Melting point/range Boiling Point:	5 mg/m3 15 mg/m3 0.05 mg/m3 5 mg/m3 15 mg/m3 9. PHYSIC : Solici : Pelle : RED : Very : Not c : Not a	PEL: PEL: Time Weighted Average (TWA): PEL: PEL: CAL AND CHEMICAL PR L Evap ts Speci Bulk faint Vapo determined Vapo applicable pH	Exposure type Respirable fraction. Total dust. Respirable fraction. Respirable fraction. Total dust. OPERTIES oration rate : Not ific Gravity: : Not density : Not or pressure : Not wordensity : Not	OSHA Z OSHA Z ACGIH OSHA Z OSHA Z OSHA Z				
Components Calcium carbonate Quartz Quartz Form Appearance Color Odor Melting point/range Boiling Point:	5 mg/m3 15 mg/m3 0.05 mg/m3 5 mg/m3 15 mg/m3 9. PHYSIO : Solici : Pelle : RED : Very : Not of	PEL: PEL: Time Weighted Average (TWA): PEL: PEL: CAL AND CHEMICAL PR L Evap ts Speci Bulk faint Vapo determined Vapo applicable pH	Exposure type Respirable fraction. Total dust. Respirable fraction. Respirable fraction. Total dust. OPERTIES oration rate : Not ific Gravity: : Not density : Not or pressure : Not wordensity : Not	OSHA Z OSHA Z ACGIH OSHA Z OSHA Z OSHA Z determined established applicable applicable				
Components Calcium carbonate Quartz Quartz Form Appearance Color Odor Melting point/range Boiling Point:	5 mg/m3 15 mg/m3 0.05 mg/m3 5 mg/m3 15 mg/m3 9. PHYSIC : Solic : Pelle : RED : Very : Not a : Insol	PEL: PEL: Time Weighted Average (TWA): PEL: PEL: CAL AND CHEMICAL PR L Evap ts Speci Bulk faint Vapo determined Vapo applicable pH	Exposure type Respirable fraction. Total dust. Respirable fraction. Respirable fraction. Total dust. OPERTIES oration rate : Not ific Gravity: : Not or pressure : Not wir density : Not : Not	OSHA ZI OSHA ZI ACGIH OSHA ZI OSHA ZI OSHA ZI applicable determined established applicable applicable				
Components Calcium carbonate Quartz Form Appearance Color Odor	5 mg/m3 15 mg/m3 0.05 mg/m3 5 mg/m3 15 mg/m3 9. PHYSIC : Solic : Pelle : RED : Very : Not c : Insol 10. S	PEL: PEL: Time Weighted Average (TWA): PEL: PE	Exposure type Respirable fraction. Total dust. Respirable fraction. Respirable fraction. Total dust. OPERTIES oration rate : Not ific Gravity: : Not or pressure : Not wir density : Not : Not	OSHA ZI OSHA ZI ACGIH OSHA ZI OSHA ZI OSHA ZI applicable determined established applicable applicable				

3/6



MATERIAL SAFETY DATA SHEET 030RD393

Version Number 1.1 Revision Date 12/19/2003		Page 4 of 6 Print Date <i>11/13/2011</i>
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Avoid contact with strong oxidizers. Also, avoid contact with acetal or acetal copolymers and with amine containing materials during processing. At processing conditions, these materials are mutually destructive and involve rapid degradation. Thoroughly purge and mechanically clean processing equipment to avoid even trace quantities of these materials from coming in contact with each other. Prevent cross contamination of feedstocks.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
14808-60-7	Quartz	Systemic effects	Eyes, Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:



MATERIAL SAFETY DATA SHEET 030RD393

Version Number 1.1 Revision Date 12/19/2003 Page 5 of 6 Print Date 11/13/2011

Quartz 14808-60-7 This material in its free releasable form may cause respiratory tract irritation. Long term exposure may cause caughing, chest pain, diminished chest expansion and possibly silicosis which is a scarring of the lungs.

Persistence and degradability	: Not readily biodegradable.	
Environmental Toxicity	: Chemicals are not readily available as they are bound within the ma of the polymer.	tri
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the ma of the polymer.	tri
Additional advice	: No data available	
	13. DISPOSAL CONSIDERATIONS	
Product	: Like most thermoplastic plastics the product can be recycled. Whe possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.	re
Contaminated packaging	: Recycling is preferred when possible. The generator of waste mate has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.	1
	14. TRANSPORT INFORMATION	
U.S. DOT Classification	: Not regulated for transportation.	
ICAO/IATA (air)	: Refer to specific regulation.	
IMO / IMDG (maritime)	: Refer to specific regulation.	
	15. REGULATORY INFORMATION	
US Regulations:		
OSHA Status	: Classified as hazardous based on components.	
TSCA Status	: All components of this product are listed on or exempt from the TS Inventory.	CA
US. EPA CERCLA Hazardous	Substances (40 CFR 302)	
Not applicable		



MATERIAL SAFETY DATA SHEET **030RD393**

Version Number 1.1 Revision Date 12/19/2003			Print Date	Page 6 of 6 11/13/201
California Proposition 65	:	WARNING! This product contains a chemical California to cause cancer.	known to the	e State of
SARA Title III Section 302 Ext	rem	ely Hazardous Substance		
Not applicable				
SARA Title III Section 313 Tox	ic C	Chemicals:		
Not applicable Canadian Regulations:				
National Pollutant Relea	se Iı	nventory (NPRI)		
Not applicable				
WHMIS Classification	:	D2A		
DSL	:	All components of this product are on the Can Substances List (DSL) or are exempt.	adian Domest	tic
National Inventories:				
Australia AICS	:	Listed		
China IECS	:	Listed		
Europe EINECS	:	Not determined		
Japan ENCS	:	Not determined		
Korea KECI	:	Listed		
Philippines PICCS	:	Listed		
		16. OTHER INFORMATION		

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.