

MATERIAL SAFETY DATA SHEET

GREEN 3

Version Number 1.1 Revision Date 10/09/2001 Page 1 of 6 Print Date 11/1/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	GREEN 3
Product code	:	CC10002443
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	1 - 5
Chromium (III) oxide	1308-38-9	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion	Resin particles, like other inert materials, can be mechanically irritating.May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.





REEN 3	
rsion Number 1.1 evision Date 10/09/2001	Page 2 of Print Date 11/1/201
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not relevant Carbon dioxide blanket, water spray, dry powder, foam.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

MATERIAL SAFETY DATA SHEET



GREEN 3

Storage : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place. 8.EXPOSURE CONTROLS / PERSONAL PROTECTION Respiratory protection : No personal respiratory protective equipment normally required. Eye/Face Protection : Safety glasses with side-shields. Hand protection : Protective gloves. Skin and body protection : Long sleeved clothing. Additional Protective : Safety shoes. Measures General Hygiene General Hygiene : Handle in accordance with good industrial hygiene and safety practice Considerations Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) Ormoments Value Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) Ormoments Value Evenosure limit(s) 0.5 mg/m3 Time Weighted Average Total dust. ACGIH PHYSICAL AND CHEMICAL PROPERTIES Form : Solid Evaporation rate : Not applicable. Appearance <t< th=""><th>sion Number 1.1 sion Date 10/09/2001</th><th></th><th></th><th>Print</th><th>Page 3 Date 11/1/2</th></t<>	sion Number 1.1 sion Date 10/09/2001			Print	Page 3 Date 11/1/2
Respiratory protection : No personal respiratory protective equipment normally required. Eye/Face Protection : Safety glasses with side-shields. Hand protection : Protective gloves. Skin and body protection : Long sleeved clothing. Additional Protective : Safety shoes. Measures : Handle in accordance with good industrial hygiene and safety practice. Considerations : Handle in accordance with good industrial hygiene and safety practice. Considerations : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : : Components Value Exposure time Exposure type List: Chromium (III) oxide 0.5 mg/m3 Time Weighted Average Total dust. ACGIH Titanium dioxide 10 mg/m3 Time Weighted Average Total dust. OSHA ZI Solid Evaporation rate : Not applicable. Appearance : : Pell	Storage				e absorption
Eye/Face Protection :: Safety glasses with side-shields. Hand protection :: Protective gloves. Skin and body protection :: Long sleeved clothing. Additional Protective :: Safety shoes. Measures : Handle in accordance with good industrial hygiene and safety practice Considerations : Handle in accordance with good industrial hygiene and safety practice Considerations : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Exposure time Exposure type List: Chromium (III) oxide 0.5 mg/m3 Time Weighted Average as Cr ACGIH Titanium dioxide 10 mg/m3 Time Weighted Average Total dust. OSHA ZI Solid Evaporation rate : Not applicable. Appearance :: PHYSICAL AND CHEMICAL PROPERTIES Form :: Solid Evaporation rate : Not applicable. Appearance :: Pellets Specific Gravity : Not applicable Odor : CREEN	8. I	EXPOSURE	CONTROLS / PERSONAL	PROTECTION	
Hand protection : Protective gloves. Skin and body protection : Long sleeved clothing. Additional Protective : Safety shoes. Measures : Safety shoes. General Hygiene : Handle in accordance with good industrial hygiene and safety practice Considerations Considerations : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : : Exposure time Exposure type List: Chromium (III) oxide 0.5 mg/m3 Time Weighted Average as Cr ACGIH (TWA): : Total dust. ACGIH Titanium dioxide 10 mg/m3 Time Weighted Average Total dust. ACGIH Operance : Solid Evaporation rate : Not applicable. Appearance : Pellets Specific Gravity : Not applicable. Melting point/range : Not applicable. PH : Not applicable. Melting point/range : Not applicable PH : Not applicable. <td< td=""><td>Respiratory protection</td><td>: N</td><td>o personal respiratory protecti</td><td>ve equipment normally</td><td>required.</td></td<>	Respiratory protection	: N	o personal respiratory protecti	ve equipment normally	required.
Skin and body protection : Long sleeved clothing. Additional Protective : Safety shoes. Measures : General Hygiene : Handle in accordance with good industrial hygiene and safety practice Considerations : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Measures : ACGIH (TWA): Components Value Exposure time Exposure type List: Chromium (III) oxide 0.5 mg/m3 Time Weighted Average as Cr ACGIH Titanium dioxide 10 mg/m3 Time Weighted Average Total dust. ACGIH Very faint (TWA): : Total dust. OSHA ZI Persenance : Pellets Specific Gravity : Not applicable. Appearance : Pellets Specific Gravity : Not applicable. Odor : GREEN Bulk density : Not applicable Metting point/range : Not deprlicable pH : Not applicable Water solubility : Insoluble	Eye/Face Protection	: S	afety glasses with side-shields.		
Additional Protective Measures : Safety shoes. Measures : Handle in accordance with good industrial hygiene and safety practice Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Muse Exposure time Exposure type List: Chromium (III) oxide 0.5 mg/m3 Titanium dioxide 10 mg/m3 Time Weighted Average as Cr ACGIH (TWA): Total dust. OSHA ZI PHYSICAL AND CHEMICAL PROPERTIES Form : Solid Appearance : Pellets Specific Gravity : Not applicable. Appearance : Very faint Vapor density : Not applicable Mediting point/range : Not applicable pH : Not applicable Boiling Point: : Not applicable pH : Not applicable Water solubility : Insoluble : Insoluble : Not applicable Hot stabilitity : Insoluble : Not appli	Hand protection	: P:	rotective gloves.		
Measures : Handle in accordance with good industrial hygiene and safety practice Wash hands before breaks and at the end of workday. Engineering measures :: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) :: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) :: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) :: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) :: Meat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) :: Meat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) :: Meat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) :: Meat only in areas with appropriate exhaust ventilation. ACGIH (TWA): Titanium dioxide 10 mg/m3 Time Weighted Average Total dust. ACGIH Other is the mg/m3 :: Meat only in the exposure in the mg/m3 : Meat only in the exposure	Skin and body protection	: L	ong sleeved clothing.		
Considerations Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) Components Value Exposure time Exposure type List: Chromium (III) oxide 0.5 mg/m3 Time Weighted Average as Cr ACGIH (TWA): Total dust. ACGIH (TWA): Total dust. OSHA ZI PHYSICAL AND CHEMICAL PROPERTIES Form : Solid Evaporation rate : Not applicable. Appearance : Pellets Specific Gravity : Not determined. Color : GREEN Bulk density : Not applicable. Melting point/range : Not determined. Vapor pressure : Not applicable Boiling Point: : Not applicable pH : Not applicable Weter solubility : Insoluble : : </td <td></td> <td>: S</td> <td>afety shoes.</td> <td></td> <td></td>		: S	afety shoes.		
appropriate exhaust ventilation at machinery. Exposure limit(s) 					safety practice
Components Value Exposure time Exposure type List: Chromium (III) oxide 0.5 mg/m3 Time Weighted Average as Cr ACGIH Titanium dioxide 10 mg/m3 Time Weighted Average Total dust. ACGIH Titanium dioxide 10 mg/m3 Time Weighted Average Total dust. ACGIH (TWA): 15 mg/m3 PEL: Total dust. OSHA ZI 9. PHYSICAL AND CHEMICAL PROPERTIES Form : Solid Evaporation rate : Not applicable. Appearance : Pellets Specific Gravity : Not determined. Color : GREEN Bulk density : Not established Odor : Very faint Vapor pressure : Not applicable Boiling point/range : Not applicable pH : Not applicable Water solubility : Insoluble : Not applicable Not applicable Hazardous Polymerization : Will not occur. : Will not occur. :	Engineering measures				Provide
Chromium (III) oxide 0.5 mg/m3 Time Weighted Average (TWA): as Cr ACGIH Titanium dioxide 10 mg/m3 Time Weighted Average (TWA): Total dust. ACGIH Titanium dioxide 10 mg/m3 Time Weighted Average (TWA): Total dust. ACGIH 15 mg/m3 PEL: Total dust. OSHA Z1 9. PHYSICAL AND CHEMICAL PROPERTIES Form : Solid Evaporation rate : Not applicable. Appearance : Pellets Specific Gravity : Not determined. Color : GREEN Bulk density : Not established Odor : Very faint Vapor pressure : Not applicable Melting point/range : Not determined. Vapor density : Not applicable Boiling Point: : Not applicable pH : Not applicable Meter solubility : Insoluble : Not applicable : Mater solubility : Insoluble : Not applicable : 10. STABILITY AND REACTIVITY <th>Exposure limit(s)</th> <th></th> <th></th> <th></th> <th></th>	Exposure limit(s)				
Chromium (III) oxide 0.5 mg/m3 Time Weighted Average (TWA): as Cr ACGIH Titanium dioxide 10 mg/m3 Time Weighted Average (TWA): Total dust. ACGIH Itanium dioxide 10 mg/m3 Time Weighted Average (TWA): Total dust. ACGIH Itanium dioxide 15 mg/m3 PEL: Total dust. OSHA ZI PHYSICAL AND CHEMICAL PROPERTIES Form : Solid Evaporation rate : Not applicable. Appearance : Pellets Specific Gravity : Not determined. Color : GREEN Bulk density : Not applicable Melting point/range : Not determined. Vapor pressure : Not applicable Boiling Point: : Not applicable pH : Not applicable Water solubility : Insoluble Insoluble Insoluble Stabil. Hazardous Polymerization : Will not occur. : Will not occur.	Components	Value	Exposure time	Exposure type	List:
Image: constraint of the system of the sy		0.5 mg/m3	Time Weighted Average		ACGIH
Image: Instant Stability Image: I	Titanium dioxide	10 mg/m3	• •	Total dust.	ACGIH
Form : Solid Evaporation rate : Not applicable. Appearance : Pellets Specific Gravity : Not determined. Color : GREEN Bulk density : Not established Odor : Very faint Vapor pressure : Not applicable Melting point/range : Not determined. Vapor density : Not applicable Boiling Point: : Not applicable pH : Not applicable Water solubility : Insoluble Insoluble Insoluble Iteration Hazardous Polymerization : Will not occur.		15 mg/m3		Total dust.	OSHA Z1
Form : Solid Evaporation rate : Not applicable. Appearance : Pellets Specific Gravity : Not determined. Color : GREEN Bulk density : Not established Odor : Very faint Vapor pressure : Not applicable Melting point/range : Not determined. Vapor density : Not applicable Boiling Point: : Not applicable pH : Not applicable Water solubility : Insoluble Insoluble Insoluble Iteration Hazardous Polymerization : Will not occur.		9. PHYSI(CAL AND CHEMICAL PRO	PERTIES	
Appearance:PelletsSpecific Gravity:Not determined.Color:GREENBulk density:Not establishedOdor:Very faintVapor pressure:Not applicableMelting point/range:Not determined.Vapor density:Not applicableBoiling Point::Not applicablepH:Not applicableWater solubility:Insoluble:StabilityHazardous Polymerization:Will not occur.					
Color:GREENBulk density:Not establishedOdor:Very faintVapor pressure:Not applicableMelting point/range:Not determined.Vapor density:Not applicableBoiling Point::Not applicablepH:Not applicableWater solubility:InsolubleInsoluble:					
Odor: Very faintVapor pressure: Not applicableMelting point/range: Not determined.Vapor density: Not applicableBoiling Point:: Not applicablepH: Not applicableWater solubility: InsolubleInsolubleIO. STABILITY AND REACTIVITYStabilityHazardous Polymerization: Will not occur.	11				
Melting point/range : Not determined. Vapor density : Not applicable Boiling Point: : Not applicable pH : Not applicable Water solubility : Insoluble Insoluble : Not applicable Stability : Stable. Hazardous Polymerization : Will not occur. : Will not occur.					
Boiling Point: : Not applicable pH : Not applicable Water solubility : Insoluble : Insoluble : Insoluble IO. STABILITY AND REACTIVITY Stability : Stable. Hazardous Polymerization : Will not occur.					
Water solubility : Insoluble 10. STABILITY AND REACTIVITY Stability : Stable. Hazardous Polymerization : Will not occur.			1		
Stability:Stable.Hazardous Polymerization:Will not occur.					uppneuoie
Hazardous Polymerization : Will not occur.		10. S	TABILITY AND REACTIV	TTY	
	Stability	: S	table.		
Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal	Hazardous Polymerizatio	n : W	ill not occur.		
			· · · · · · · · · · · · · · · · · · ·	ts and open flame. To	woid thormal



MATERIAL SAFETY DATA SHEET

sion Date 10/09/2001			Page / Print Date 11/1/
	decomposition	a, do not overheat.	
Incompatible Materials	: Incompatible v	with strong acids and o	oxidizing agents.
Hazardous decomposition products			oxide (CO), oxides of nitrogen and smoke are all possible.
	11. TOXICOLOG	ICAL INFORMATIO	ON
health data for the individuation the individuation the second structure	al components which co	mprise the mixture.	are effects listed are based on ex have the following characteristi
-		-	
CAS-No. 13463-67-7 Tit	Chemical Name anium dioxide	Effect Systemic effects	Target OrganRespiratory system.
			N
	12. ECOLOGIC	AL INFORMATION	I
Persistence and degradabili	ty : Not readily bio	1 1 1 1	
-	.,	odegradable.	
Environmental Toxicity		not readily available a	s they are bound within the matr
-	: Chemicals are of the polymer	not readily available a not readily available a	is they are bound within the matrices they are bound within the matrices they are bound within the matrices.
Environmental Toxicity	 Chemicals are of the polymer Chemicals are 	not readily available a not readily available a	
Environmental Toxicity Bioaccumulation Potential	 Chemicals are of the polyment Chemicals are of the polyment No data availa 	not readily available a not readily available a	s they are bound within the matri
Environmental Toxicity Bioaccumulation Potential Additional advice	 Chemicals are of the polymer Chemicals are of the polymer Chemicals are of the polymer No data availa 13. DISPOSAL Like most ther recycling is pr waste material transportation 	not readily available a not readily available a ble. CONSIDERATIONS moplastics the produc eferred to disposal or	ts they are bound within the matrices they are bound within the matrices the second state of the second state of the generator of the generator of the second state of
Environmental Toxicity Bioaccumulation Potential	 Chemicals are of the polymer Chemicals are of the polymer Chemicals are of the polymer No data availa 13. DISPOSAL Like most ther recycling is pr waste material transportation state/provincia Recycling is pr has the respondent 	not readily available a not readily available a the not re	ts they are bound within the matrices they are bound within the matrices the second state of the second state of the generator of the generator of the second state of
Environmental Toxicity Bioaccumulation Potential Additional advice Product	 Chemicals are of the polymer Chemicals are of the polymer Chemicals are of the polymer No data availa 13. DISPOSAL Like most ther recycling is pr waste material transportation state/provincia Recycling is pr has the respon and disposal in and local regular 	not readily available a not readily available a the not re	ts they are bound within the matrices they are bound within the matrices to can be recycled. Where possibility incineration. The generator of for proper waste classification, lance with applicable federal, s. e. The generator of waste materi te classification, transportation



MATERIAL SAFETY DATA SHEET

ion Number 1.1 sion Date 10/09/2001			Page Print Date 11/1
Classification (Non-bulk ground)			
ICAO/IATA	: Not regulate	ed for transportation.	
IMO / IMDG	: Not regulate	ed for transportation.	
	15. REGULAT	ORY INFORMATIC	ON
US Regulations:			
OSHA Status	: Classified a	s hazardous based on c	components.
TSCA Status	: All compon exempt.	ents of this product are	listed on the TSCA inventory or a
California Proposition 65	: This produc	t does not contain a sul	bstance listed by California Prop (
SARA Title III Section 313 To	oxic Chemicals:		
Chemical Nam CHROMIUM	e III COMPOUNDS	CAS-No. 1308-38-9	Weight % 12.34
Canadian Regulations:			
WHMIS Classification	1 : D2B		
WHMIS Ingredient Dis	sclosure List		
CAS-No. 1308-38-9			
DSL	: Listed.		
National Inventories:			
Australia AICS	: Not determine	ned.	
China IECS	: Not determine	ned.	
Europe EINECS	: Not determi	ned.	
Japan ENCS	: Not determi	ned.	
Korea KECI	: Not determi	ned.	
Philippines PICCS	: Not determi	ned.	
		R INFORMATION	

MATERIAL SAFETY DATA SHEET



GREEN 3

Version Number 1.1 Revision Date 10/09/2001 Page 6 of 6 Print Date 11/1/2011

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.