

MATERIAL SAFETY DATA SHEET

FILM PUDDY

Version Number 1.0 Revision Date 10/23/2001 Page 1 of 5 Print Date 11/1/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

| NON-EMERGENCY TELEPHONE | : | Product Stewardship (770) 271-5902 |
|-------------------------------|---|--|
| Emergency telephone number | : | CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident). |
| Product name | : | FILM PUDDY |
| Product code | : | CC10002953 |
| Chemical Name | : | Mixture |
| CAS-No. | : | Mixture |
| Product Use | : | Industrial Applications |

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

| Components | CAS-No. | Weight % |
|------------------|------------|----------|
| Titanium dioxide | 13463-67-7 | 10 - 30 |

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

| Routes of Exposure: | : Inhalation, Ingestion, Skin contact |
|---|---|
| Acute exposure | |
| Inhalation Ingestion Eyes | Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes. |
| Skin | : Experience shows no unusual dermatitis hazard from routine handling. |
| Chronic exposure Medical Conditions Aggravated by Exposure: | Refer to Section 11 for Toxicological Information.None known. |



MATERIAL SAFETY DATA SHEET

FILM PUDDY

| ision Date 10/23/2001 | Print Date 11/1/2 |
|--|---|
| | 4. FIRST AID MEASURES |
| Inhalation | : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice. |
| Ingestion | : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice. |
| Eyes | : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention. |
| Skin | : Wash off with soap and plenty of water. If skin irritation persists seel medical attention. |
| | 5. FIRE-FIGHTING MEASURES |
| Flash point | : Not applicable |
| Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media | Not applicable Not applicable Not relevant Carbon dioxide blanket, water spray, dry powder, foam. |
| Special Fire Fighting Procedures Unusual Fire/Explosion Hazards | Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None |
| | 6. ACCIDENTAL RELEASE MEASURES |
| Personal precautions | : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. |
| Environmental precautions | : Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil. |
| Methods for cleaning up | : Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods. |
| | 7. HANDLING AND STORAGE |
| Handling | : Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. |
| Storage | : Keep containers dry and tightly closed to avoid moisture absorption |



MATERIAL SAFETY DATA SHEET

FILM PUDDY

| RE CONT No perso Safety g Protectiv Long sle Safety sl Handle i Wash ha Heat onl appropri | in accordance with ands before breaks ly in areas with ap iate exhaust ventil Exposure time ne Weighted Aver (TWA): PEL: | DNAL PROTEC protective equipm shields. h good industrial s and at the end of ppropriate exhau lation at machine rage To | TION hent normally hygiene and of workday. st ventilation | safety practic |
|--|---|--|---|--|
| No perso Safety g Protectiv Long sle Safety sl Handle i Wash ha Heat onl appropri | sonal respiratory p glasses with side-s ive gloves. eeved clothing. shoes. in accordance with ands before breaks ily in areas with ap iate exhaust ventil <u>Exposure time</u> ne Weighted Aver (TWA): PEL: | brotective equipm shields. h good industrial s and at the end of ppropriate exhau lation at machine <u>Expo</u> rage To | hygiene and of workday. st ventilation ery. | safety practic . Provide List: ACGIH |
| Safety g Protectiv Long sle Safety sl Handle i Wash ha Heat onl appropri | glasses with side-s ive gloves. eeved clothing. shoes. in accordance with ands before breaks ily in areas with ap- riate exhaust ventil <u>Exposure time</u> ne Weighted Aver (TWA): PEL: | h good industrial s and at the end of ppropriate exhau lation at machine <u>Expo</u> age To | hygiene and of workday. st ventilation ery. osure type tal dust. | safety practic . Provide List: ACGIH |
| Protectiv Long sle Safety sl Handle i Wash ha Heat onl appropri | ive gloves. eeved clothing. shoes. in accordance with ands before breaks ily in areas with ap- riate exhaust ventil <u>Exposure time</u> ne Weighted Aver (TWA): PEL: | h good industrial s and at the end o ppropriate exhau lation at machine <u>Expo</u> rage To | of workday. st ventilation ery. osure type tal dust. | List: |
| Long sle Safety sl Handle i Wash ha Heat onl appropri | eeved clothing. shoes. in accordance with ands before breaks ily in areas with ap iate exhaust ventil Exposure time ne Weighted Aver (TWA): PEL: | s and at the end oppropriate exhau lation at machine Expo rage To | of workday. st ventilation ery. osure type tal dust. | List: |
| Safety sl Handle i Wash ha Heat onl appropri | shoes. in accordance with ands before breaks ily in areas with ap iate exhaust ventil Exposure time ne Weighted Aver (TWA): PEL: | s and at the end oppropriate exhau lation at machine Expo rage To | of workday. st ventilation ery. osure type tal dust. | List: |
| Handle i Wash ha Heat onl appropri | in accordance with ands before breaks ly in areas with ap iate exhaust ventil Exposure time ne Weighted Aver (TWA): PEL: | s and at the end oppropriate exhau lation at machine Expo rage To | of workday. st ventilation ery. osure type tal dust. | List: |
| Wash ha Heat onl appropri n3 Tim | ands before breaks ily in areas with ap riate exhaust ventil <u>Exposure time</u> ne Weighted Aver (TWA): PEL: | s and at the end oppropriate exhau lation at machine Expo rage To | of workday. st ventilation ery. osure type tal dust. | List: |
| appropri | Exposure time ne Weighted Aver (TWA): PEL: | lation at machine Expo rage To | ery. Desure type tal dust. | List: ACGIH |
| n3 Tim n3 | ne Weighted Aver (TWA): PEL: | rage To | tal dust. | ACGIH |
| n3 | (TWA): PEL: | 0 | | |
| | | То | tal dust. | |
| SICAT A | | | | USIIA Z |
| SICAL A | AND CHEMICAL | L PROPERTIE | S | |
| | letsSpecifiEYBulk dry faintVaport determined.Vaport applicablepH | | ration rate : Not applicable. c Gravity : Not determined. ensity : Not established pressure : Not applicable density : Not applicable : Not applicable | |
| 0 STARI | ILITY AND REA | CTIVITY | | |
| | | | | |
| | | | | |
| Will not | t occur. | | | |
| - | • | | en flame. To | avoid therma |
| Incompa | atible with strong | acids and oxidiz | ing agents. | |
| | Stable. Will no Keep av decomp | Stable. Will not occur. Keep away from oxidizin decomposition, do not ov | Will not occur. Keep away from oxidizing agents and ope decomposition, do not overheat. | Stable. Will not occur. Keep away from oxidizing agents and open flame. To |



MATERIAL SAFETY DATA SHEET

FILM PUDDY

Version Number 1.0 Revision Date 10/23/2001 Page 4 of 5 Print Date 11/1/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

| CAS-No. | Chemical Name | Effect | Target Organ | | | |
|---|--|---|---------------------|--|--|--|
| 13463-67-7 | Titanium dioxide | Systemic effects | Respiratory system. | | | |
| | 12. ECOLOGIO | CAL INFORMATION | 1 | | | |
| Persistence and degrade | ability : Not readily b | iodegradable. | | | | |
| Environmental Toxicity | | Chemicals are not readily available as they are bound within the matrix of the polymer. Chemicals are not readily available as they are bound within the matrix of the polymer. | | | | |
| Bioaccumulation Poten | | | | | | |
| Additional advice | : No data avail | able. | | | | |
| | 13. DISPOSAL | CONSIDERATIONS | | | | |
| Product Contaminated packagir | recycling is p waste materia transportation state/provinci ng : Recycling is p has the respon and disposal | Like most thermoplastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. | | | | |
| | 14. TRANSPO | RT INFORMATION | | | | |
| U.S. D.O.T. / CA T.D. Classification (Non-bui ground) | G. : Not regulated | : Not regulated for transportation. | | | | |
| ICAO/IATA | : Not regulated | l for transportation. | | | | |
| IMO / IMDG | : Not regulated | l for transportation. | | | | |
| | 15 DECULATO | ORY INFORMATION | T | | | |

MATERIAL SAFETY DATA SHEET



FILM PUDDY Version Number 1.0 Page 5 of 5 Print Date 11/1/2011 Revision Date 10/23/2001 US Regulations: **OSHA Status** : Classified as hazardous based on components. **TSCA Status** All components of this product are listed on the TSCA inventory or are : exempt. California Proposition : This product does not contain a substance listed by California Prop 65. 65 Canadian Regulations: WHMIS Classification : D2B WHMIS Ingredient Disclosure List CAS-No. 1333-86-4 1309-37-1 68186-90-3 DSL : Listed. National Inventories: Australia AICS Listed. China IECS : Listed. Europe EINECS Not determined. : Japan ENCS Not determined. : Korea KECI Listed. : **Philippines PICCS** Not determined. :

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.