

MATERIAL SAFETY DATA SHEET

DARK AMBER

Version Number 1.0 Revision Date 10/12/2001 Page 1 of 6 Print Date 11/1/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	DARK AMBER
Product code	:	CC10003254
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Carbon black	1333-86-4	0.1 - 1
Iron oxide	1309-37-1	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed.
Eyes	 Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.





DARK AMBER Version Number 1.0 Page 2 of 6 Revision Date 10/12/2001 Print Date 11/1/2011 **Medical Conditions** : None known. Aggravated by Exposure: 4. FIRST AID MEASURES Move to fresh air in case of accidental inhalation of fumes from Inhalation overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice. Do not induce vomiting without medical advice. When symptoms Ingestion : persist or in all cases of doubt seek medical advice. Eyes : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention. Skin : Wash off with soap and plenty of water. If skin irritation persists seek medical attention. **5. FIRE-FIGHTING MEASURES** Flash point : Not applicable Flammable Limits Upper explosion limit Not applicable : Lower explosion limit Not applicable : Autoignition temperature Not relevant : Suitable extinguishing media : Carbon dioxide blanket, water spray, dry powder, foam. Special Fire Fighting Fullface self-contained breathing apparatus (SCBA) used in positive : Procedures pressure mode should be worn to prevent inhalation of airborne contaminants. Unusual Fire/Explosion None • Hazards 6. ACCIDENTAL RELEASE MEASURES Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. Environmental precautions Should not be released into the environment. The product should not : be allowed to enter drains, water courses or the soil. Methods for cleaning up Clean up promptly by sweeping or vacuum. Package all material in : plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods. 7. HANDLING AND STORAGE Handling Take measures to prevent the build up of electrostatic charge. Heat · only in areas with appropriate exhaust ventilation.

MATERIAL SAFETY DATA SHEET





ARK AMBER				
sion Number 1.0 vision Date 10/12/2001			Print	Page 3 c Date 11/1/20
Storage		eep containers dry and tightly on the contamination. Keep in a dr		e absorption
8.1	EXPOSURE	CONTROLS / PERSONAL I	PROTECTION	
Respiratory protection	: N	o personal respiratory protectiv	e equipment normally	required.
Eye/Face Protection	: S	afety glasses with side-shields.		
Hand protection	: P	rotective gloves.		
Skin and body protection	: L	ong sleeved clothing.		
Additional Protective Measures	: S	afety shoes.		
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.			
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.			
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Carbon black	3.5 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH
	3.5 mg/m3	PEL:	Total dust.	OSHA Z1
Iron oxide	5 mg/m3	Time Weighted Average (TWA):	as Fe	ACGIH
	10 mg/m3	PEL:	Fume.	OSHA Z1
	9. PHYSIC	CAL AND CHEMICAL PRO	PERTIES	
Form	: Solid	l Evapor	ation rate : No	t applicable.
Appearance	· Dollo	-		t determined

- Appearance Color Odor Melting point/range Boiling Point: Water solubility
- : Pellets : BROWN : Very faint : Not determined. : Not applicable : Insoluble
- Specific Gravity Bulk density Vapor pressure Vapor density pН
- : Not determined. : Not established : Not applicable
 - : Not applicable : Not applicable
- **10. STABILITY AND REACTIVITY**

Stability

: Stable.

Hazardous Polymerization

: Will not occur.



MATERIAL SAFETY DATA SHEET

DARK AMBER

Version Number 1.0 Revision Date 10/12/2001		Page 4 of 6 Print Date <i>11/1/2011</i>
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.
1309-37-1	Iron oxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1333-86-4	Carbon black	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:



MATERIAL SAFETY DATA SHEET

DARK AMBER

Version Number 1.0	Page 5 of 6
Revision Date 10/12/2001	Print Date 11/1/2011

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: Not regulated for transportation.
ICAO/IATA	: Not regulated for transportation.
IMO / IMDG	: Not regulated for transportation.
	15. REGULATORY INFORMATION
US Regulations:	



MATERIAL SAFETY DATA SHEET

DARK AMBER	
Version Number 1.0 Revision Date 10/12/2001	Page 6 of 6 Print Date <i>11/1/2011</i>
OSHA Status :	Classified as hazardous based on components.
TSCA Status :	All components of this product are listed on the TSCA inventory or are exempt.
California Proposition : 65	This product does not contain a substance listed by California Prop 65.
Canadian Regulations:	
WHMIS Classification :	D2A
WHMIS Ingredient Disclos	ure List
CAS-No. 1333-86-4 1309-37-1 150-13-0	
DSL :	Listed.
National Inventories:	
Australia AICS :	Listed.
China IECS :	Listed.
Europe EINECS :	Not determined.
Japan ENCS :	Listed.
Korea KECI :	Listed.
Philippines PICCS :	Listed.
	16. OTHER INFORMATION
The information provided in this S	afety Data Sheet is correct to the best of our knowledge, information and

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.