

MATERIAL SAFETY DATA SHEET

WISK RED MULTI

Version Number 1.0 Revision Date 10/26/2001 Page 1 of 5 Print Date 11/1/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	WISK RED MULTI
Product code	:	CC10003263
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

WISK RED MULTI

Version Number 1.0 Page 2 of 5 Revision Date 10/26/2001 Print Date 11/1/2011 **4. FIRST AID MEASURES** Inhalation Move to fresh air in case of accidental inhalation of fumes from ÷ overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice. Ingestion Do not induce vomiting without medical advice. When symptoms : persist or in all cases of doubt seek medical advice. Eyes Rinse immediately with plenty of water, also under the eyelids, for at : least 15 minutes. If eye irritation persists, seek medical attention. Skin Wash off with soap and plenty of water. If skin irritation persists seek : medical attention. **5. FIRE-FIGHTING MEASURES** Flash point Not applicable : Flammable Limits Upper explosion limit Not applicable : Lower explosion limit Not applicable : Autoignition temperature Not relevant : Carbon dioxide blanket, water spray, dry powder, foam. Suitable extinguishing media : Special Fire Fighting Fullface self-contained breathing apparatus (SCBA) used in positive : Procedures pressure mode should be worn to prevent inhalation of airborne contaminants. Unusual Fire/Explosion None · Hazards 6. ACCIDENTAL RELEASE MEASURES Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. Environmental precautions Should not be released into the environment. The product should not : be allowed to enter drains, water courses or the soil. Clean up promptly by sweeping or vacuum. Package all material in Methods for cleaning up : plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods. 7. HANDLING AND STORAGE Handling Take measures to prevent the build up of electrostatic charge. Heat : only in areas with appropriate exhaust ventilation. Storage Keep containers dry and tightly closed to avoid moisture absorption ·



MATERIAL SAFETY DATA SHEET

V

sion Number 1.0				Page 3	
vision Date 10/26/2001			Print	Date 11/1/2	
	ar	nd contamination. Keep in a d	rv, cool place.		
		ľ			
8. E	XPOSURE	CONTROLS / PERSONAL	PROTECTION		
Respiratory protection	: N	o personal respiratory protection	ve equipment normally	required.	
Eye/Face Protection	: Safety glasses with side-shields.				
Hand protection	: Protective gloves.				
Skin and body protection	: Long sleeved clothing.				
Additional Protective Measures	: Sa	afety shoes.			
General Hygiene Considerations		andle in accordance with good ash hands before breaks and a		safety practice.	
Engineering measures		eat only in areas with appropr ppropriate exhaust ventilation		Provide	
Engineering measures Exposure limit(s)				Provide	
0				Provide List:	
Exposure limit(s)	aı	Exposure time Time Weighted Average	at machinery.		
Exposure limit(s) Components	aj Value	ppropriate exhaust ventilation Exposure time	at machinery. Exposure type	List:	
Exposure limit(s) Components	ap Value 10 mg/m3 15 mg/m3	Exposure time Time Weighted Average (TWA):	at machinery. Exposure type Total dust. Total dust.	List: ACGIH	
Exposure limit(s) Components Titanium dioxide	ap Value 10 mg/m3 15 mg/m3 9. PHYSIC	Exposure time Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO	at machinery. Exposure type Total dust. Total dust. DPERTIES	List: ACGIH OSHA Z1	
Exposure limit(s) Components Titanium dioxide Form	ap Value 10 mg/m3 15 mg/m3 9. PHYSIC : Solid	Exposure time Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PR(Evapo	at machinery. Exposure type Total dust. Total dust. DPERTIES ration rate : No	List: ACGIH OSHA Z1 t applicable.	
Exposure limit(s) Components Titanium dioxide Form Appearance	ap Value 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle	Exposure time Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO I Evapo ts Specifi	at machinery. Exposure type Total dust. Total dust. DPERTIES ration rate : No ic Gravity : No	List: ACGIH OSHA Z1 t applicable. t determined.	
Exposure limit(s) Components Titanium dioxide Form Appearance Color	Value 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : RED	Exposure time Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRC I Evapo ts Specif Bulk d	at machinery. Exposure type Total dust. Total dust. DPERTIES ration rate : No ic Gravity : No lensity : No	List: ACGIH OSHA Z1 t applicable. t determined. t established	
Exposure limit(s) Components Titanium dioxide Form Appearance Color Odor	Value 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : RED : Very	Exposure time Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRC I Evapo ts Specif Bulk d faint Vapor	at machinery. Exposure type Total dust. Total dust. DPERTIES ration rate : No ic Gravity : No lensity : No pressure : No	List: ACGIH OSHA Z1 t applicable. t determined. t established t applicable	
Exposure limit(s) Components Titanium dioxide Form Appearance Color	Value 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : RED : Very : Not c	Exposure time Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRC I Evapo ts Specif Bulk d faint Vapor	at machinery. Exposure type Total dust. Total dust. DPERTIES ration rate : No ic Gravity : No lensity : No pressure : No density : No	List: ACGIH OSHA Z1 t applicable. t determined. t established	

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.



MATERIAL SAFETY DATA SHEET

WISK RED MULTI

Version Number 1.0 Revision Date 10/26/2001 Page 4 of 5 Print Date 11/1/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ			
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.			
	12. ECOLOGIO	CAL INFORMATION	I			
Persistence and degrada	ability : Not readily b	iodegradable.				
Environmental Toxicity		: Chemicals are not readily available as they are bound within the matrix of the polymer.				
Bioaccumulation Poten		: Chemicals are not readily available as they are bound within the matrix of the polymer.				
Additional advice	: No data avail	: No data available.				
	13. DISPOSAL	CONSIDERATIONS				
Product Contaminated packagin	recycling is p waste materia transportation state/provinci g : Recycling is p has the respo	 Like most thermoplastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. 				
		RT INFORMATION				
U.S. D.O.T. / CA T.D. Classification (Non-bul ground)	G. : Not regulated	l for transportation.				
ICAO/IATA	: Not regulated	l for transportation.				
IMO / IMDG	: Not regulated	l for transportation.				
	15 RECHLAT	ORY INFORMATION	J			

MATERIAL SAFETY DATA SHEET





Version Number 1.0 Revision Date 10/26/2001		Page 5 of 5 Print Date 11/1/2011
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on the TSCA inventory or are exempt.
California Proposition 65	:	This product does not contain a substance listed by California Prop 65.
Canadian Regulations:		
WHMIS Classification	:	D2B
DSL	:	Listed.
National Inventories:		
Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Not determined.
Japan ENCS	:	Listed.
Korea KECI	:	Listed.
Philippines PICCS	:	Not determined.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.