

MATERIAL SAFETY DATA SHEET

PURPLE 2665C

Version Number 1.0 Revision Date 10/16/2001 Page 1 of 5 Print Date 11/1/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PURPLE 2665C
Product code	:	CC10003306
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes. 		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		
Medical Conditions Aggravated by Exposure:	: None known.		



MATERIAL SAFETY DATA SHEET

PURPLE 2665C

sion Date 10/16/2001	Print Date 11/1/2
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not relevant Carbon dioxide blanket, water spray, dry powder, foam.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption



MATERIAL SAFETY DATA SHEET

PURPLE 2665C

ision Date 10/16/2001			Print	Page 3 Date 11/1/2	
	aı	nd contamination. Keep in a c	lry, cool place.		
8. E	XPOSURE	CONTROLS / PERSONAL	PROTECTION		
Respiratory protection	: N	o personal respiratory protect	ive equipment normally	required.	
Eye/Face Protection	: S	afety glasses with side-shields	5.		
Hand protection	: P	rotective gloves.			
Skin and body protection	: L	ong sleeved clothing.			
Additional Protective Measures	: Safety shoes.				
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.				
Engineering measures		leat only in areas with appropription propriate exhaust ventilation		Provide	
Exposure limit(s)					
	TT 1	- ·		1 . .,	
Components	Value	Exposure time	Exposure type	List:	
Components Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH	
		Time Weighted Average			
	10 mg/m3 15 mg/m3	Time Weighted Average (TWA):	Total dust. Total dust.	ACGIH	
Titanium dioxide	10 mg/m3 15 mg/m3 9. PHYSIC	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO	Total dust. Total dust.	ACGIH OSHA Z1	
Titanium dioxide	10 mg/m3 15 mg/m3 9. PHYSIC : Solid	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO	Total dust. Total dust. DPERTIES oration rate : Not	ACGIH OSHA Z1 applicable.	
Titanium dioxide	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO I Evapo Its Specifi	Total dust. Total dust. DPERTIES oration rate : Not Fic Gravity : Not	ACGIH OSHA Z1 applicable. determined.	
Titanium dioxide Form Appearance Color	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : PUR	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO the Evapo sts Specif PLE Bulk of	Total dust. Total dust. DPERTIES oration rate : Not fic Gravity : Not lensity : Not	ACGIH OSHA Z1 applicable. determined. established	
Titanium dioxide Form Appearance Color Odor	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : PUR : Very	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO E Evapo the Evapo the Specif PLE Bulk of faint Vapor	Total dust. Total dust. DPERTIES oration rate : Not fic Gravity : Not lensity : Not pressure : Not	ACGIH OSHA Z1 applicable. determined. established applicable	
Titanium dioxide Titanium dioxide Form Appearance Color Odor Melting point/range	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : PUR : Very : Not c	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO the Evapor the Evapor	Total dust. Total dust. OPERTIES oration rate : Not Tic Gravity : Not lensity : Not oressure : Not ordensity : Not ordensity : Not	ACGIH OSHA Z1 applicable. determined. established applicable applicable	
Titanium dioxide Form Appearance Color Odor	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : PUR : Very : Not c	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO t Evapor ts Specif PLE Bulk of faint Vapor determined. Vapor applicable pH	Total dust. Total dust. OPERTIES oration rate : Not Tic Gravity : Not lensity : Not oressure : Not ordensity : Not ordensity : Not	ACGIH OSHA Z1 applicable. determined. established applicable	
Titanium dioxide Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point:	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : PUR : Very : Not a : Insol	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO t Evapor ts Specif PLE Bulk of faint Vapor determined. Vapor applicable pH	Total dust. Total dust. DPERTIES oration rate : Not cic Gravity : Not ensity : Not of density : Not : Not : Not	ACGIH OSHA Z1 applicable. determined. established applicable applicable	
Titanium dioxide Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point:	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : PUR : Very : Not c : Insol 10. S	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO I Evapo ets Specif PLE Bulk of faint Vapor determined. Vapor applicable pH uble Uble	Total dust. Total dust. DPERTIES oration rate : Not cic Gravity : Not ensity : Not of density : Not : Not : Not	ACGIH OSHA Z1 applicable. determined. established applicable applicable	
Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : PUR : Very : Not c : Not a : Insol 10. S : Si	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO Metric Specifies PLE Bulk of faint Vapor determined. Vapor applicable pH uble	Total dust. Total dust. DPERTIES oration rate : Not cic Gravity : Not ensity : Not of density : Not : Not : Not	ACGIH OSHA Z1 applicable. determined. established applicable applicable	
Titanium dioxide Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point: Water solubility Stability	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : PUR : Very : Not c : Not a : Insol 10. S 10. S 1 . Si . Si . Si . Si	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO I Evapor tas Specif PLE Bulk of faint Vapor determined. Vapor applicable pH uble STABILITY AND REACTIV table.	Total dust. Total dust. OPERTIES oration rate : Not fic Gravity : Not oressure : Not of density : Not virty : Not virty : Not virty : Not	ACGIH OSHA Z1 applicable. determined. established applicable applicable applicable	



MATERIAL SAFETY DATA SHEET

PURPLE 2665C

Version Number 1.0 Revision Date 10/16/2001

Page 4 of 5 Print Date 11/1/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ			
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.			
	12. ECOLOGI	CAL INFORMATION	1			
Persistence and degrad	ability : Not readily b	viodegradable.				
Environmental Toxicit		: Chemicals are not readily available as they are bound within the matrix of the polymer.				
Bioaccumulation Poter		: Chemicals are not readily available as they are bound within the matrix of the polymer.				
Additional advice	: No data avai	lable.				
	13. DISPOSAL	CONSIDERATIONS				
Product Contaminated packagin	recycling is p waste materi transportation state/provinc ng : Recycling is has the respo and disposal	: Like most thermoplastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.				
	14. TRANSPO	ORT INFORMATION				
U.S. D.O.T. / CA T.D. Classification (Non-bu ground)	G. : Not regulated	d for transportation.				
ICAO/IATA	: Not regulated	d for transportation.				
IMO / IMDG	: Not regulated	d for transportation.				
	15 RECHLAT	ORY INFORMATION	T			

MATERIAL SAFETY DATA SHEET



PURPLE 2665C

	Page 5 of 5 Print Date 11/1/2011
:	Classified as hazardous based on components.
:	All components of this product are listed on the TSCA inventory or are exempt.
:	This product does not contain a substance listed by California Prop 65.
:	D2B
:	Listed.
:	Listed.
:	Listed.
:	Not determined.
:	Listed.
:	Listed.
:	Listed.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.