

MATERIAL SAFETY DATA SHEET

PANTONE 349C

Version Number 1.0 Revision Date 10/12/2001 Page 1 of 6 Print Date 11/1/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PANTONE 349C
Product code	:	CC10003635
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	1 - 5
C.I. Pigment Yellow 163	68186-92-5	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion	Resin particles, like other inert materials, can be mechanically irritating.May be harmful if swallowed.
Eyes	 Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.





PANTONE 349C Version Number 1.0 Page 2 of 6 Revision Date 10/12/2001 Print Date 11/1/2011 **Medical Conditions** : None known. Aggravated by Exposure: 4. FIRST AID MEASURES Move to fresh air in case of accidental inhalation of fumes from Inhalation overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice. Do not induce vomiting without medical advice. When symptoms Ingestion : persist or in all cases of doubt seek medical advice. Eyes : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention. Skin : Wash off with soap and plenty of water. If skin irritation persists seek medical attention. **5. FIRE-FIGHTING MEASURES** Flash point : Not applicable Flammable Limits Upper explosion limit Not applicable : Lower explosion limit Not applicable : Autoignition temperature Not relevant : Suitable extinguishing media : Carbon dioxide blanket, water spray, dry powder, foam. Special Fire Fighting Fullface self-contained breathing apparatus (SCBA) used in positive : Procedures pressure mode should be worn to prevent inhalation of airborne contaminants. Unusual Fire/Explosion None • Hazards 6. ACCIDENTAL RELEASE MEASURES Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. Environmental precautions Should not be released into the environment. The product should not : be allowed to enter drains, water courses or the soil. Methods for cleaning up Clean up promptly by sweeping or vacuum. Package all material in : plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods. 7. HANDLING AND STORAGE Handling Take measures to prevent the build up of electrostatic charge. Heat · only in areas with appropriate exhaust ventilation.

MATERIAL SAFETY DATA SHEET

PANTONE 349C



ersion Number 1.0 evision Date 10/12/2001		Page 3 of Print Date 11/1/201
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXF	OSUR	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

Components	Value	Exposure time	Exposure type	List:
C.I. Pigment Yellow	0.5 mg/m3	Time Weighted Average	as Cr	ACGIH
163		(TWA):		
Titanium dioxide	10 mg/m3	Time Weighted Average	Total dust.	ACGIH
	_	(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1

Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	 Solid Pellets GREEN Very faint Not determined. Not applicable Insoluble 	Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH	 Not applicable. Not determined. Not established Not applicable Not applicable Not applicable
	10. STABILITY AND	D REACTIVITY	
Stability	: Stable.		
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	: Keep away from or	kidizing agents and open fl	lame. To avoid thermal



MATERIAL SAFETY DATA SHEET

PANTONE 349C

sion Number 1.0 ision Date 10/12/20	001		Page 4 Print Date <i>11/1/</i> 2
	decompo	sition, do not overheat.	
Incompatible Materia	als : Incompat	tible with strong acids a	nd oxidizing agents.
Hazardous decompos products			onoxide (CO), oxides of nitrogen s, and smoke are all possible.
	11. TOXICOL	OGICAL INFORMA	TION
	been evaluated as a whole dividual components whice		posure effects listed are based on exis
Toxicity Overview This product contain	s the following componen	ts which in their pure for	orm have the following characteristic
CAS-No.	Chemical Name	Effect	Target Organ
13463-67-7	Titanium dioxide	Systemic effect	
68186-92-5	C.I. Pigment Yellow	163 Irritant	Eyes, Skin.
	12 ECOLO	GICAL INFORMATI	ION
	12.10010		
Persistence and degra	adability : Not readi	ly biodegradable.	
Environmental Toxic	city : Chemical of the pol		le as they are bound within the matrix
Bioaccumulation Pot	tential : Chemical of the pol		le as they are bound within the matrix
Additional advice	: No data a	wailable.	
	13. DISPOS	SAL CONSIDERATIO	DNS
Product	recycling waste ma transporta	is preferred to disposal terial has the responsibi	duct can be recycled. Where possible or incineration. The generator of lity for proper waste classification, cordance with applicable federal, ions.
Contaminated packa	has the re and dispo	esponsibility for proper	ible. The generator of waste material waste classification, transportation applicable federal, state/provincial
	14. TRANS	SPORT INFORMATIO	ON
U.S. D.O.T. / CA T.I Classification (Non-I ground)		ated for transportation.	
	bulk		



MATERIAL SAFETY DATA SHEET

ion Date 10/12/2001			Print	Date 11/1
CAO/IATA	: Not regulated :	for transportation.		
MO / IMDG	: Not regulated t	for transportation.		
	15. REGULATO	RY INFORMATIO	N	
JS Regulations:				
OSHA Status : Classified as hazardous based on components.				
TSCA Status	: All component exempt.	s of this product are l	isted on the TSCA in	ventory or
California Propositior 65	n : This product d	oes not contain a subs	stance listed by Calif	ornia Prop
ARA Title III Section 313 T	Foxic Chemicals:			
Chemical Nan	ne	CAS-No.	Weight %	
	I III COMPOUNDS	68186-92-5	15.87	
CAS-No. 68186-92-5 1333-86-4 DSL Jational Inventories:	: Listed.			
Australia AICS	: Listed.			
China IECS	: Not determined	d.		
Europe EINECS	: Not determined	d.		
Japan ENCS	: Not determined	d.		
Korea KECI	: Not determined	d.		
	: Listed.			
Philippines PICCS				
Philippines PICCS	16. OTHER	INFORMATION		
Philippines PICCS	16. OTHER	INFORMATION		



MATERIAL SAFETY DATA SHEET

PANTONE 349C

Version Number 1.0 Revision Date 10/12/2001 Page 6 of 6 Print Date 11/1/2011

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.