

MATERIAL SAFETY DATA SHEET

GREEN OUTER

Version Number 1.0 Revision Date 10/22/2001 Page 1 of 6 Print Date 11/1/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	GREEN OUTER
Product code	:	CC10003792
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Rutile, antimony chromium buff	68186-90-3	1 - 5
Titanium dioxide	13463-67-7	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed.
Eyes	 Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.





GREEN OUTER Version Number 1.0 Page 2 of 6 Revision Date 10/22/2001 Print Date 11/1/2011 **Medical Conditions** : None known. Aggravated by Exposure: 4. FIRST AID MEASURES Move to fresh air in case of accidental inhalation of fumes from Inhalation overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice. Do not induce vomiting without medical advice. When symptoms Ingestion : persist or in all cases of doubt seek medical advice. Eyes : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention. Skin : Wash off with soap and plenty of water. If skin irritation persists seek medical attention. **5. FIRE-FIGHTING MEASURES** Flash point : Not applicable Flammable Limits Upper explosion limit Not applicable : Lower explosion limit Not applicable : Autoignition temperature Not relevant : Suitable extinguishing media : Carbon dioxide blanket, water spray, dry powder, foam. Special Fire Fighting Fullface self-contained breathing apparatus (SCBA) used in positive : Procedures pressure mode should be worn to prevent inhalation of airborne contaminants. Unusual Fire/Explosion None • Hazards 6. ACCIDENTAL RELEASE MEASURES Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. Environmental precautions Should not be released into the environment. The product should not : be allowed to enter drains, water courses or the soil. Methods for cleaning up Clean up promptly by sweeping or vacuum. Package all material in : plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods. 7. HANDLING AND STORAGE Handling Take measures to prevent the build up of electrostatic charge. Heat · only in areas with appropriate exhaust ventilation.

MATERIAL SAFETY DATA SHEET

GREEN OUTER



Version Number 1.0 Revision Date 10/22/2001		Page 3 of 6 Print Date 11/1/2011
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXI	POSUF	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

Components	Value	Exposure time	Exposure type	List:
Rutile, antimony	0.5 mg/m3	Time Weighted Average	as Cr	ACGIH
chromium buff	_	(TWA):		
	0.5 mg/m3	PEL:	as Cr	OSHA Z1
	1 mg/m3	PEL:	Dust. as Cr	OSHA Z1
	0.5 mg/m3	Time Weighted Average	as Sb	ACGIH
		(TWA):		
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
Titanium dioxide	10 mg/m3	Time Weighted Average	Total dust.	ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- Solid
 Pellets
 GREEN
 Very faint
 Not determined.
 Not applicable
 Insoluble
- Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH
- Not applicable.
 Not determined.
 Not established
 Not applicable
 Not applicable
 Not applicable

10. STABILITY AND REACTIVITY



MATERIAL SAFETY DATA SHEET

GREEN OUTER

Version Number 1.0 Revision Date 10/22/2001		Page 4 of 6 Print Date 11/1/2011
Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
68186-90-3	Rutile, antimony chromium buff	Irritant	Eyes, Skin.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Additional Health Hazard Information:

Rutile, antimony chromium buff 68186-90-3 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	:	No data available.
	1	3. DISPOSAL CONSIDERATIONS

Product : Like most thermoplastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.



MATERIAL SAFETY DATA SHEET

GREEN OUTER		
Version Number 1.0 Revision Date 10/22/2001		
Contaminated packaging	:	R

Page 5 of 6 Print Date 11/1/2011

contaminated packaging	:	Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

14. TRANSPORT INFORMATION

U.S. D.O.T. / CA T.D.G.	:	Not regulated for transportation.
Classification (Non-bulk ground)		

ICAO/IATA : Not regulated for transportation.

: Not regulated for transportation.

15. REGULATORY INFORMATION

US Regulations:

IMO / IMDG

OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on the TSCA inventory or are exempt.
California Proposition 65	:	This product does not contain a substance listed by California Prop 65.

SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
CHROMIUM III COMPOUNDS	68186-90-3	2.86
ANTIMONY COMPOUNDS		

Canadian Regulations:

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

CAS-No.	
1333-86-4	
1309-37-1	
68186-90-3	

DSL

: Listed.

National Inventories:

Australia AICS : Listed.



MATERIAL SAFETY DATA SHEET

GREEN OUTER

Version Number 1.0 Revision Date 10/22/2001			Page 6 of 6 Print Date 11/1/2011	
China IECS	:	Listed.		
Europe EINECS	:	Not determined.		
Japan ENCS	:	Not determined.		
Korea KECI	:	Listed.		
Philippines PICCS	:	Listed.		
16. OTHER INFORMATION				

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.