

MATERIAL SAFETY DATA SHEET

WHITE

Version Number 1.0 Revision Date 10/18/2001 Page 1 of 5 Print Date 11/1/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name Product code Chemical Name CAS-No. Product Use	:	WHITE CC10003955 Mixture Mixture Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

WHITE

sion Date 10/18/2001	Print Date 11/1/2
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not relevant Carbon dioxide blanket, water spray, dry powder, foam.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption



MATERIAL SAFETY DATA SHEET

WHITE

Respiratory protection		nd contamination. K	eep in a d	ry, cool place.	
Respiratory protection	POSURE			· •	
		CONTROLS / PER	SONAL	PROTECTION	
	: N	o personal respirator	y protecti	ve equipment norma	dly required.
Eye/Face Protection	: Safety glasses with side-shields.				
Hand protection	: Protective gloves.				
Skin and body protection	: Long sleeved clothing.				
Additional Protective Measures	: Safety shoes.				
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice Wash hands before breaks and at the end of workday.				
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
Components Titanium dioxide	Value 10 mg/m3	Exposure tin Time Weighted A		Exposure type Total dust.	List: ACGIH
Titanium dioxide	10 mg/m3	Time Weighted A (TWA):	verage	Total dust.	ACGIH
1	15 mg/m3	PEL:		Total dust.	OSHA Z1
	9. PHYSIC	CAL AND CHEMI	CAL PRO	PERTIES	
Melting point/range : Not		ets Specific Gravity ITE Bulk density y faint Vapor pressure determined. Vapor density applicable pH		ic Gravity : ensity : pressure : density :	Not applicable. Not determined. Not established Not applicable Not applicable Not applicable
	10. S	STABILITY AND F	REACTIV	TTY	
Stability	: S	table.			
Hazardous Polymerization	: W	Vill not occur.			
Conditions to avoid		eep away from oxid			Γo avoid thermal
Incompatible Materials	: Ir	acompatible with stro	ong acids a	and oxidizing agents	i.



MATERIAL SAFETY DATA SHEET

WHITE

Version Number 1.0 Revision Date 10/18/2001 Page 4 of 5 Print Date 11/1/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ		
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.		
	12. ECOLOGIO	CAL INFORMATION	[
Persistence and degrad	ability : Not readily b	iodegradable.			
Environmental Toxicit		: Chemicals are not readily available as they are bound within the matrix of the polymer.			
Bioaccumulation Poter		: Chemicals are not readily available as they are bound within the matrix of the polymer.			
Additional advice	: No data avail	able.			
	13. DISPOSAL	CONSIDERATIONS			
Product Contaminated packagin	recycling is p waste materia transportation state/provinci ng : Recycling is p has the respo and disposal	 Like most thermoplastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. 			
	14. TRANSPO	RT INFORMATION			
U.S. D.O.T. / CA T.D. Classification (Non-bu ground)	G. : Not regulated	egulated for transportation.			
ICAO/IATA	: Not regulated	: Not regulated for transportation.			
IMO / IMDG	: Not regulated	l for transportation.			
	15 DECULATO	ORY INFORMATION	T		

MATERIAL SAFETY DATA SHEET



WHITE Version Number 1.0 Page 5 of 5 Print Date 11/1/2011 Revision Date 10/18/2001 US Regulations: **OSHA Status** Classified as hazardous based on components. : **TSCA Status** All components of this product are listed on the TSCA inventory or are : exempt. California Proposition : This product does not contain a substance listed by California Prop 65. 65 Canadian Regulations: WHMIS Classification : D2B WHMIS Ingredient Disclosure List CAS-No. 1333-86-4 68186-90-3 DSL : Listed. National Inventories: Australia AICS : Listed. China IECS Listed. Europe EINECS Not determined. : Japan ENCS : Not determined. Korea KECI · Listed. **Philippines PICCS** : Listed. **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.