

MATERIAL SAFETY DATA SHEET

TEAL 0-73

Version Number 1.0 Revision Date 10/23/2001 Page 1 of 5 Print Date 11/1/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	TEAL O-73
Product code	:	CC10004117
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

TEAL O-73

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits	
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Autoignition temperature	: Not relevant
Suitable extinguishing media	: Carbon dioxide blanket, water spray, dry powder, foam.
Special Fire Fighting	Eullface calf contained breathing apparentus (SCPA) used in positive
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption





TEAL 0-73

sion Date 10/23/2001			Print	Page 2 Date 11/1/
	aı	nd contamination. Keep in	a dry, cool place.	
8. H	EXPOSURE	CONTROLS / PERSONA	AL PROTECTION	
Respiratory protection	: N	o personal respiratory prot	ective equipment normally	required.
Eye/Face Protection	: Safety glasses with side-shields.			
Hand protection	: Protective gloves.			
Skin and body protection	: Long sleeved clothing.			
Additional Protective Measures	: Safety shoes.			
General Hygiene Considerations		landle in accordance with g Vash hands before breaks an	ood industrial hygiene and s nd at the end of workday.	safety practic
Engineering measures		leat only in areas with appr ppropriate exhaust ventilati	opriate exhaust ventilation. on at machinery.	Provide
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Titanium dioxide	10 mg/m3	Time Weighted Average	e Total dust.	ACCIL
	-	(TWA):		ACGIH
	15 mg/m3		Total dust.	
	15 mg/m3	(TWA):	Total dust.	OSHA Z
Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	15 mg/m3 9. PHYSIC : Solid : Pelle : AQU : Very : Not o	(TWA): PEL: CAL AND CHEMICAL P I Eva JA Bull I faint Vaj determined. Vaj applicable pH	Total dust. PROPERTIES aporation rate : Not ecific Gravity : Not lk density : Not por pressure : Not por density : Not	OSHA Z
Form Appearance Color Odor Melting point/range Boiling Point:	15 mg/m3 9. PHYSIC : Solid : Pelle : AQU : Very : Not c : Not a : Insol	(TWA): PEL: CAL AND CHEMICAL P I Eva JA Bull I faint Vaj determined. Vaj applicable pH	Total dust. PROPERTIES aporation rate : Noi ceific Gravity : Noi lk density : Noi por pressure : Noi por density : Noi : Noi	OSHA Z t applicable. t determined. t established t applicable t applicable
Form Appearance Color Odor Melting point/range Boiling Point:	15 mg/m3 9. PHYSIC : Solid : Pelle : AQU : Very : Not c : Not a : Insol 10. S	(TWA): PEL: CAL AND CHEMICAL P L Eva ts Spe JA Bully faint Vaj determined. Vaj applicable pH uble	Total dust. PROPERTIES aporation rate : Noi ceific Gravity : Noi lk density : Noi por pressure : Noi por density : Noi : Noi	OSHA Z t applicable. t determined t established t applicable t applicable
Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	15 mg/m3 9. PHYSIC : Solid : Pelle : AQU : Very : Not c : Not a : Insol 10. S : Si	(TWA): PEL: CAL AND CHEMICAL P I Eva its Spe JA Bull faint Vaj determined. Vaj applicable pH uble STABILITY AND REACT	Total dust. PROPERTIES aporation rate : Noi ceific Gravity : Noi lk density : Noi por pressure : Noi por density : Noi : Noi	OSHA Z t applicable. t determined. t established t applicable t applicable
Form Appearance Color Odor Melting point/range Boiling Point: Water solubility Stability	15 mg/m3 9. PHYSIC : Solid : Pelle : AQU : Very : Not c : Not a : Insol 10. S n : W : K	(TWA): PEL: PEL: CAL AND CHEMICAL P I Eva its Specification JA Buily faint Vaj determined. Vaj applicable pH uble STABILITY AND REACT table. Vill not occur.	Total dust. PROPERTIES aporation rate : Noi ecific Gravity : Noi por pressure : Noi por density : Noi TIVITY	OSHA Z t applicable. t determined. t established t applicable t applicable



MATERIAL SAFETY DATA SHEET

TEAL O-73

Version Number 1.0 Revision Date 10/23/2001 Page 4 of 5 Print Date 11/1/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ			
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.			
	12. ECOLOGIO	CAL INFORMATION	1			
Persistence and degrada	ability : Not readily b	iodegradable.				
Environmental Toxicity		 Chemicals are not readily available as they are bound within the matrix of the polymer. Chemicals are not readily available as they are bound within the matrix of the polymer. 				
Bioaccumulation Poten						
Additional advice	: No data avail	able.				
	13. DISPOSAL	CONSIDERATIONS				
Product Contaminated packagin	recycling is p waste materia transportatior state/provinci g : Recycling is p has the respon	referred to disposal or a al has the responsibility and disposal in accord al and local regulations preferred when possible nsibility for proper was in accordance with app	et can be recycled. Where possible incineration. The generator of for proper waste classification, lance with applicable federal, s. e. The generator of waste materia te classification, transportation licable federal, state/provincial			
		RT INFORMATION				
U.S. D.O.T. / CA T.D. Classification (Non-bul ground)	G. : Not regulated	for transportation.				
ICAO/IATA	: Not regulated	l for transportation.				
IMO / IMDG	: Not regulated	l for transportation.				
	15 RECHLATO	ORY INFORMATION	J			

MATERIAL SAFETY DATA SHEET



TEAL O-73		
Version Number 1.0 Revision Date 10/23/2001		Page 5 of 5 Print Date 11/1/2011
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on the TSCA inventory or are exempt.
California Proposition 65	:	This product does not contain a substance listed by California Prop 65.
Canadian Regulations:		
WHMIS Classification	:	D2B
DSL	:	Listed.
National Inventories:		
Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Listed.
Philippines PICCS	:	Listed.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.