

MATERIAL SAFETY DATA SHEET

BLUE Q280-1-1

Version Number 1.0 Revision Date 10/29/2001 Page 1 of 5 Print Date 11/1/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	BLUE Q280-1-1
Product code	:	CC10004300
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact			
Acute exposure				
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes. 			
Skin	: Experience shows no unusual dermatitis hazard from routine handling.			
Chronic exposure	: Refer to Section 11 for Toxicological Information.			
Medical Conditions Aggravated by Exposure:	: None known.			



MATERIAL SAFETY DATA SHEET

BLUE Q280-1-1

ion Number 1.0 sion Date 10/29/2001	Page 2 Print Date 11/1/2
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not relevant Carbon dioxide blanket, water spray, dry powder, foam.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
	6. ACCIDENTAL RELEASE MEASURES
	, ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption



MATERIAL SAFETY DATA SHEET

BLUE Q280-1-1

Respiratory protection Eye/Face Protection Hand protection Skin and body protection Additional Protective Measures General Hygiene Considerations Engineering measures Exposure limit(s) Components Val Titanium dioxide 10 mg 9. PH Form : Appearance : Color : Odor :	SURE C : No : Saf : Pro : Lon : Saf : Ha Wa : He app	o personal respira fety glasses with otective gloves. ng sleeved cloth fety shoes. andle in accordan ash hands before eat only in areas propriate exhaus <u>Exposure</u> Time Weighted (TWA	PERSONAL I atory protective a side-shields. and a side shields. and a side breaks and a with appropri- at ventilation a	PROTECTION we equipment normally industrial hygiene and s t the end of workday. ate exhaust ventilation.	afety practic	
Respiratory protection Eye/Face Protection Hand protection Skin and body protection Additional Protective Measures General Hygiene Considerations Engineering measures Exposure limit(s) Components Val Titanium dioxide 10 mg 15 mg Form : Appearance : Color : Odor :	: No : Saf : Pro : Loo : Saf : Ha Wa : He app	o personal respira fety glasses with otective gloves. ng sleeved cloth fety shoes. andle in accordan ash hands before eat only in areas propriate exhaus <u>Exposure</u> Time Weighted (TWA	atory protectiv a side-shields. aing. ace with good breaks and a with appropri- at ventilation a	ve equipment normally i industrial hygiene and s t the end of workday. ate exhaust ventilation. at machinery. Exposure type	afety practic Provide List:	
Eye/Face Protection Hand protection Skin and body protection Additional Protective Measures General Hygiene Considerations Engineering measures Exposure limit(s) Components Val Titanium dioxide 10 mg 15 mg Form : Appearance : Color : Odor :	: Saf : Pro : Lon : Saf : Ha Wa : He app	fety glasses with otective gloves. ng sleeved cloth fety shoes. andle in accordan ash hands before eat only in areas propriate exhause <u>Exposure</u> Time Weighted (TWA	n side-shields. ning. nce with good breaks and a with appropri- at ventilation a	industrial hygiene and s t the end of workday. ate exhaust ventilation. at machinery. Exposure type	afety practic Provide List:	
Measures General Hygiene Considerations Engineering measures Exposure limit(s) Components Val Titanium dioxide 10 mg 15 mg 9. PH Form : Appearance : Color : Odor :	: Pro : Lon : Saf : Ha Wa : He app	otective gloves. ng sleeved cloth fety shoes. andle in accordan ash hands before eat only in areas propriate exhause <u>Exposure</u> Time Weighted (TWA	ing. ace with good breaks and a with appropri- to ventilation a	industrial hygiene and s t the end of workday. ate exhaust ventilation. at machinery. Exposure type	Provide List:	
Skin and body protection Additional Protective Measures General Hygiene Considerations Engineering measures Exposure limit(s) Components Val Titanium dioxide 10 mg Image: Second structure 15 mg Form : Appearance : Odor :	: Lor : Saf : Ha Wa : He app	ng sleeved cloth fety shoes. andle in accordan ash hands before eat only in areas y propriate exhause <u>Exposure</u> Time Weighted (TWA	nce with good breaks and a with appropri- at ventilation a	t the end of workday. ate exhaust ventilation. at machinery. Exposure type	Provide List:	
Additional Protective Measures General Hygiene Considerations Engineering measures Exposure limit(s) Components Val Titanium dioxide 10 mg 15 mg Form : Appearance : Color : Odor :	: Saf : Ha Wa : Hea app	fety shoes. andle in accordan ash hands before at only in areas propriate exhaus <u>Exposure</u> Time Weighted (TWA	nce with good breaks and a with appropri- at ventilation a	t the end of workday. ate exhaust ventilation. at machinery. Exposure type	Provide List:	
Measures General Hygiene Considerations Engineering measures Exposure limit(s) Components Val Titanium dioxide 10 mg 15 mg 9. PH Form : Appearance : Color : Odor :	: Ha Wa : He app ue g/m3	andle in accordan ash hands before eat only in areas propriate exhause <u>Exposure</u> Time Weighted (TWA	e breaks and a with appropri- t ventilation a	t the end of workday. ate exhaust ventilation. at machinery. Exposure type	Provide List:	
Considerations Engineering measures Exposure limit(s) Components Val Titanium dioxide 10 mg I 15 mg Form I 15 mg Form I 15 mg Color I 15 mg Odor I 15 mg I 15	Wa : Hea app ue g/m3	ash hands before eat only in areas y propriate exhause <u>Exposure</u> Time Weighted (TWA	e breaks and a with appropri- t ventilation a	t the end of workday. ate exhaust ventilation. at machinery. Exposure type	Provide List:	
Exposure limit(s) Components Val Titanium dioxide 10 mg 15 mg 15 mg Perform : Appearance : Color : Odor :	app ue g/m3	propriate exhaus Exposure Time Weighter (TWA	t ventilation a	at machinery. Exposure type	List:	
ComponentsValTitanium dioxide10 mg15 mg9. PHForm:Appearance:Color:Odor:	g/m3	Time Weighted (TWA				
9. PH Form : Appearance : Color : Odor :	g/m3					
9. PH Form : Appearance : Color : Odor :		PEL:		Total dust.	OSHA Z	
Form : Appearance : Color : Odor :	AVSIC	AL AND CHEN	MICAL PRO	PFRTIES		
Appearance:Color:Odor:						
Color : Odor :	Solid				applicable.	
Odor :	Pellets			5	determined.	
	BLUE		Bulk de		established	
	Very f		Vapor j	Vapor pressure: Not applicableVapor density: Not applicable		
01 0		etermined.	-			
Water solubility :	Insolu	ble				
	10. ST	FABILITY ANI	D REACTIV	ITY		
Stability	: Sta	able.				
Hazardous Polymerization	: Wi	ill not occur.				
Conditions to avoid		ep away from ox composition, do		ts and open flame. To a	woid thermal	
Incompatible Materials	: Inc	compatible with	strong acids a	and oxidizing agents.		



MATERIAL SAFETY DATA SHEET

BLUE Q280-1-1

Version Number 1.0 Revision Date 10/29/2001 Page 4 of 5 Print Date 11/1/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ			
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.			
	12. ECOLOGIO	CAL INFORMATION	1			
Persistence and degrada	ability : Not readily b	iodegradable.				
Environmental Toxicity	Chemicals are of the polyme		s they are bound within the matri			
Bioaccumulation Poten		: Chemicals are not readily available as they are bound within the matrix of the polymer.				
Additional advice	: No data avail	able.				
	13. DISPOSAL	CONSIDERATIONS				
Product Contaminated packagin	recycling is p waste materia transportatior state/provinci g : Recycling is p has the respon	referred to disposal or a al has the responsibility and disposal in accord al and local regulations preferred when possible nsibility for proper was in accordance with app	et can be recycled. Where possible incineration. The generator of for proper waste classification, lance with applicable federal, s. e. The generator of waste materia te classification, transportation licable federal, state/provincial			
		RT INFORMATION				
U.S. D.O.T. / CA T.D. Classification (Non-bul ground)	G. : Not regulated	for transportation.				
ICAO/IATA	: Not regulated	l for transportation.				
IMO / IMDG	: Not regulated	l for transportation.				
	15 RECHLATO	ORY INFORMATION	J			

MATERIAL SAFETY DATA SHEET



BLUE Q280-1-1

Version Number 1.0 Revision Date 10/29/2001		Page 5 of 5 Print Date 11/1/2011
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on the TSCA inventory or are exempt.
California Proposition 65	ı :	This product does not contain a substance listed by California Prop 65.
Canadian Regulations:		
WHMIS Classification	n :	D2B
DSL	:	Listed.
National Inventories:		
Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Not determined.
Japan ENCS	:	Listed.
Korea KECI	:	Listed.
Philippines PICCS	:	Listed.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.