

MATERIAL SAFETY DATA SHEET

PURPLE

Version Number 1.0 Revision Date 10/31/2001 Page 1 of 5 Print Date 11/1/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PURPLE
Product code	:	CC10004352
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous	7631-86-9	1 - 5
Titanium dioxide	13463-67-7	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation Ingestion	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. 		
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		





ion Number 1.0 sion Date 10/31/2001	Page 2 Print Date 11/1/2
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation : Move to fresh air in case of accidental inhalation of fumes fro overheating or combustion. When symptoms persist or in all doubt seek medical advice.	
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Not applicable Not applicable Not relevant Carbon dioxide blanket, water spray, dry powder, foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

MATERIAL SAFETY DATA SHEET



PURPLE Version Number 1.0 Page 3 of 5 Print Date 11/1/2011 Revision Date 10/31/2001 Keep containers dry and tightly closed to avoid moisture absorption Storage : and contamination. Keep in a dry, cool place. 8. EXPOSURE CONTROLS / PERSONAL PROTECTION Respiratory protection No personal respiratory protective equipment normally required. : Eye/Face Protection Safety glasses with side-shields. : Hand protection Protective gloves. : Skin and body protection : Long sleeved clothing. Additional Protective Safety shoes. : Measures General Hygiene Handle in accordance with good industrial hygiene and safety practice. : Considerations Wash hands before breaks and at the end of workday. Heat only in areas with appropriate exhaust ventilation. Provide Engineering measures : appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Silica, amorphous	20 mppcf	PEL:	Total dust.	OSHA
	20 mppcf	PEL:	Total dust.	Z3
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1

9. PHYSICAL AND	O CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- Solid
 Pellets
 PURPLE
 Very faint
 Not determined.
 Not applicable
 Insoluble
- Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH

Keep away from oxidizing agents and open flame. To avoid thermal

- : Not applicable.
- : Not determined.
- : Not established
- : Not applicable
- : Not applicable
- : Not applicable

10. STABILITY AND REACTIVITY

- Stability : Stable.
- Hazardous Polymerization : Will not occur.

:

Conditions to avoid

3/5



MATERIAL SAFETY DATA SHEET

sion Number 1.0			Page 4		
vision Date 10/31/20	001		Print Date 11/1/2		
	decompos	ition, do not overheat.			
Incompatible Materi	als : Incompati	: Incompatible with strong acids and oxidizing agents.			
Hazardous decompo products		: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.			
	11. TOXICOL	OGICAL INFORMAT	ION		
	been evaluated as a whole dividual components which		osure effects listed are based on exi-		
	s the following component	ts which in their pure for	m have the following characteristic		
CAS-No.	Chemical Name	Effect	Target Organ		
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.		
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.		
		GICAL INFORMATIO			
Bioaccumulation Po Additional advice	of the poly	 Chemicals are not readily available as they are bound within the matrix of the polymer. No data available. 			
	13. DISPOS	AL CONSIDERATION	NS		
Product	recycling waste mat transporta	is preferred to disposal over the second sec	uct can be recycled. Where possible or incineration. The generator of ty for proper waste classification, ordance with applicable federal, ons.		
Contaminated packa	has the res and dispos	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.			
	14. TRANS	PORT INFORMATIO	N		
U.S. D.O.T. / CA T. Classification (Non- ground)	e	ated for transportation.			



MATERIAL SAFETY DATA SHEET

PURPLE		
Version Number 1.0 Revision Date 10/31/2001		Page 5 of 5 Print Date 11/1/2011
ICAO/IATA	:	Not regulated for transportation.
IMO / IMDG	:	Not regulated for transportation.
	15	5. REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on the TSCA inventory or are exempt.
California Proposition 65	:	This product does not contain a substance listed by California Prop 65.
Canadian Regulations:		
WHMIS Classification	:	D2B
WHMIS Ingredient Disc	losı	are List
CAS-No. 7631-86-9		
DSL	:	Listed.
National Inventories:		
Australia AICS	:	Not determined.
China IECS	:	Not determined.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Not determined.
Philippines PICCS	:	Not determined.
		16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.