

MATERIAL SAFETY DATA SHEET

DARK GRAY

Version Number 1.1 Revision Date 12/19/2003 Page 1 of 8 Print Date 11/13/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	DARK GRAY
Product code	:	CC10004682
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
8-Oxa-3,5-dithia-4-stannatetradecanoic acid,	57583-35-4	1 - 5
10-ethyl-4,4-dimethyl-7-oxo-, 2-ethylhexyl		
ester		
Carbon black	1333-86-4	1 - 5
Chromium (III) oxide	1308-38-9	1 - 5
Titanium dioxide	13463-67-7	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

: Inhalation, Ingestion, Skin contact		
: Particulates, like other inert materials can be mechanically irritating. Excessive inhalation of product vapors, especially during heating or processing, may be irritating to respiratory system.		
: May be harmful if swallowed.		
: Particulates, like other inert materials can be mechanically irritating.		
: Experience shows no unusual dermatitis hazard from routine handling.		



MATERIAL SAFETY DATA SHEET **DARK GRAY**

Version Number 1.1 Revision Date 12/19/2003 Page 2 of 8 Print Date 11/13/2011

Iedical Conditions : None known. ggravated by Exposure:			
	4. FIRST AID MEASURES		
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice.	of	
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.		
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for least 15 minutes. If eye irritation persists, seek medical attention.	at	
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.	eek	
	5. FIRE-FIGHTING MEASURES		
Flash point	: Not applicable		
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone. 		
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fir conditions. 	7	
	ACCIDENTAL RELEASE MEASURES		
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.		
Environmental precautions	: Should not be released into the environment. The product should n be allowed to enter drains, water courses or the soil.	ot	
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material ir plastic, cardboard or metal containers for disposal. Refer to Section		



MATERIAL SAFETY DATA SHEET DARK GRAY

ersion Number 1.1 evision Date 12/19/2003		Page 3 of Print Date 11/13/201
		of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXP	OSUF	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		



MATERIAL SAFETY DATA SHEET DARK GRAY

Version Number 1.1 Revision Date 12/19/2003

Page 4 of 8 Print Date 11/13/2011

Components	Value	Exposure time	Exposure type	List:
8-Oxa-3,5-dithia-4-sta	0.1 mg/m3	PEL:	as Sn	OSHA Z1
nnatetradecanoic acid,				
10-ethyl-4,4-dimethyl-				
7-oxo-, 2-ethylhexyl				
ester				
	0.1 mg/m3	Time Weighted Average	as Sn	ACGIH
		(TWA):		
	0.2 mg/m3	Short Term Exposure Limit	as Sn	ACGIH
		(STEL):		
Carbon black	3.5 mg/m3	Time Weighted Average	Total dust. as carbon	ACGIH
		(TWA):	black	
	3.5 mg/m3	PEL:	Total dust. as carbon	OSHA Z1
			black	
Chromium (III) oxide	0.5 mg/m3	Time Weighted Average	as Cr	ACGIH
		(TWA):		
	1 mg/m3	PEL:	as Cr	OSHA Z1
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
	_	(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- : Solid : Pellets : GREY : Very faint : Not determined : Not applicable : Insoluble

Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density pН

- Not applicable : Not determined : Not established : : Not applicable :
- Not applicable
- Not applicable :

10. STABILITY AND REACTIVITY

Stability	:	Stable. Will not occur.
Hazardous Polymerization		
Conditions to avoid	•	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Avoid contact with strong oxidizers. Also, avoid contact with acetal or acetal copolymers and with amine containing materials during processing. At processing conditions, these materials are mutually destructive and involve rapid degradation. Thoroughly purge and mechanically clean processing equipment to avoid even trace quantities of these materials from coming in contact with each other. Prevent cross contamination of feedstocks.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and



MATERIAL SAFETY DATA SHEET

DARK GRAY

Version Number 1.1 Revision Date 12/19/2003 Page 5 of 8 Print Date 11/13/2011

smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
57583-35-4	8-Oxa-3,5-dithia-4-stannat etradecanoic acid, 10-ethyl-4,4-dimethyl-7-o xo-, 2-ethylhexyl ester	Irritant	Eyes, Skin.
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.
1308-38-9	Chromium (III) oxide	Irritant	Eyes, Skin.
		sensitizer	Skin.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Additional Health Hazard Information:

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). The IARC 2B listing only pertains to airborne, unbound carbon black particles of respirable size. Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

Additional Health Hazard Information:

Chromium (III) oxide 1308-38-9 The bi and trivalent forms of chrome have a low order of acute toxicity but may cause skin sensitization and irritation to the eyes. No effects have been reported for chromium (III) oxide. Chromium (III) componds are not considered carcinogenic in animals or humans.

12. ECOLOGICAL INFORMATION



MATERIAL SAFETY DATA SHEET **DARK GRAY**

Version Number 1.1 Revision Date 12/19/2003	Page 6 of 8 Print Date 11/13/2011
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	
California Proposition 65	: WARNING! This product contains a chemical known to the State of California to cause cancer.

P<u>olyOne</u>

MATERIAL SAFETY DATA SHEET **DARK GRAY**

Version Number 1.1 Revision Date 12/19/2003

Page 7 of 8 Print Date 11/13/2011

SARA Title III Section 302 Extremely Hazardous Substance

Not applicable

SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
CHROMIUM III COMPOUNDS	1308-38-9	3.21

Canadian Regulations:

National Pollutant Release Inventory (NPR	I)
-------------------------------------------	----

Chemical Name	CAS-No.	Weight %	NPRI ID#
Chromium (III) oxide	1308-38-9	3.21	68

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.	
57583-35-4	
1333-86-4	
1308-38-9	

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	: Not determined
China IECS	: Listed
Europe EINECS	: Not determined
Japan ENCS	: Not determined
Korea KECI	: Not determined
Philippines PICCS	: Listed

:

16. OTHER INFORMATION



MATERIAL SAFETY DATA SHEET **DARK GRAY**

Version Number 1.1 Revision Date 12/19/2003

Page 8 of 8 Print Date *11/13/2011*

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.