

MATERIAL SAFETY DATA SHEET

NAPCO-CAMEO

Version Number 1.0 Revision Date 11/11/2001 Page 1 of 6 Print Date 11/2/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	NAPCO-CAMEO
Product code	:	CC10005177
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Rutile, antimony chromium buff	68186-90-3	1 - 5
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation Ingestion	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. 		
Eyes	 Resin particles, like other inert materials, are mechanically irritating to eyes. 		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		





ion Number 1.0 sion Date 11/11/2001	Page 2 Print Date 11/2/
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion	 Not applicable Not applicable Not relevant Carbon dioxide blanket, water spray, dry powder, foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
Hazards	
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

MATERIAL SAFETY DATA SHEET

NAPCO-CAMEO



sion Number 1.0 vision Date 11/11/2001			Print	Page 3 of Date 11/2/201	
Storage		Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.			
8. E	XPOSURE	CONTROLS / PERSONAL	PROTECTION		
Respiratory protection	: N	lo personal respiratory protecti	ve equipment normally r	required.	
Eye/Face Protection	: S	Safety glasses with side-shields.			
Hand protection	: P	Protective gloves.			
Skin and body protection	: L	Long sleeved clothing.			
Additional Protective Measures	: S	Safety shoes.			
General Hygiene Considerations		: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.			
Engineering measures		: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.			
Exposure limit(s)					
Components	Value	Exposure time	Exposure type	List:	
Rutile, antimony	0.5 mg/m3	Time Weighted Average	Total dust. as Cr	ACGIH	

Components	value	Exposure time	Exposure type	LISt.
Rutile, antimony	0.5 mg/m3	Time Weighted Average	Total dust. as Cr	ACGIH
chromium buff		(TWA):		
	0.5 mg/m3	PEL:	Total dust. as Cr	OSHA Z1
	0.5 mg/m3	Time Weighted Average	as Sb	ACGIH
		(TWA):		
	0.5 mg/m3	PEL:	Total dust. as Sb	OSHA Z1
Titanium dioxide	10 mg/m3	Time Weighted Average	Total dust.	ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- Pellets
 TAN
 Very faint
 Not determined.
 Not applicable
 Insoluble

: Solid

- Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH
- Not applicable.
 Not determined.
 Not established
 Not applicable
 Not applicable
 Not applicable

10. STABILITY AND REACTIVITY

Stability

: Stable.



MATERIAL SAFETY DATA SHEET

NAPCO-CAMEO

Version Number 1.0 Revision Date 11/11/2001		Page 4 of 6 Print Date 11/2/2011
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
68186-90-3	Rutile, antimony chromium buff	Irritant	Eyes, Skin.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Additional Health Hazard Information:

Rutile, antimony chromium buff 68186-90-3 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia



MATERIAL SAFETY DATA SHEET

NAPCO-CAMEO

rision Date 11/11/2001			Print	Page 5 c Date 11/2/20
	and d	ne responsibility for proper wa lisposal in accordance with ap local regulations.		
	14. TR	ANSPORT INFORMATIO	N	
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)		egulated for transportation.		
ICAO/IATA	: Not r	egulated for transportation.		
IMO / IMDG	: Not r	egulated for transportation.		
	15. REG	ULATORY INFORMATIC	DN	
US Regulations:				
OSHA Status	: Class	ified as hazardous based on c	omponents.	
			-	nuantary or are
TSCA Status	: All co exem	omponents of this product are pt.	listed on the 1SCA i	nventory or are
California Propos 65	sition : This	product does not contain a sub	ostance listed by Cali	fornia Prop 65.
SARA Title III Section 3	313 Toxic Chemic	als:		
Chemical		CAS-No.	Weight %	
CHROMI	Name IUM III COMPOU NY COMPOUNI	UNDS 68186-90-3	Weight % 2.75	
CHROMI ANTIMO	UM III COMPOU	UNDS 68186-90-3		
CHROMI ANTIMO Canadian Regulations:	IUM III COMPOU NY COMPOUNI	UNDS 68186-90-3		
CHROMI ANTIMO Canadian Regulations: WHMIS Classifie	UM III COMPOUNI NY COMPOUNI cation : D2B	UNDS 68186-90-3 DS		
CHROMI ANTIMO Canadian Regulations: WHMIS Classific WHMIS Ingredier	UM III COMPOU DNY COMPOUNI cation : D2B nt Disclosure List	UNDS 68186-90-3 DS		
CHROMI ANTIMO Canadian Regulations: WHMIS Classifie	UM III COMPOUNY ONY COMPOUNI cation : D2B nt Disclosure List	UNDS 68186-90-3 DS		
CHROMI ANTIMO Canadian Regulations: WHMIS Classific WHMIS Ingredier CAS-No	UM III COMPOUNY ONY COMPOUNI cation : D2B nt Disclosure List	UNDS 68186-90-3 DS		
CHROMI ANTIMO Canadian Regulations: WHMIS Classifie WHMIS Ingredien CAS-No 68186-90	CUM III COMPOUNI NY COMPOUNI cation : D2B nt Disclosure List 	UNDS 68186-90-3 DS		
CHROMI ANTIMO Canadian Regulations: WHMIS Classifie WHMIS Ingredied CAS-No 68186-90 DSL	CUM III COMPOUNI NY COMPOUNI cation : D2B nt Disclosure List 	UNDS 68186-90-3 DS 68186-90-3		
CHROMI ANTIMO Canadian Regulations: WHMIS Classifie WHMIS Ingredien CAS-No 68186-90 DSL National Inventories:	UM III COMPOUNI DNY COMPOUNI cation : D2B nt Disclosure List 	UNDS 68186-90-3 DS d.		



Page 6 of 6

MATERIAL SAFETY DATA SHEET

NAPCO-CAMEO

Version Number 1.0 Revision Date 11/11/2001

Date 11/11/2001		Print Date 11/2/2011
Japan ENCS	: Not determined.	
Korea KECI	: Listed.	
Philippines PICCS	: Listed.	

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.