

MATERIAL SAFETY DATA SHEET

ORANGE

Version Number 1.0 Revision Date 11/26/2001 Page 1 of 6 Print Date 11/2/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	ORANGE
Product code	:	CC10005183
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Benzenesulfonic acid,	67801-01-8	1 - 5
5-chloro-4-ethyl-2-[(2-hydroxy-1-naphthalen		
yl)azo]-, barium salt (2:1)		
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: No known effects.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.





ORANGE Version Number 1.0 Page 2 of 6 Revision Date 11/26/2001 Print Date 11/2/2011 **Medical Conditions** : None known. Aggravated by Exposure: **4. FIRST AID MEASURES** Inhalation Move to fresh air in case of accidental inhalation of fumes from : overheating or combustion. Seek medical attention after significant exposure. : Do not induce vomiting without medical advice. Seek medical Ingestion attention if necessary. Eyes Rinse immediately with plenty of water for at least 15 minutes. If eye : irritation persists, seek medical attention. Skin Wash off with soap and plenty of water. If skin irritation persists seek : medical attention. **5. FIRE-FIGHTING MEASURES** Flash point Greater than 200 Deg F : Flammable Limits Upper explosion limit Not applicable. : Lower explosion limit Not applicable. : Autoignition temperature : Not applicable. Carbon dioxide blanket, dry powder, foam. Suitable extinguishing media : Special Fire Fighting : Fullface self-contained breathing apparatus (SCBA) used in positive Procedures pressure mode should be worn to prevent inhalation of airborne contaminants. Unusual Fire/Explosion : None Hazards 6. ACCIDENTAL RELEASE MEASURES Personal precautions Wear appropriate personal protection during cleanup, such as : impervious gloves, boots and coveralls. Environmental precautions Should not be released into the environment. The product should not : be allowed to enter drains, water courses or the soil. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, Methods for cleaning up : universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.

7. HANDLING AND STORAGE

MATERIAL SAFETY DATA SHEET



ion Date 11/26/2001			Print	Page t Date 11/2			
Handling	: Heat only in areas with appropriate exhaust ventilation.						
Storage	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.						
8. E	XPOSURE	CONTROLS / PERSONA	AL PROTECTION				
Respiratory protection	: U	: Under normal handling conditions a respirator is not required.					
Eye/Face Protection	: S	afety glasses with side-shie	lds.				
Hand protection	: P	rotective gloves.					
Skin and body protection	: L	ong sleeved clothing.					
Additional Protective Measures	: S	: Safety shoes.					
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.						
Engineering measures		eat only in areas with appropriate exhaust ventilation		. Provide			
7							
Exposure limit(s)							
	Value	Exposure time	Exposure type	List:			
Components Benzenesulfonic acid, 5-chloro-4-ethyl-2-[(2- hydroxy-1-naphthalen yl)azo]-, barium salt (2:1)	Value 0.5 mg/m3	Exposure time Time Weighted Average (TWA):	Exposure type e as Ba				
Components Benzenesulfonic acid, 5-chloro-4-ethyl-2-[(2- hydroxy-1-naphthalen yl)azo]-, barium salt		Time Weighted Average		ACGIF			
Components Benzenesulfonic acid, 5-chloro-4-ethyl-2-[(2- hydroxy-1-naphthalen yl)azo]-, barium salt	0.5 mg/m3	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA):	e as Ba as Ba	ACGII OSHA Z ACGII			
Components Benzenesulfonic acid, 5-chloro-4-ethyl-2-[(2- hydroxy-1-naphthalen yl)azo]-, barium salt (2:1)	0.5 mg/m3	Time Weighted Average (TWA): PEL: Time Weighted Average	e as Ba as Ba	OSHA Z OSHA Z			
Components Benzenesulfonic acid, 5-chloro-4-ethyl-2-[(2- hydroxy-1-naphthalen yl)azo]-, barium salt (2:1)	0.5 mg/m3 0.5 mg/m3 10 mg/m3 15 mg/m3	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA):	e as Ba as Ba e Total dust. Total dust.	ACGII OSHA Z ACGII			
Components Benzenesulfonic acid, 5-chloro-4-ethyl-2-[(2- hydroxy-1-naphthalen yl)azo]-, barium salt (2:1)	0.5 mg/m3 0.5 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : liquid	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL P d Eva	e as Ba as Ba e Total dust. Total dust. ROPERTIES	ACGII OSHA Z ACGII OSHA Z			
Components Benzenesulfonic acid, 5-chloro-4-ethyl-2-[(2- hydroxy-1-naphthalen yl)azo]-, barium salt (2:1) Titanium dioxide	0.5 mg/m3 0.5 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : liquid : visco	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL P d Eva us, liquid Spe	e as Ba as Ba as Ba Total dust. Total dust. ROPERTIES	ACGIF OSHA 2 ACGIF OSHA 2 OSHA 2			
Components Benzenesulfonic acid, 5-chloro-4-ethyl-2-[(2- hydroxy-1-naphthalen yl)azo]-, barium salt (2:1) Titanium dioxide	0.5 mg/m3 0.5 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : liquid : visco : ORA	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL P d Eva us, liquid Spe NGE Bul	e as Ba as Ba Total dust. Total dust. ROPERTIES	ACGII OSHA 2 ACGII OSHA 2 OSHA 2			
Components Benzenesulfonic acid, 5-chloro-4-ethyl-2-[(2- hydroxy-1-naphthalen yl)azo]-, barium salt (2:1) Titanium dioxide	0.5 mg/m3 0.5 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : liquid : visco : ORA : Very	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL P d Eva us, liquid Spe NGE Bul faint Vap	e as Ba as Ba as Ba Total dust. Total dust. ROPERTIES	ACGIH OSHA Z ACGIH OSHA Z OSHA Z			
Components Benzenesulfonic acid, 5-chloro-4-ethyl-2-[(2- hydroxy-1-naphthalen yl)azo]-, barium salt (2:1) Titanium dioxide	0.5 mg/m3 0.5 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : liquid : visco : ORA : Very : Not a	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL P d Eva us, liquid Spe NGE Bul faint Vap	e as Ba as Ba Total dust. Total dust. PROPERTIES PROPER	ACGIH OSHA Z ACGIH OSHA Z OSHA Z			
Components Benzenesulfonic acid, 5-chloro-4-ethyl-2-[(2- hydroxy-1-naphthalen yl)azo]-, barium salt (2:1) Titanium dioxide	0.5 mg/m3 0.5 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : liquid : visco : ORA : Very	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL P d Eva us, liquid Spe NGE Bul faint Vap	e as Ba as Ba as Ba Total dust. Total dust. ROPERTIES	OSI OSI OSI OSI OSI OSI OSI OSI OSI OSI			



MATERIAL SAFETY DATA SHEET

ORANGE	
UNANOL	

Version Number 1.0 Revision Date 11/26/2001		Page 4 of 6 Print Date 11/2/2011
Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
67801-01-8	Benzenesulfonic acid,	Irritant	Eyes, Skin.
	5-chloro-4-ethyl-2-[(2-hyd		
	roxy-1-naphthalenyl)azo]-,		
	barium salt (2:1)		
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

12. ECOLOGICAL	INFORMATION

Persistence and degradability	: Not readily biodegradable.			
Environmental Toxicity	Adverse ecological impact is not known or expected under normal use.Does not bioaccumulate			
Bioaccumulation Potential				
Additional advice	: No data available.			
	13. DISPOSAL CONSIDERATIONS			
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.			
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.			
	14. TRANSPORT INFORMATION			



MATERIAL SAFETY DATA SHEET

ion Number 1.0 sion Date 11/26/2001				Page Print Date 11/2	
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	:	: Not regulated for transportation.			
ICAO/IATA	:	Not regulated for	transportation.		
IMO / IMDG	:	Not regulated for	transportation.		
	15	5. REGULATORY	INFORMATIC	DN	
US Regulations:					
OSHA Status	:	Classified as haza	ardous based on c	components.	
TSCA Status	:	: All components of this product are listed on the TSCA inventory or are exempt.			
California Proposition 65	:	This product does	s not contain a sul	ostance listed by California Prop	
SARA Title III Section 313 To:	xic (Chemicals:			
Chemical Name			CAS-No.	Weight %	
BARIUM COM	POU	JNDS	67801-01-8	2.42	
Canadian Regulations:					
WHMIS Classification	:	D2B			
WHMIS Ingredient Disc	losi	ire List			
CAS-No. 67801-01-8					
DSL	:	: Listed.			
National Inventories:					
Australia AICS	:	Not determined.			
China IECS	:	Not determined.			
Europe EINECS	:	Not determined.			
Japan ENCS	:	Not determined.			
Korea KECI	:	Not determined.			
Philippines PICCS	:	Not determined.			

MATERIAL SAFETY DATA SHEET



ORANGE

Version Number 1.0 Revision Date 11/26/2001 Page 6 of 6 Print Date 11/2/2011

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.