

MATERIAL SAFETY DATA SHEET

# WHITE 21525

Version Number 1.0 Revision Date 11/13/2001 Page 1 of 6 Print Date 11/2/2011

# 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	WHITE 21525
Product code	:	CC10005198
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
C.I. Pigment Yellow 53	8007-18-9	0.1 - 1
Titanium dioxide	13463-67-7	30 - 60

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

## POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion	<ul> <li>Resin particles, like other inert materials, can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> </ul>
Eyes	<ul> <li>Resin particles, like other inert materials, are mechanically irritating to eyes.</li> </ul>
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.





ion Number 1.0 sion Date 11/13/2001	Page : Print Date 11/2/
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not relevant</li> <li>Carbon dioxide blanket, water spray, dry powder, foam.</li> </ul>
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge Heat only in areas with appropriate exhaust ventilation.

### MATERIAL SAFETY DATA SHEET





Version Number 1.0 Revision Date 11/13/2001		Page 3 of 6 Print Date 11/2/2011
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXP	OSUR	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

Components	Value	Exposure time	Exposure type	List:
C.I. Pigment Yellow	0.2 mg/m3	Time Weighted Average	as Ni	ACGIH
53		(TWA):		
	1 mg/m3	PEL:	as Ni	OSHA Z1
	0.5 mg/m3	Time Weighted Average	as Sb	ACGIH
		(TWA):		
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
Titanium dioxide	10 mg/m3	Time Weighted Average	Total dust.	ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1

## 9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- Solid
  Pellets
  WHITE
  Very faint
  Not determined.
  Not applicable
  Insoluble
- Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH
- Not applicable.
  Not determined.
  Not established
  Not applicable
  Not applicable
  Not applicable

#### **10. STABILITY AND REACTIVITY**

Stability

: Stable.



#### MATERIAL SAFETY DATA SHEET

# WHITE 21525

Version Number 1.0 Revision Date 11/13/2001		Page 4 of 6 Print Date 11/2/2011
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

#### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
8007-18-9	C.I. Pigment Yellow 53	Irritant	Eyes, Skin.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
8007-18-9	C.I. Pigment Yellow 53	no	1	2

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

#### **12. ECOLOGICAL INFORMATION**

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	:	No data available.



MATERIAL SAFETY DATA SHEET

# WHITE 21525

sion Number 1.0 ision Date 11/13/2001			Page 5 Print Date 11/2/2	
	13. DISPOSAL CO	DNSIDERATION	S	
Product	recycling is prefe waste material ha transportation an	erred to disposal or as the responsibilit	act can be recycled. Where possible r incineration. The generator of y for proper waste classification, rdance with applicable federal, ns.	
Contaminated packaging	has the responsib	ility for proper wa	le. The generator of waste material aste classification, transportation plicable federal, state/provincial	
	14. TRANSPORT	INFORMATION	N	
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: Not regulated for	transportation.		
ICAO/IATA	CAO/IATA : Not regulated for transportation.			
IMO / IMDG       : Not regulated for transportation.				
	15. REGULATORY	Y INFORMATIO	N	
US Regulations:				
OSHA Status	: Classified as haz	ardous based on co	omponents.	
TSCA Status : All components exempt.		of this product are listed on the TSCA inventory or are		
California Proposition : WARNING! This product contains a chemical known in the State 65 California to cause cancer.			s a chemical known in the State of	
SARA Title III Section 313 To:	xic Chemicals:			
Chemical Name		CAS-No.	Weight %	
NICKEL COMPOUNDS ANTIMONY COMPOUNDS		8007-18-9	0.48	
Canadian Regulations:				
WHMIS Classification	: D2B			
WHMIS Ingredient Disc	elosure List			
CAS-No. 8007-18-9				

# PolyOne.

# MATERIAL SAFETY DATA SHEET

# WHITE 21525

Version Number 1.0 Revision Date 11/13/2001 Page 6 of 6 Print Date 11/2/2011

1333-86-4		
DSL	:	Listed.
National Inventories:		
Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Listed.
Philippines PICCS	:	Listed.

## **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.