

## MATERIAL SAFETY DATA SHEET BEIGE W/SPECKLE

Version Number 1.1 Revision Date 02/02/2004

Page 1 of 6 Print Date *11/13/2011* 

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	BEIGE W/SPECKLE
Product code	:	CC10005204
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Cellulose	9004-34-6	1 - 5
Rutile, antimony chromium buff	68186-90-3	1 - 5
Titanium dioxide	13463-67-7	30 - 60

### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion	<ul><li>Resin particles, like other inert materials, can be mechanically irritating.</li><li>May be harmful if swallowed.</li></ul>
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



## MATERIAL SAFETY DATA SHEET BEIGE W/SPECKLE

Version Number 1.1 Revision Date 02/02/2004 Page 2 of 6 Print Date 11/13/2011

Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> </ul>
Suitable extinguishing media	: Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	<ul> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge Heat only in areas with appropriate exhaust ventilation.



# MATERIAL SAFETY DATA SHEET BEIGE W/SPECKLE

Version Number 1.1 Revision Date 02/02/2004 Page 3 of 6 Print Date 11/13/2011

Storage Keep containers dry and tightly closed to avoid moisture absorption : and contamination. Keep in a dry, cool place. 8. EXPOSURE CONTROLS / PERSONAL PROTECTION Respiratory protection : No personal respiratory protective equipment normally required. Eye/Face Protection Safety glasses with side-shields. : Hand protection Protective gloves. : Skin and body protection Long sleeved clothing. : Additional Protective Safety shoes. : Measures General Hygiene Handle in accordance with good industrial hygiene and safety practice. : Considerations Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Cellulose	10 mg/m3	Time Weighted Average	Total dust.	ACGIH
		(TWA):		
	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Rutile, antimony	1 mg/m3	PEL:		OSHA Z1
chromium buff				
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average	as Cr	ACGIH
		(TWA):		
	0.5 mg/m3	Time Weighted Average	as Sb	ACGIH
		(TWA):		
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1

appropriate exhaust ventilation at machinery.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color Odor Melting point/range Boiling Point: Solid
Pellets
TAN
Very faint
Not determined
Not applicable

Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density pH Not applicable
Not determined
Not established
Not applicable
Not applicable
Not applicable





## MATERIAL SAFETY DATA SHEET BEIGE W/SPECKLE

Version Number 1.1 Revision Date 02/02/2004 Page 4 of 6 Print Date *11/13/2011* 

Water solubility :	Ins	soluble	
	10	. STABILITY AND REACTIVITY	
Stability	:	Stable.	
Hazardous Polymerization	:	Will not occur.	
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.	
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.	
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.	

### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
9004-34-6	Cellulose	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
68186-90-3	Rutile, antimony chromium buff	Irritant	Eyes, Skin, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

### LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
9004-34-6	Cellulose	LC50	> 5800 mg/m3	rat
		Oral LD50	> 5 gm/kg	rat
		Dermal LD50	> 2 gm/kg	rabbit

### Additional Health Hazard Information:

Rutile, antimony chromium buff 68186-90-3 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

12. ECOLOGICAL INFORMATION			
Persistence and degradability	:	Not readily biodegradable.	
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the matrix of the polymer.	



# MATERIAL SAFETY DATA SHEET BEIGE W/SPECKLE

Version Number 1.1 Revision Date 02/02/2004 Page 5 of 6 Print Date 11/13/2011

	: Chemicals are not readily available as they are bound within the matr of the polymer.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Wher possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSC Inventory.
US. EPA CERCLA Hazardo	us Substances (40 CFR 302)
Not applicable	
California Proposition 65	n : WARNING! This product contains a chemical known to the State of California to cause cancer.
SARA Title III Section 302 H	Extremely Hazardous Substance
Not applicable	

## MATERIAL SAFETY DATA SHEET BEIGE W/SPECKLE

Version Number 1.1 Revision Date 02/02/2004

Page 6 of 6 Print Date 11/13/2011

SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
CHROMIUM III COMPOUNDSANTIMONY	68186-90-3	1.98
COMPOUNDS		

Canadian Regulations:

Rutile, antimony chromium buff	68186-90-3	1.98	68
Rutile, antimony chromium buff	68186-90-3	1.98	17

WHMIS	Classification	:	D2B

WHMIS Ingredient Disclosure List

:

CAS-No.
68186-90-3

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	: Listed
China IECS	: Listed
Europe EINECS	: Listed
Japan ENCS	: Not determined
Korea KECI	: Listed
Philippines PICCS	: Listed

### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.