

MATERIAL SAFETY DATA SHEET

CHRRY RED W/ UV NYL

Version Number 1.0 Revision Date 11/16/2001 Page 1 of 6 Print Date 11/2/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

| NON-EMERGENCY TELEPHONE | : | Product Stewardship (770) 271-5902 |
|-------------------------------|---|--|
| Emergency telephone number | : | CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident). |
| Product name | : | CHRRY RED W/ UV NYL |
| Product code | : | CC10005220 |
| Chemical Name | : | Mixture |
| CAS-No. | : | Mixture |
| Product Use | : | Industrial Applications |

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

| Components | CAS-No. | Weight % |
|--|------------|----------|
| 1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetramethyl-4-piperidinyl)-, polymer with 2,4,6-trichloro-1,3,5-triazine, reaction products | 70624-18-9 | 1 - 5 |
| Silica, amorphous | 7631-86-9 | 1 - 5 |

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

| Routes of Exposure: | : Inhalation, Ingestion, Skin contact | | |
|---------------------|---|--|--|
| Acute exposure | | | |
| Inhalation | : Resin particles, like other inert materials, can be mechanically irritating. | | |
| Ingestion | : May be harmful if swallowed. | | |
| Eyes | : Resin particles, like other inert materials, are mechanically irritating to eyes. | | |
| Skin | : Experience shows no unusual dermatitis hazard from routine handling. | | |
| | | | |



MATERIAL SAFETY DATA SHEET

CHRRY RED W/ UV NYL

| ion Number 1.0 sion Date 11/16/2001 | Page 2 Print Date 11/2/2 |
|--|---|
| Chronic exposure | : Refer to Section 11 for Toxicological Information. |
| Medical Conditions Aggravated by Exposure: | : None known. |
| | 4. FIRST AID MEASURES |
| Inhalation | : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice. |
| Ingestion | : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice. |
| Eyes | : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention. |
| Skin | : Wash off with soap and plenty of water. If skin irritation persists seel medical attention. |
| | 5. FIRE-FIGHTING MEASURES |
| Flash point | : Not applicable |
| Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media | Not applicable Not applicable Not relevant Carbon dioxide blanket, water spray, dry powder, foam. |
| Special Fire Fighting Procedures | : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. |
| Unusual Fire/Explosion Hazards | : None |
| | 6. ACCIDENTAL RELEASE MEASURES |
| Personal precautions | : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. |
| Environmental precautions | : Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil. |
| Methods for cleaning up | : Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1: of this MSDS for proper disposal methods. |
| | 7. HANDLING AND STORAGE |

Conditions to avoid



MATERIAL SAFETY DATA SHEET

CHRRY RED W/ UV NYL

| sion Number 1.0 ision Date 11/16/2001 | | | | Print | Page 3 Date 11/2/2 |
|--|---|--|--------------------------------|-------------------|----------------------------|
| Handling | | Take measures to prevent the build up of electrostatic charge Heat only in areas with appropriate exhaust ventilation. | | | arge Heat |
| Storage | | Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place. | | | |
| 8. 1 | EXPOSURE | CONTROLS / I | PERSONAL PROT | TECTION | |
| Respiratory protection | : N | lo personal respir | atory protective equ | ipment normally 1 | required. |
| Eye/Face Protection | : S | afety glasses with | n side-shields. | | |
| Hand protection | : P | rotective gloves. | | | |
| Skin and body protection | : L | ong sleeved cloth | ning. | | |
| Additional Protective Measures | : S | : Safety shoes. | | | |
| General Hygiene Considerations | : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. | | | | |
| Engineering measures | : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. | | | | |
| Exposure limit(s) | | | | | |
| Components | Value | Exposure | e time E | Exposure type | List: |
| Silica, amorphous | 20 mppcf | PEL | : | Total dust. | OSHA 72 |
| | 20 mppcf | PEL | • | Total dust. | Z3 |
| | 9. PHYSIC | CAL AND CHE | MICAL PROPER | ΓIES | |
| Form Appearance | : Solic : Pelle | | Evaporation : Specific Grav | | applicable. determined. |
| Color | : RED | | Bulk density | : Not | established |
| Odor | | faint | Vapor pressu | | applicable |
| Melting point/range | : Not determined. | | Vapor densit | | applicable |
| Boiling Point: Water solubility | | : Not applicable pH : Not app : Insoluble | | | applicable |
| | 10. 5 | STABILITY AN | D REACTIVITY | | |
| | | | | | |

3/6

: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.



MATERIAL SAFETY DATA SHEET

CHRRY RED W/ UV NYL

 Version Number 1.0
 Page 4 of 6

 Revision Date 11/16/2001
 Print Date 11/2/2011

 Incompatible Materials
 : Incompatible with strong acids and oxidizing agents.

 Hazardous decomposition products
 : Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

| CAS-No. | Chemical Name | Effect | Target Organ |
|------------|---|--------------|---------------------------------|
| 70624-18-9 | 1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetrameth | Highly Toxic | Refer to MSDS for Toxicity Data |
| | yl-4-piperidinyl)-,polymer with | | |
| | 2,4,6-trichloro-1,3,5-triazi ne, reaction products | | |
| 7631-86-9 | Silica, amorphous | Irritant | Eyes, Respiratory system. |

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

| CAS-No. | Chemical Name | Route | Value | Species |
|------------|---|-------------------|---------------------------|------------|
| 70624-18-9 | 1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetrameth yl-4-piperidinyl)-,polymer with 2,4,6-trichloro-1,3,5-triazi ne, reaction products | LC50 Oral LD50 | 112 mgm34H 9,910 mg/kg | rat rat |

12. ECOLOGICAL INFORMATION

| Persistence and degradability | Not readily biodegradable. | |
|-------------------------------|--|------|
| Environmental Toxicity | Chemicals are not readily available as they are bound within the mat of the polymer. | trix |
| Bioaccumulation Potential | Chemicals are not readily available as they are bound within the mat of the polymer. | trix |
| Additional advice | No data available. | |
| | 3. DISPOSAL CONSIDERATIONS | |
| Product | Like most thermoplastics the product can be recycled. Where possi recycling is preferred to disposal or incineration. The generator of | |



MATERIAL SAFETY DATA SHEET

| sion Number 1.0 ision Date 11/16/2001 | Page 5 Print Date 11/2/2 |
|--|---|
| | waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. |
| Contaminated packaging | : Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. |
| | 14. TRANSPORT INFORMATION |
| U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground) | : Not regulated for transportation. |
| ICAO/IATA | : Not regulated for transportation. |
| IMO / IMDG | : Not regulated for transportation. |
| | 15. REGULATORY INFORMATION |
| US Regulations: | |
| OSHA Status | : Classified as hazardous based on components. |
| TSCA Status | : All components of this product are listed on the TSCA inventory or an exempt. |
| California Proposition 65 | : This product does not contain a substance listed by California Prop 65 |
| Canadian Regulations: | |
| WHMIS Classification | : D1A |
| WHMIS Ingredient Disc | osure List |
| CAS-No. 7631-86-9 | |
| DSL | : Listed. |
| National Inventories: | |
| Australia AICS | : Not determined. |
| China IECS | : Listed. |
| Europe EINECS | : Not determined. |
| Japan ENCS | : Not determined. |



MATERIAL SAFETY DATA SHEET

CHRRY RED W/ UV NYL

Version Number 1.0 Revision Date 11/16/2001 Page 6 of 6 Print Date 11/2/2011

| Korea KECI | : | Not determined. |
|------------|---|-----------------|
| | | |

Philippines PICCS

: Not determined.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.