

MATERIAL SAFETY DATA SHEET

BLUE 12-4607TP

Version Number 1.0 Revision Date 11/09/2001 Page 1 of 5 Print Date 11/2/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	BLUE 12-4607TP
Product code	:	CC10005229
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

BLUE 12-4607TP

ion Number 1.0 sion Date 11/09/2001	Page 2 Print Date 11/2/2
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not relevant Carbon dioxide blanket, water spray, dry powder, foam.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption



MATERIAL SAFETY DATA SHEET

BLUE 12-4607TP

			Print I	Date 11/2/2	
	aı	nd contamination. Keep in a c	ry, cool place.		
8. E	XPOSURE	CONTROLS / PERSONAL	PROTECTION		
Respiratory protection	: N	o personal respiratory protect	ve equipment normally r	required.	
Eye/Face Protection	: Safety glasses with side-shields.				
Hand protection	: Protective gloves.				
Skin and body protection	: Long sleeved clothing.				
Additional Protective Measures	: Safety shoes.				
General Hygiene Considerations		andle in accordance with good Vash hands before breaks and		afety practice	
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
Exposure limit(s)					
[]	Value	Exposure time	Exposure type	List:	
Components	value	Exposure time	Enposare type	Libt.	
Components Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH	
-		Time Weighted Average			
÷	10 mg/m3 15 mg/m3	Time Weighted Average (TWA):	Total dust. Total dust.	ACGIH	
Titanium dioxide	10 mg/m3 15 mg/m3 9. PHYSIC	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO	Total dust. Total dust. DPERTIES	ACGIH OSHA Z1	
Titanium dioxide	10 mg/m3 15 mg/m3 9. PHYSIC : Solid	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO	Total dust. Total dust. DPERTIES ration rate : Not	ACGIH OSHA Z1 applicable.	
Titanium dioxide	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO I Evapo ts Specif	Total dust. Total dust. DPERTIES ration rate : Not ic Gravity : Not	ACGIH OSHA Z1 applicable. determined.	
Titanium dioxide Form Appearance Color	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : BLU	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO E Evapo ts Specif E Bulk o	Total dust. Total dust. DPERTIES ration rate : Not ic Gravity : Not ensity : Not	ACGIH OSHA Z1 applicable. determined. established	
Titanium dioxide Form Appearance Color Odor	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : BLU : Very	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PR(E E Specif E Bulk c faint Vapor	Total dust. Total dust. DPERTIES ration rate : Not ic Gravity : Not ensity : Not pressure : Not	ACGIH OSHA Z1 applicable. determined. established applicable	
Titanium dioxide Titanium dioxide Form Appearance Color Odor Melting point/range	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : BLU : Very : Not c	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO I Evapo ts Specif E Bulk o faint Vapor determined. Vapor	Total dust. Total dust. DPERTIES ration rate : Not ic Gravity : Not ensity : Not pressure : Not density : Not	ACGIH OSHA Z1 applicable. determined. established applicable applicable	
Titanium dioxide Form Appearance Color Odor	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : BLU : Very : Not c	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO I Evapo ts Specif E Bulk of faint Vapor determined. Vapor applicable pH	Total dust. Total dust. DPERTIES ration rate : Not ic Gravity : Not ensity : Not pressure : Not density : Not	ACGIH OSHA Z1 applicable. determined. established applicable	
Titanium dioxide Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point:	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : BLU : Very : Not a : Insol	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO I Evapo ts Specif E Bulk of faint Vapor determined. Vapor applicable pH	Total dust. Total dust. DPERTIES ration rate : Not ic Gravity : Not ensity : Not pressure : Not : Not : Not	ACGIH OSHA Z1 applicable. determined. established applicable applicable	
Titanium dioxide Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point:	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : BLU : Very : Not c : Not a : Insol 10. S	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO I Evapo ts Specif E Bulk c faint Vapor determined. Vapor applicable pH uble Uble	Total dust. Total dust. DPERTIES ration rate : Not ic Gravity : Not ensity : Not pressure : Not : Not : Not	ACGIH OSHA Z1 applicable. determined. established applicable applicable	
Titanium dioxide Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : BLU : Very : Not c : Not a : Insol 10. S : Si	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO I Evapo ts Specif E Bulk of faint Vapor determined. Vapor applicable pH uble	Total dust. Total dust. DPERTIES ration rate : Not ic Gravity : Not ensity : Not pressure : Not : Not : Not	ACGIH OSHA Z1 applicable. determined. established applicable applicable	
Titanium dioxide Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point: Water solubility Stability	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : BLU : Very : Not a : Insol 10. S 10. S 11. S 11. S	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO I Evapo ts Specif E Bulk of faint Vapor determined. Vapor applicable pH uble CTABILITY AND REACTIV table.	Total dust. Total dust. DPERTIES ration rate : Not ic Gravity : Not pressure : Not density : Not /ITY tts and open flame. To a	ACGIH OSHA Z1 applicable. determined. established applicable applicable	



MATERIAL SAFETY DATA SHEET

BLUE 12-4607TP

Version Number 1.0 Revision Date 11/09/2001 Page 4 of 5 Print Date 11/2/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ			
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.			
	12. ECOLOGIO	CAL INFORMATION	1			
Persistence and degrada	ability : Not readily b	iodegradable.				
Environmental Toxicity	Chemicals are of the polyme		s they are bound within the matri			
Bioaccumulation Poten		: Chemicals are not readily available as they are bound within the matrix of the polymer.				
Additional advice	: No data avail	able.				
	13. DISPOSAL	CONSIDERATIONS				
Product Contaminated packagir	recycling is p waste materia transportation state/provinci g : Recycling is p has the respon and disposal	 Like most thermoplastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. 				
	14. TRANSPO	RT INFORMATION				
U.S. D.O.T. / CA T.D. Classification (Non-bul ground)	G. : Not regulated	for transportation.				
ICAO/IATA	: Not regulated	l for transportation.				
IMO / IMDG	: Not regulated	l for transportation.				
	15 DECHLAT	ORY INFORMATION	T			

MATERIAL SAFETY DATA SHEET



BLUE 12-4607TP

Version Number 1.0 Revision Date 11/09/2001		Page 5 of 5 Print Date 11/2/2011
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on the TSCA inventory or are exempt.
California Proposition 65	:	This product does not contain a substance listed by California Prop 65.
Canadian Regulations:		
WHMIS Classification	:	D2B
WHMIS Ingredient Discl	losu	ire List
CAS-No. 1333-86-4		
DSL	:	Listed.
National Inventories:		
Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Not determined.
Japan ENCS	:	Listed.
Korea KECI	:	Listed.
Philippines PICCS	:	Listed.
		16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.