

MATERIAL SAFETY DATA SHEET

Silver Mist Sub

Version Number 1.2 Revision Date 01/20/2004

Page 1 of 7 Print Date *11/13/2011*

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	Silver Mist Sub
Product code	:	CC10005848
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
8-Oxa-3,5-dithia-4-stannatetradecanoic acid,	57583-35-4	1 - 5
10-ethyl-4,4-dimethyl-7-oxo-, 2-ethylhexyl		
ester		
Carbon black	1333-86-4	1 - 5
Stannane,	57583-34-3	1 - 5
methyltris(2-ethylhexyloxycarbonylmethylth		
io)-		

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Particulates, like other inert materials can be mechanically irritating. Excessive inhalation of product vapors, especially during heating or processing, may be irritating to respiratory system.
Ingestion	: May be harmful if swallowed.
Eyes	: Particulates, like other inert materials can be mechanically irritating.



MATERIAL SAFETY DATA SHEET

Silver Mist Sub

Version Number 1.2 Revision Date 01/20/2004 Page 2 of 7 Print Date 11/13/2011

Skin	: Experience shows no unusual dermatitis hazard from routine handling
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
	: Clean up promptly by sweeping or vacuum. Package all material in



MATERIAL SAFETY DATA SHEET

Silver Mist Sub

Considerations

Exposure limit(s)

Engineering measures

Version Number 1.2 Revision Date 01/20/2004 Page 3 of 7 Print Date 11/13/2011

	plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.				
7. HANDLING AND STORAGE					
Handling	: Take measures to prevent the build up of electrostatic charge Heat only in areas with appropriate exhaust ventilation.				
Storage	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.				
8. EXPOSURE CONTROLS / PERSONAL PROTECTION					
Respiratory protection	: No personal respiratory protective equipment normally required.				
Eye/Face Protection	: Safety glasses with side-shields.				
Hand protection	: Protective gloves.				
Skin and body protection	: Long sleeved clothing.				
Additional Protective Measures	: Safety shoes.				
General Hygiene	: Handle in accordance with good industrial hygiene and safety practice.				

Wash hands before breaks and at the end of workday.

appropriate exhaust ventilation at machinery.

: Heat only in areas with appropriate exhaust ventilation. Provide



MATERIAL SAFETY DATA SHEET

Silver Mist Sub

Version Number 1.2 Revision Date 01/20/2004

Page 4 of 7 Print Date 11/13/2011

Components	Value	Exposure time	Exposure type	List:
8-Oxa-3,5-dithia-4-sta nnatetradecanoic acid, 10-ethyl-4,4-dimethyl- 7-oxo-, 2-ethylhexyl ester		PEL:	as Sn	OSHA Z1
	0.1 mg/m3	Time Weighted Average (TWA):	as Sn	ACGIH
	0.2 mg/m3	Short Term Exposure Limit (STEL):	as Sn	ACGIH
Carbon black	3.5 mg/m3	Time Weighted Average (TWA):	Total dust. as carbon black	ACGIH
	3.5 mg/m3	PEL:	Total dust. as carbon black	OSHA Z1
Stannane, methyltris(2-ethylhexy loxycarbonylmethylthi o)-	0.1 mg/m3	PEL:	as Sn	OSHA Z1
	0.1 mg/m3	Time Weighted Average (TWA):	as Sn	ACGIH
	0.2 mg/m3	Short Term Exposure Limit (STEL):	as Sn	ACGIH

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range **Boiling Point:** Water solubility
- : Solid : Pellets GREY Very faint : Not determined Not applicable Insoluble

:

:

:

•

- Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density pH
- : Not applicable
- Not determined :
- Not established : :
 - Not applicable
 - Not applicable
- Not applicable

:

10. STABILITY AND REACTIVITY Stability Stable. : Hazardous Polymerization Will not occur. : Conditions to avoid Keep away from oxidizing agents and open flame. To avoid thermal : decomposition, do not overheat. **Incompatible Materials** Avoid contact with strong oxidizers. Also, avoid contact with acetal or : acetal copolymers and with amine containing materials during processing. At processing conditions, these materials are mutually destructive and involve rapid degradation. Thoroughly purge and mechanically clean processing equipment to avoid even trace quantities of these materials from coming in contact with each other. Prevent cross contamination of feedstocks.



MATERIAL SAFETY DATA SHEET

Silver Mist Sub

Version Number 1.2 Revision Date 01/20/2004 Page 5 of 7 Print Date *11/13/2011*

Hazardous decomposition products

 Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
57583-35-4	8-Oxa-3,5-dithia-4-stannat	Irritant	Eyes, Skin.
	etradecanoic acid,		
	10-ethyl-4,4-dimethyl-7-o		
	xo-, 2-ethylhexyl ester		
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.
57583-34-3	Stannane,	Irritant	Eyes, Skin.
	methyltris(2-ethylhexylox		
	ycarbonylmethylthio)-		

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit
57583-34-3	Stannane, methyltris(2-ethylhexylox ycarbonylmethylthio)-	Oral LD50	920 mg/kg	rat

Additional Health Hazard Information:

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). The IARC 2B listing only pertains to airborne, unbound carbon black particles of respirable size. Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

12. ECOLOGICAL INFORMATION



MATERIAL SAFETY DATA SHEET Silver Mist Sub

Sliver Mist Sub	
Version Number 1.2 Revision Date 01/20/2004	Page 6 of 7 Print Date 11/13/2011
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	
California Proposition 65	: WARNING! This product contains a chemical known to the State of California to cause cancer.



MATERIAL SAFETY DATA SHEET

Silver Mist Sub

Version Number 1.2 Revision Date 01/20/2004 Page 7 of 7 Print Date *11/13/2011*

SARA Title III Section 302 Extremely Hazardous Substance

Not applicable

SARA Title III Section 313 Toxic Chemicals:

Not applicable Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Not applicable

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.
57583-35-4
1333-86-4
57583-34-3

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	: Not determined
China IECS	: Not determined
Europe EINECS	: Not determined
Japan ENCS	: Not determined
Korea KECI	: Not determined
Philippines PICCS	: Not determined

:

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.