

### MATERIAL SAFETY DATA SHEET

### GRAY

Version Number 1.1 Revision Date 02/02/2004 Page 1 of 6 Print Date *11/13/2011* 

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902	
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).	
Product name	:	GRAY	
Product code	:	CC10005992	
Chemical Name	:	Mixture	
CAS-No.	:	Mixture	
Product Use	:	Industrial Applications	

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous	7631-86-9	1 - 5
Titanium dioxide	13463-67-7	5 - 10

### 3. HAZARDS IDENTIFICATION

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation Ingestion Eyes	<ul> <li>Resin particles, like other inert materials, can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Resin particles, like other inert materials, are mechanically irritating to eyes.</li> </ul>		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		



### MATERIAL SAFETY DATA SHEET **GRAY**

Version Number 1.1 Revision Date 02/02/2004 Page 2 of 6 Print Date 11/13/2011

Aggravated by Exposure:					
	4. FIRST AID MEASURES				
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.				
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.				
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.				
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.				
	5. FIRE-FIGHTING MEASURES				
Flash point	: Not applicable				
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> <li>Carbon dioxide blanket, water spray, dry powder, foamnone.</li> </ul>				
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.				
Unusual Fire/Explosion Hazards	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.				
	6. ACCIDENTAL RELEASE MEASURES				
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.				
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.				
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.				
	7. HANDLING AND STORAGE				
Handling	: Take measures to prevent the build up of electrostatic charge Heat only in areas with appropriate exhaust ventilation.				



### MATERIAL SAFETY DATA SHEET **GRAY**

#### Version Number 1.1 Revision Date 02/02/2004

Storage

Page 3 of 6 Print Date 11/13/2011

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Silica, amorphous	20 mppcf	PEL:	Total dust.	OSHA
	20 mppcf	PEL:	Total dust.	Z3
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1

Form	: Solid	Evaporation rate	: Not applicable
Appearance	: Pellets	Specific Gravity:	: Not determined
Color	: GREY	Bulk density	: Not established
Odor	: Very faint	Vapor pressure	: Not applicable
Melting point/range	: Not determined	Vapour density	: Not applicable
Boiling Point:	: Not applicable	pH	: Not applicable
Water solubility	: Insoluble		
	10. STABILITY AN	D REACTIVITY	
Stability	: Stable.		
•			
,	· Will not occur		
Hazardous Polymerization	: Will not occur.		



## MATERIAL SAFETY DATA SHEET **GRAY**

ion Number 1.1				Dama	
sion Date 02/02/2	004			Page 4 Print Date 11/13/2	
		decompositio	n, do not overheat.		
Incompatible Materials : Incompat		Incompatible	tible with strong acids and oxidizing agents.		
Hazardous decompo products	osition :			oxide (CO), oxides of nitrogen ad smoke are all possible.	
	11.	TOXICOLOG	ICAL INFORMATIO	DN	
health data for the ir Toxicity Overview	ndividual comp	oonents which co	omprise the mixture.	are effects listed are based on exit	
This product contair	ns the following	g components w	hich in their pure form	have the following characteristic	
CAS-No.		nical Name	Effect	Target Organ	
7631-86-9	Silica, am		Irritant	Eyes, Respiratory system.	
13463-67-7	Titanium	dioxide	Systemic effects	Respiratory system.	
	tential :	Chemicals are	e not readily available a	s they are bound within the matri	
Additional advice	:	of the polyme	able		
Additional advice	:	of the polyme	er.		
Additional advice	:	of the polyme No data avail I.3. DISPOSAL Like most the possible recyc generator of v classification,	er. able CONSIDERATIONS ermoplastic plastics the cling is preferred to dis waste material has the r	product can be recycled. Where posal or incineration. The esponsibility for proper waste posal in accordance with	
	:	of the polyme No data avail I.3. DISPOSAL Like most the possible recyc generator of v classification, applicable fec Recycling is p has the respon	er. able <b>CONSIDERATIONS</b> ermoplastic plastics the cling is preferred to dis waste material has the r , transportation and disp deral, state/provincial a preferred when possible nsibility for proper was in accordance with app	product can be recycled. Where posal or incineration. The esponsibility for proper waste posal in accordance with	
Product	: 1 I I I I I I I I I I I I I I I I I I	of the polyme No data avail <b>I3. DISPOSAL</b> Like most the possible recyc generator of v classification, applicable fee Recycling is p has the respon and disposal i and local regu	er. able <b>CONSIDERATIONS</b> ermoplastic plastics the cling is preferred to dis waste material has the r , transportation and disp deral, state/provincial a preferred when possible nsibility for proper was in accordance with app	product can be recycled. Where posal or incineration. The esponsibility for proper waste posal in accordance with nd local regulations. b. The generator of waste materia te classification, transportation	
Product	:  aging :	of the polyme No data avail <b>I3. DISPOSAL</b> Like most the possible recyc generator of v classification, applicable fec Recycling is p has the respon and disposal i and local regu	er. able <b>CONSIDERATIONS</b> ermoplastic plastics the cling is preferred to dis waste material has the r , transportation and disp leral, state/provincial a preferred when possible nsibility for proper was in accordance with app alations.	product can be recycled. Where posal or incineration. The esponsibility for proper waste posal in accordance with nd local regulations. b. The generator of waste materia te classification, transportation	



### MATERIAL SAFETY DATA SHEET **GRAY**

Version Number 1.1 Revision Date 02/02/2004

Page 5 of 6 Print Date 11/13/2011

	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	s Substances (40 CFR 302)
Not applicable	
California Proposition 65	: This product does not contain a substance listed by California Prop 65.
SARA Title III Section 302 E	xtremely Hazardous Substance
Not applicable	
SARA Title III Section 313 To	oxic Chemicals:
Not applicable Canadian Regulations:	
National Pollutant Rele	ease Inventory (NPRI)
WHMIS Classification	n : D2B
WHMIS Classification WHMIS Ingredient Dis	
WHMIS Ingredient Dis CAS-No.	
WHMIS Ingredient Dis CAS-No. 7631-86-9	<ul> <li>All of the components of this product are listed on the Canadian Inventories or are exempt. However, at least one component of this product is on the Canadian Non-Domestic Substances List (NDSL).</li> </ul>





### MATERIAL SAFETY DATA SHEET **GRAY**

Version Number 1.1 Revision Date 02/02/2004

Page 6 of 6 Print Date *11/13/2011* 

China IECS	:	Listed
Europe EINECS	:	Listed
Japan ENCS	:	Not determined
Korea KECI	:	Not determined
Philippines PICCS	:	Not determined

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.