

MATERIAL SAFETY DATA SHEET

ORANGE

Version Number 1.0 Revision Date 11/28/2001 Page 1 of 5 Print Date 11/2/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone : CH		CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	ORANGE
Product code	:	CC10006358
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

ORANGE

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Autoignition temperature Suitable extinguishing media	Not relevantCarbon dioxide blanket, water spray, dry powder, foam.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption





ORANGE

					Print L	Date 11/2/2
	а	nd contamination.	Keep in a d	ry, cool place.		
8. I	EXPOSURE	CONTROLS / P	ERSONAL	PROTECTION		
Respiratory protection	: N	No personal respira	tory protecti	ve equipment norm	nally r	equired.
Eye/Face Protection	: Safety glasses with side-shields.					
Hand protection	: Protective gloves.					
Skin and body protection	: I	Long sleeved clothing.				
Additional Protective Measures	: Safety shoes.					
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice Wash hands before breaks and at the end of workday.					
Engineering measures		: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
Exposure limit(s)						
Components	Value	Exposure		Exposure typ	e	List:
Titanium dioxide	10 mg/m3	Time Weighted (TWA)	-	Total dust.		ACGIH
	15 mg/m3	PEL:		Total dust.		OSHA Z1
	9. PHYSI	CAL AND CHEM	AICAL PRO	PERTIES		
					Not	annliachta
Form	: Solie	1	Evapor	ration rate :	100	applicable.
Appearance	: Pelle	ets	Specifi	ic Gravity :	Not	applicable. determined.
Appearance Color	: Pelle : ORA	ets ANGE	Specifi Bulk d	c Gravity : ensity :	Not Not	determined. established
Appearance Color Odor	: Pelle : ORA : Very	ets ANGE y faint	Specifi Bulk d Vapor	ic Gravity : ensity : pressure :	Not Not Not	determined. established applicable
Appearance Color Odor Melting point/range	: Pelle : ORA : Very : Not	ets ANGE y faint determined.	Specifi Bulk d Vapor Vapor	c Gravity : ensity :	Not Not Not Not	determined. established applicable applicable
Appearance Color Odor Melting point/range Boiling Point:	: Pelle : ORA : Very : Not : Not	ets ANGE y faint determined. applicable	Specifi Bulk d Vapor	ic Gravity : ensity : pressure :	Not Not Not Not	determined. established applicable
Appearance Color Odor Melting point/range	: Pelle : ORA : Very : Not	ets ANGE y faint determined. applicable	Specifi Bulk d Vapor Vapor	ic Gravity : ensity : pressure :	Not Not Not Not	determined. established applicable applicable
Appearance Color Odor Melting point/range Boiling Point:	: Pelle : ORA : Very : Not : Not : Inso	ets ANGE y faint determined. applicable	Specifi Bulk d Vapor Vapor pH	ic Gravity : ensity : pressure : density : :	Not Not Not Not	determined. established applicable applicable
Appearance Color Odor Melting point/range Boiling Point:	: Pelle : ORA : Very : Not : Not : Inso 10.5	ets ANGE y faint determined. applicable luble	Specifi Bulk d Vapor Vapor pH	ic Gravity : ensity : pressure : density : :	Not Not Not Not	determined. established applicable applicable
Appearance Color Odor Melting point/range Boiling Point: Water solubility	: Pelle : ORA : Very : Not : Not : Inso 10.5	ets ANGE y faint determined. applicable luble STABILITY ANI	Specifi Bulk d Vapor Vapor pH	ic Gravity : ensity : pressure : density : :	Not Not Not Not	determined. established applicable applicable
Appearance Color Odor Melting point/range Boiling Point: Water solubility Stability	: Pella : OR : Very : Not : Not : Inso 10.5 : S n : V	ets ANGE y faint determined. applicable luble STABILITY ANE Stable.	Specifi Bulk d Vapor pH DREACTIV	ts and open flame.	Not Not Not Not	determined. established applicable applicable applicable



MATERIAL SAFETY DATA SHEET

ORANGE

Version Number 1.0 Revision Date 11/28/2001 Page 4 of 5 Print Date 11/2/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ			
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.			
	12. ECOLOGI	CAL INFORMATION	I			
Persistence and degrad	lability : Not readily b	iodegradable.				
Environmental Toxicit		: Chemicals are not readily available as they are bound within the matrix of the polymer.				
Bioaccumulation Poter		: Chemicals are not readily available as they are bound within the matrix of the polymer.				
Additional advice	: No data avail	: No data available.				
	13. DISPOSAL	CONSIDERATIONS				
Product Contaminated packagi	recycling is p waste materia transportation state/provinc ng : Recycling is has the respo	 Like most thermoplastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. 				
	and local reg		neable federal, state/provincial			
	14. TRANSPO	RT INFORMATION				
U.S. D.O.T. / CA T.D. Classification (Non-bu ground)	e	Not regulated for transportation.				
ICAO/IATA : Not regulated for transportation.						
IMO / IMDG	: Not regulated	: Not regulated for transportation.				
	15 RECULAT	ORY INFORMATION	J			

MATERIAL SAFETY DATA SHEET



ORANGE		
Version Number 1.0 Revision Date 11/28/2001		Page 5 of 5 Print Date 11/2/2011
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on the TSCA inventory or are exempt.
California Proposition 65	:	This product does not contain a substance listed by California Prop 65.
Canadian Regulations:		
WHMIS Classification	:	D2B
WHMIS Ingredient Disc.	losu	are List
CAS-No. 150-13-0		
DSL	:	Listed.
National Inventories:		
Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Not determined.
Japan ENCS	:	Listed.
Korea KECI	:	Listed.
Philippines PICCS	:	Listed.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.