

#### MATERIAL SAFETY DATA SHEET

### Country Beige Sub

Version Number 1.2 Revision Date 01/20/2004

Page 1 of 6 Print Date *11/13/2011* 

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	Country Beige Sub
Product code	:	CC10006974
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous	7631-86-9	1 - 5
Titanium dioxide	13463-67-7	10 - 30

### 3. HAZARDS IDENTIFICATION

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Particulates, like other inert materials can be mechanically irritating. Excessive inhalation of product vapors, especially during heating or processing, may be irritating to respiratory system.
Ingestion	: May be harmful if swallowed.
Eyes	: Particulates, like other inert materials can be mechanically irritating.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



### MATERIAL SAFETY DATA SHEET

# Country Beige Sub

Version Number 1.2 Revision Date 01/20/2004 Page 2 of 6 Print Date 11/13/2011

Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> <li>Carbon dioxide blanket, water spray, dry powder, foamnone.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



### MATERIAL SAFETY DATA SHEET

# Country Beige Sub

Version Number 1.2 Revision Date 01/20/2004		Page 3 of 6 Print Date 11/13/2011
Handling	:	Take measures to prevent the build up of electrostatic charge Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXF	POSUR	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

Components	Value	Exposure time	Exposure type	List:
Silica, amorphous	20 mppcf	PEL:	Total dust.	OSHA
	20 mppcf	PEL:	Total dust.	Z3
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1

Form	: Solid	Evaporation rate	:	Not applicable
Appearance	: Pellets	Specific Gravity:	:	Not determined
Color	: TAN	Bulk density	:	Not established
Odor	: Very faint	Vapor pressure	:	Not applicable
Melting point/range	: Not determined	Vapour density	:	Not applicable
Boiling Point:	: Not applicable	pH	:	Not applicable
Water solubility	: Insoluble			
	10. STABILITY AND			
	IU. STADILITY ANL			
Stability	: Stable.			
	: Will not occur.			



## MATERIAL SAFETY DATA SHEET

### Country Beige Sub

Version Number 1.2 Page 4 of 6 Revision Date 01/20/2004 Print Date 11/13/2011 Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat. Incompatible Materials : Avoid contact with strong oxidizers. Also, avoid contact with acetal or acetal copolymers and with amine containing materials during processing. At processing conditions, these materials are mutually destructive and involve rapid degradation. Thoroughly purge and mechanically clean processing equipment to avoid even trace quantities of these materials from coming in contact with each other. Prevent cross contamination of feedstocks. Hazardous decomposition : Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen products (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

**11. TOXICOLOGICAL INFORMATION** 

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	C	hemical Name	Effect	Target Organ			
7631-86-9	Silica,	amorphous	Irritant	Eyes, Respiratory system.			
13463-67-7	Titaniu	m dioxide	Systemic effects	Respiratory system.			
12. ECOLOGICAL INFORMATION							
Persistence and degrad	lability	: Not readily bio	odegradable.				
Environmental Toxicity Bioaccumulation Potential			: Chemicals are not readily available as they are bound within the matr of the polymer.				
		: Chemicals are not readily available as they are bound within the matrix of the polymer.					
Additional advice		: No data availa	ble				
		13. DISPOSAL	CONSIDERATIONS	5			
Product		possible recyc generator of w classification,	ling is preferred to dis vaste material has the r	product can be recycled. Where sposal or incineration. The responsibility for proper waste posal in accordance with ind local regulations.			



MATERIAL SAFETY DATA SHEET	MA	TER	IAL	SAF	FETY	DATA	SHEET
----------------------------	----	-----	-----	-----	------	------	-------

# Country Beige Sub

Version Number 1.2 Revision Date 01/20/2004

Contaminated packaging :	:	Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.	
	1	4. TRANSPORT INFORMATION	
U.S. DOT Classification	:	Not regulated for transportation.	
ICAO/IATA (air)		Refer to specific regulation.	
IMO / IMDG (maritime)		Refer to specific regulation.	
 1	15	REGULATORY INFORMATION	
US Regulations:			
OSHA Status		Classified as hazardous based on components.	
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.	
US. EPA CERCLA Hazardous Su	bs	stances (40 CFR 302)	
Not applicable			
California Proposition : 65	:	WARNING! This product contains a chemical known to the State of California to cause cancer.	
SARA Title III Section 302 Extrem	me	ely Hazardous Substance	
Not applicable			
SARA Title III Section 313 Toxic	C	'hemicals:	
Not applicable Canadian Regulations:			
National Pollutant Release	Ir	ventory (NPRI)	
Not applicable			
WHMIS Classification :	:	D2B	

WHMIS Ingredient Disclosure List



### MATERIAL SAFETY DATA SHEET

### Country Beige Sub

Version Number 1.2 Revision Date 01/20/2004 Page 6 of 6 Print Date *11/13/2011* 

CAS-No. 7631-86-9			
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.	
National Inventories:			
Australia AICS	:	Not determined	
China IECS	:	Not determined	
Europe EINECS	:	Not determined	
Japan ENCS	:	Not determined	
Korea KECI	:	Not determined	
Philippines PICCS	:	Not determined	
		16. OTHER INFORMATION	1

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.