

MATERIAL SAFETY DATA SHEET

MAUVE-2

Version Number 1.0 Revision Date 12/12/2001 Page 1 of 5 Print Date 11/2/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	MAUVE-2
Product code	:	CC10007098
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Mica	12001-26-2	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

MAUVE-2

ion Number 1.0 sion Date 12/12/2001	Page 2 Print Date 11/2/2
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Autoignition temperature	: Not relevant
Suitable extinguishing media	: Carbon dioxide blanket, Water spray, dry powder, foam.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption





MAUVE-2

				1 10	nt Date 11/2/
	a	nd contamination. Kee	ep in a d	ry, cool place.	
8. I	EXPOSURE	CONTROLS / PERS	SONAL	PROTECTION	
Respiratory protection	: N	lo personal respiratory	protecti	ve equipment normall	y required.
Eye/Face Protection	: Safety glasses with side-shields.				
Hand protection	: Protective gloves.				
Skin and body protection	: L	: Long sleeved clothing.			
Additional Protective Measures	: Safety shoes.				
General Hygiene Considerations		landle in accordance w Vash hands before brea			l safety practic
Engineering measures		: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.			
Components	Value	Exposure time	;	Exposure type	List:
Components Mica	Value 3 mg/m3	Time Weighted Av		Exposure type Total dust.	List: ACGIH
	20 mppcf	(TWA): PEL:		Total dust.	OSHA
	9. PHYSIO	CAL AND CHEMIC	AL PRO	PERTIES	
_	~		Hyano	ration rate : N	ot applicable.
Form	: Solic				
Appearance	: Pelle	ets	Specif	ic Gravity : N	ot determined
Appearance Color	: Pelle : PINI	ets K	Specif Bulk d	ic Gravity : N ensity : N	ot determined ot established
Appearance Color Odor	: Pelle : PINI : Very	ets K 7 faint	Specif Bulk d Vapor	ic Gravity : N ensity : N pressure : N	ot determined ot established ot applicable
Appearance Color Odor Melting point/range	: Pelle : PINI : Very : Not	ets K v faint determined	Specif Bulk d Vapor Vapor	ic Gravity : N ensity : N pressure : N density : N	ot determined ot established ot applicable ot applicable
Appearance Color Odor Melting point/range Boiling Point:	: Pelle : PINI : Very : Not e : Not a	ets K v faint determined applicable	Specif Bulk d Vapor	ic Gravity : N ensity : N pressure : N density : N	ot determined ot established ot applicable
Appearance Color Odor Melting point/range	: Pelle : PINI : Very : Not	ets K v faint determined applicable	Specif Bulk d Vapor Vapor	ic Gravity : N ensity : N pressure : N density : N	ot determined ot established ot applicable ot applicable
Appearance Color Odor Melting point/range Boiling Point:	: Pelle : PINI : Very : Not e : Not e : Insol	ets K v faint determined applicable	Specif Bulk d Vapor Vapor pH	ic Gravity : N ensity : N pressure : N density : N : N	ot determined ot established ot applicable ot applicable
Appearance Color Odor Melting point/range Boiling Point:	: Pelle : PINI : Very : Not e : Not : : Insol	ets K 7 faint determined applicable luble	Specif Bulk d Vapor Vapor pH	ic Gravity : N ensity : N pressure : N density : N : N	ot determined ot established ot applicable ot applicable
Appearance Color Odor Melting point/range Boiling Point: Water solubility	: Pelle : PINI : Very : Not (: Not : : Insol 10. \$: S	ets K 7 faint determined applicable luble STABILITY AND RH	Specif Bulk d Vapor Vapor pH	ic Gravity : N ensity : N pressure : N density : N : N	ot determined ot established ot applicable ot applicable
Appearance Color Odor Melting point/range Boiling Point: Water solubility Stability	: Pelle : PINI : Very : Not (: Not : : Insol 	ets K 7 faint determined applicable luble STABILITY AND RH table.	Specif Bulk d Vapor Vapor pH EACTIV	ic Gravity : N ensity : N pressure : N density : N : N	ot determined ot established ot applicable ot applicable ot applicable



MATERIAL SAFETY DATA SHEET

MAUVE-2

Version Number 1.0 Revision Date 12/12/2001 Page 4 of 5 Print Date 11/2/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ			
12001-26-2	Mica	Systemic effects	Respiratory system.			
	12. ECOLOGIO	CAL INFORMATION	I			
Persistence and degrada	ability : Not readily b	iodegradable.				
Environmental Toxicity		: Chemicals are not readily available as they are bound within the of the polymer.				
Bioaccumulation Poten	tial : Chemicals ar of the polyme	micals are not readily available as they are bound within the matrix he polymer.				
Additional advice	: No data avail	able.				
	13. DISPOSAL	CONSIDERATIONS				
Product Contaminated packagin	recycling is p waste materia transportation state/provinc g : Recycling is	 Like most thermoplastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation 				
	and disposal	and disposal in accordance with applicable federal, state/provincial and local regulations.				
	14. TRANSPO	ORT INFORMATION				
U.S. D.O.T. / CA T.D. Classification (Non-bul ground)	e	Not regulated for transportation.				
ICAO/IATA	: Not regulated	: Not regulated for transportation.				
IMO / IMDG	: Not regulated	l for transportation.				
	15 RECHLAT	ORY INFORMATION	J			

MATERIAL SAFETY DATA SHEET



MAUVE-2 Version Number 1.0 Page 5 of 5 Print Date 11/2/2011 Revision Date 12/12/2001 US Regulations: **OSHA Status** : Classified as hazardous based on components. **TSCA Status** : All components of this product are listed on the TSCA inventory or are exempt. California Proposition : This product does not contain a substance listed by California Prop 65. 65 Canadian Regulations: WHMIS Classification : Not controlled. WHMIS Ingredient Disclosure List CAS-No. 1333-86-4 12001-26-2 150-13-0 18282-10-5 DSL : Listed. National Inventories: Australia AICS : Listed. China IECS Listed. : Europe EINECS Not determined. : Japan ENCS Not determined. : Korea KECI Listed. : **Philippines PICCS** : Listed.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.