

MATERIAL SAFETY DATA SHEET

ORANGE

Version Number 1.0 Revision Date 12/19/2001 Page 1 of 6 Print Date 11/2/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	ORANGE
Product code	:	CC10007344
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Rutile, antimony chromium buff	68186-90-3	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes. 		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		
Medical Conditions Aggravated by Exposure:	: None known.		



MATERIAL SAFETY DATA SHEET

ORANGE

ision Date 12/19/2001	Print Date 11/2/2
	A FIDOT AID MEACUDEC
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
-	11
Flammable Limits	
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Autoignition temperature	: Not relevant
Suitable extinguishing media	: Carbon dioxide blanket, Water spray, dry powder, foam.
Special Fire Fighting	: Fullface self-contained breathing apparatus (SCBA) used in positive
Procedures	pressure mode should be worn to prevent inhalation of airborne
	contaminants.
Unusual Fire/Explosion Hazards	: None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption





ORANGE

sion Number 1.0 ision Date 12/19/2001			Print	Page 3 o Date 11/2/20
	ar	nd contamination. Keep in a d	lry, cool place.	
8.1	EXPOSURE	CONTROLS / PERSONAL	PROTECTION	
Respiratory protection	: N	o personal respiratory protecti	ve equipment normally	required.
Eye/Face Protection	: Sa	afety glasses with side-shields		
Hand protection	: P1	rotective gloves.		
Skin and body protection	: L	ong sleeved clothing.		
Additional Protective Measures	: Sa	afety shoes.		
General Hygiene Considerations	: H W	andle in accordance with good Vash hands before breaks and a	l industrial hygiene and s at the end of workday.	afety practice.
Engineering measures		eat only in areas with appropr ppropriate exhaust ventilation		Provide
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Rutile, antimony chromium buff	0.5 mg/m3	Time Weighted Average (TWA):	Total dust. as Cr	ACGIH
	0.5 mg/m3	(TWA): PEL:	Total dust. as Cr	ACGIH OSHA Z1
	-	(TWA): PEL: Time Weighted Average		ACGIH
	0.5 mg/m3	(TWA): PEL:	Total dust. as Cr	ACGIH OSHA Z1
	0.5 mg/m3 0.5 mg/m3 0.5 mg/m3	(TWA): PEL: Time Weighted Average (TWA): PEL:	Total dust. as Cr as Sb Total dust. as Sb	ACGIH OSHA Z1 ACGIH
	0.5 mg/m3 0.5 mg/m3 0.5 mg/m3	(TWA): PEL: Time Weighted Average (TWA):	Total dust. as Cr as Sb Total dust. as Sb	ACGIH OSHA Z1 ACGIH
chromium buff	0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 9. PHYSIC : Solid	(TWA): PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO	Total dust. as Cr as Sb Total dust. as Sb DPERTIES ration rate : Not	ACGIH OSHA Z1 ACGIH OSHA Z1 applicable.
chromium buff	0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 9. PHYSIC : Solid : Pelle	(TWA): PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO L Evapo ts Specif	Total dust. as Cr as Sb Total dust. as Sb DPERTIES ration rate : Not ic Gravity : Not	ACGIH OSHA Z1 ACGIH OSHA Z1 applicable. determined
chromium buff chromium buff Form Appearance Color	0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 9. PHYSIC : Solid : Pelle : ORA	(TWA): PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO I Evapo Is Specif NGE Bulk d	Total dust. as Cr as Sb Total dust. as Sb DPERTIES ration rate : Not ic Gravity : Not lensity : Not	ACGIH OSHA Z1 ACGIH OSHA Z1 applicable. determined established
chromium buff Form Appearance Color Odor	0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 9. PHYSIC : Solid : Pelle : ORA : Very	(TWA): PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO I Evapo ts Specif NGE Bulk d faint Vapor	Total dust. as Cr as Sb Total dust. as Sb DPERTIES ration rate : Not ic Gravity : Not lensity : Not pressure : Not	ACGIH OSHA Z1 ACGIH OSHA Z1 applicable. determined established applicable
chromium buff chromium buff Form Appearance Color Odor Melting point/range	0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 9. PHYSIC : Solid : Pelle : ORA : Very : Not c	(TWA): PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO I Evapo ts Specif NGE Bulk d faint Vapor determined Vapor	Total dust. as Cr as Sb Total dust. as Sb DPERTIES ration rate : Not ic Gravity : Not lensity : Not pressure : Not density : Not	ACGIH OSHA Z1 ACGIH OSHA Z1 OSHA Z1 applicable. determined established applicable applicable
chromium buff Form Appearance Color Odor	0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 9. PHYSIC : Solid : Pelle : ORA : Very : Not c	(TWA): PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO I Evapo ts Specification NGE Bulk do faint Vapor determined Vapor applicable pH	Total dust. as Cr as Sb Total dust. as Sb DPERTIES ration rate : Not ic Gravity : Not lensity : Not pressure : Not density : Not	ACGIH OSHA Z1 ACGIH OSHA Z1 applicable. determined established applicable
chromium buff chromium buff Form Appearance Color Odor Melting point/range Boiling Point:	0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 9. PHYSIC : Solid : Pelle : ORA : Very : Not c : Not a : Insol	(TWA): PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO I Evapo ts Specification NGE Bulk do faint Vapor determined Vapor applicable pH	Total dust. as Cr as Sb Total dust. as Sb DPERTIES ration rate : Not ic Gravity : Not pressure : Not density : Not : Not	ACGIH OSHA Z1 ACGIH OSHA Z1 applicable. determined established applicable applicable
chromium buff chromium buff Form Appearance Color Odor Melting point/range Boiling Point:	0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 9. PHYSIC : Solid : Pelle : ORA : Very : Not c : Not a : Insol 10. S	(TWA): PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO I Evapo ts Specif NGE Bulk d faint Vapor applicable pH uble Uble	Total dust. as Cr as Sb Total dust. as Sb DPERTIES ration rate : Not ic Gravity : Not pressure : Not density : Not : Not	ACGIH OSHA Z1 ACGIH OSHA Z1 applicable. determined established applicable applicable
chromium buff chromium buff buff Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 9. PHYSIC : Solid : Pelle : ORA : Very : Not c : Not a : Insol 10. S	(TWA): PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO I Evapo ts Specification faint Vapor applicable pH uble	Total dust. as Cr as Sb Total dust. as Sb DPERTIES ration rate : Not ic Gravity : Not pressure : Not density : Not : Not	ACGIH OSHA Z1 ACGIH OSHA Z1 applicable. determined established applicable applicable



MATERIAL SAFETY DATA SHEET

ORANGE

Version Number 1.0 Revision Date 12/19/2001	Page 4 of 6 Print Date 11/2/2011		
Incompatible Materials Hazardous decomposition	 Incompatible with strong acids and oxidizing agents. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOn), ather beganders metricle, and enable are all passible. 		
products	(NOx), other hazardous materials, and smoke are all possible. 11. TOXICOLOGICAL INFORMATION		
This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.			
<u>Toxicity Overview</u> This product contains the foll	owing components which in their pure form have the following characteristics:		

CAS-No.	Chemical Name	Effect	Target Organ
68186-90-3	Rutile, antimony	Irritant	Eyes, Skin.
	chromium buff		

Additional Health Hazard Information:

Rutile, antimony chromium buff 68186-90-3 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastics the product can be recycled. Where possibl recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION



MATERIAL SAFETY DATA SHEET

ORANGE				
Version Number 1.0 Revision Date 12/19/2001			Print	Page 5 of 6 Date 11/2/2011
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: Not regulated	for transportation.		
ICAO/IATA	: Not regulated	for transportation.		
IMO / IMDG	: Not regulated	for transportation.		
	15. REGULATO	RY INFORMATIO	N	
US Regulations:				
OSHA Status	: Classified as h	azardous based on co	omponents.	
TSCA Status	: All componen exempt.	ts of this product are l	isted on the TSCA in	iventory or are
California Proposition : This product does not contain a substance listed by California Prop 65. 65				
SARA Title III Section 313 To	xic Chemicals:			
Chemical Name	;	CAS-No.	Weight %	
	II COMPOUNDS	68186-90-3	6.31	

Chemical Name	CAS-No.	Weight %
CHROMIUM III COMPOUNDS ANTIMONY COMPOUNDS	68186-90-3	6.31

Canadian Regulations:

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

CAS-No.	
1333-86-4	
1309-37-1	
68186-90-3	

DSL

: Listed.

National Inventories:

Australia AICS	:	Not determined.
China IECS	:	Not determined.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Not determined.



Page 6 of 6

Print Date 11/2/2011

MATERIAL SAFETY DATA SHEET

ORANGE

Version Number 1.0 Revision Date 12/19/2001

Philippines PICCS

: Not determined.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.