

MATERIAL SAFETY DATA SHEET

PURPLE TYPE F 20000033

Version Number 1.0 Revision Date 12/16/2001 Page 1 of 6 Print Date 11/2/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PURPLE TYPE F 20000033
Product code	:	CC10007374
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Carbon black	1333-86-4	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes Skin	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Particulates, like other inert materials can be mechanically irritating. Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

PURPLE TYPE F 20000033

Version Number 1.0 Revision Date 12/16/2001 Page 2 of 6 Print Date 11/2/2011

		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5	5. FIRE-FIGHTING MEASURES
Flash point	:	Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	: : :	Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, dry powder, foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. none
	6. AC	CIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by scoop or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption



MATERIAL SAFETY DATA SHEET

PURPLE TYPE F 20000033

Version Number 1.0 Revision Date 12/16/2001 Page 3 of 6 Print Date 11/2/2011

		nd contamination. Keep i	n u urj, coor pr		
8. H	EXPOSURE	CONTROLS / PERSON	NAL PROTEC'	TION	
Respiratory protection		No personal respiratory pro usty conditions occur wea			
Eye/Face Protection	: sa	afety glasses			
Hand protection	: P	rotective gloves.			
Skin and body protection	: L	ong sleeved clothing.			
Additional Protective Measures	: S	afety shoes.			
General Hygiene Considerations	р	Vash hands and face befor roduct. Handle in accorda ractice for diagnostics.			
Engineering measures		Heat only in areas with app ppropriate exhaust ventila			Provide
Exposure limit(s)					
	Value	Exposure time	Expo	sure type	List [.]
Components Carbon black	Value 3.5 mg/m3	Exposure time Time Weighted Avera (TWA):		sure type al dust.	List: ACGIH
Components			ge Tot		
Components	3.5 mg/m3 3.5 mg/m3	Time Weighted Avera (TWA):	ge Tot Tot	al dust. al dust.	ACGIH
Components Carbon black	3.5 mg/m3 3.5 mg/m3 9. PHYSIC	Time Weighted Avera (TWA): PEL: CAL AND CHEMICAL	ge Tot Tot PROPERTIES	al dust. al dust. S	ACGIH OSHA Z1
Components Carbon black Form	3.5 mg/m3 3.5 mg/m3 9. PHYSIC : Solid	Time Weighted Avera (TWA): PEL: CAL AND CHEMICAL	ge Tot Tot PROPERTIES vaporation rate	al dust. al dust. 5 : Not	ACGIH OSHA Z1 applicable.
Components Carbon black Form Appearance	3.5 mg/m3 3.5 mg/m3 9. PHYSIC	Time Weighted Avera (TWA): PEL: CAL AND CHEMICAL d E es S	ge Tot Tot PROPERTIES vaporation rate pecific Gravity	al dust. al dust. 5 : Not : Not	ACGIH OSHA Z1
Components Carbon black Form Appearance Color	3.5 mg/m3 3.5 mg/m3 9. PHYSIC : Solic : flake : PUR	Time Weighted Avera (TWA): PEL: CAL AND CHEMICAL d E es Sj PLE B	ge Tot Tot PROPERTIES vaporation rate	al dust. al dust. 5 : Not : Not : Not : Not	ACGIH OSHA Z1 applicable. determined
Components Carbon black Form Appearance Color Odor	3.5 mg/m3 3.5 mg/m3 9. PHYSIC : Solic : flake : PUR : Very	Time Weighted Avera (TWA): PEL: CAL AND CHEMICAL d E es Sj PLE B y faint V	ge Tot Tot PROPERTIES vaporation rate pecific Gravity ulk density	al dust. al dust. 5 5 2 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	ACGIH OSHA Z1 applicable. determined determined
Components Carbon black Form Appearance Color Odor Melting point/range	3.5 mg/m3 3.5 mg/m3 9. PHYSIC : Solic : flake : PUR : Very : Grea	Time Weighted Avera (TWA): PEL: CAL AND CHEMICAL d E es Sj PLE B y faint V	ge Tot Tot PROPERTIES vaporation rate pecific Gravity ulk density apor pressure apor density	al dust. al dust. 5 5 5 7 8 7 8 7 8 7 8 7 8 7 8 7 8 7 8 7	ACGIH OSHA Z1 applicable. determined determined determined
Components Carbon black Form Appearance Color Odor Melting point/range Boiling Point:	3.5 mg/m3 3.5 mg/m3 9. PHYSIC : Solic : flake : PUR : Very : Grea	Time Weighted Avera (TWA): PEL: CAL AND CHEMICAL d E cs S PLE B / faint V tter than 130 Deg C V applicable pl	ge Tot Tot PROPERTIES vaporation rate pecific Gravity ulk density apor pressure apor density	al dust. al dust. 5 5 5 7 8 7 8 7 8 7 8 7 8 7 8 7 8 7 8 7	ACGIH OSHA Z1 applicable. determined determined determined determined
Components Carbon black Form Appearance Color Odor Melting point/range Boiling Point:	3.5 mg/m3 3.5 mg/m3 9. PHYSIC : Solic : flake : PUR : Very : Grea : Not : Insol	Time Weighted Avera (TWA): PEL: CAL AND CHEMICAL d E cs S PLE B / faint V tter than 130 Deg C V applicable pl	ge Tot Tot PROPERTIES vaporation rate pecific Gravity ulk density apor pressure apor density H	al dust. al dust. 5 5 5 7 8 7 8 7 8 7 8 7 8 7 8 7 8 7 8 7	ACGIH OSHA Z1 applicable. determined determined determined determined
Components Carbon black Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	3.5 mg/m3 3.5 mg/m3 9. PHYSIC : Solic : flake : PUR : Very : Grea : Not : Insol 10. §	Time Weighted Avera (TWA): PEL: CAL AND CHEMICAL d E S CAL AND CHEMICAL d E taint E v faint V ter than 130 Deg C V applicable pl luble	ge Tot Tot PROPERTIES vaporation rate pecific Gravity ulk density apor pressure apor density H	al dust. al dust. 5 5 5 7 8 7 8 7 8 7 8 7 8 7 8 7 8 7 8 7	ACGIH OSHA Z1 applicable. determined determined determined determined
Components Carbon black Carbon black Form Appearance Color Odor Melting point/range Boiling Point: Water solubility Stability	3.5 mg/m3 3.5 mg/m3 9. PHYSIC : Solid : flake : PUR : Very : Grea : Not : : Insol 10. S : S	Time Weighted Avera (TWA): PEL: CAL AND CHEMICAL d E es S PLE B 7 faint V ter than 130 Deg C V applicable pl luble	ge Tot Tot PROPERTIES vaporation rate pecific Gravity ulk density apor pressure apor density H	al dust. al dust. 5 5 5 7 8 7 8 7 8 7 8 7 8 7 8 7 8 7 8 7	ACGIH OSHA Z1 applicable. determined determined determined determined
Components Carbon black	3.5 mg/m3 3.5 mg/m3 9. PHYSIC : Solid : flake : PUR : Very : Grea : Not : Insol 10. S : S n : V	Time Weighted Avera, (TWA): PEL: CAL AND CHEMICAL d E cs Sj PLE B / faint V ter than 130 Deg C V applicable pl luble STABILITY AND REAC	ge Tot Tot PROPERTIES vaporation rate pecific Gravity ulk density apor pressure apor density H	al dust. al dust. S S C Not Not Not Not	ACGIH OSHA Z1 applicable. determined determined determined determined



MATERIAL SAFETY DATA SHEET

PURPLE TYPE F 20000033

Version Number 1.0 Revision Date 12/16/2001 Page 4 of 6 Print Date 11/2/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	> 15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1333-86-4	Carbon black	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.



MATERIAL SAFETY DATA SHEET

PURPLE TYPE F 20000033

Version Number 1.0 Revision Date 12/16/2001 Page 5 of 6 Print Date 11/2/2011

Demoistance and demoistance	Not modily biodogradshi-
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matri of the polymer.
Bioaccumulation Potential	: Not inherently biodegradable.
Additional advice	: Chemicals are not readily available as they are bound within the matri of the polymer.
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. Th generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: Not regulated for transportation.
ICAO/IATA	: Not regulated for transportation.
IMO / IMDG	: Not regulated for transportation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on the TSCA inventory or ar exempt.
California Proposition 65	: This product does not contain a substance listed by California Prop 65
Canadian Regulations:	
WHMIS Classification	: D2A



MATERIAL SAFETY DATA SHEET

PURPLE TYPE F 20000033

Version Number 1.0 Revision Date 12/16/2001 Page 6 of 6 Print Date 11/2/2011

WHMIS Ingredient Dis	sclosu	ire List
CAS-No. 1333-86-4		
DSL	:	Listed.
National Inventories:		
Australia AICS	:	Not determined.
China IECS	:	Not determined.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Not determined.
Philippines PICCS	:	Not determined.
		16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.