

MATERIAL SAFETY DATA SHEET

LASERMARK G

Version Number 1.1 Revision Date 01/29/2002 Page 1 of 6 Print Date 11/3/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	LASERMARK G
Product code	:	CC10007712
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
C.I. Pigment Black 23	68187-54-2	1 - 5
Mica	12001-26-2	1 - 5
Silica, amorphous	7631-86-9	1 - 5
Titanium dioxide	13463-67-7	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

: Inhalation, Ingestion, Skin contact		
Resin particles, like other inert materials, can be mechanically irritating.May be harmful if swallowed.		
: Resin particles, like other inert materials, are mechanically irritating to eyes.		
: Experience shows no unusual dermatitis hazard from routine handling.		
: Refer to Section 11 for Toxicological Information.		





LASERMARK G Version Number 1.1 Page 2 of 6 Revision Date 01/29/2002 Print Date 11/3/2011 **Medical Conditions** : None known. Aggravated by Exposure: 4. FIRST AID MEASURES Move to fresh air in case of accidental inhalation of fumes from Inhalation overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice. Do not induce vomiting without medical advice. When symptoms Ingestion : persist or in all cases of doubt seek medical advice. Eyes : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention. Skin : Wash off with soap and plenty of water. If skin irritation persists seek medical attention. **5. FIRE-FIGHTING MEASURES** Flash point : Not applicable Flammable Limits Upper explosion limit Not applicable : Lower explosion limit Not applicable : Autoignition temperature Not relevant : Suitable extinguishing media : Carbon dioxide blanket, Water spray, dry powder, foam. Special Fire Fighting Fullface self-contained breathing apparatus (SCBA) used in positive : Procedures pressure mode should be worn to prevent inhalation of airborne contaminants. Unusual Fire/Explosion None • Hazards 6. ACCIDENTAL RELEASE MEASURES Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. Environmental precautions Should not be released into the environment. The product should not : be allowed to enter drains, water courses or the soil. Methods for cleaning up Clean up promptly by sweeping or vacuum. Package all material in : plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods. 7. HANDLING AND STORAGE Handling Take measures to prevent the build up of electrostatic charge. Heat · only in areas with appropriate exhaust ventilation.

MATERIAL SAFETY DATA SHEET

LASERMARK G

P	bly	One.
	-	

Version Number 1.1 Revision Date 01/29/2002		Page 3 of 6 Print Date <i>11/3/2011</i>
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXP	OSUR	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
C.I. Pigment Black 23	0.5 mg/m3	Time Weighted Average	as Sb	ACGIH
		(TWA):		
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average	as Sb	MX OEL
		(TWA):		
Mica	3 mg/m3	Time Weighted Average	Total dust.	ACGIH
		(TWA):		
	20 mppcf	PEL:	Total dust.	OSHA
Silica, amorphous	20 mppcf	PEL:	Total dust.	OSHA
	20 mppcf	PEL:	Total dust.	Z3
Titanium dioxide	10 mg/m3	Time Weighted Average	Total dust.	ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1

appropriate exhaust ventilation at machinery.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color Odor Melting point/range Boiling Point: Water solubility : Solid
: Pellets
: WHITE
: Very faint
: Not determined
: Not applicable
: Insoluble

Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH Not applicable.
Not determined
Not established
Not applicable
Not applicable
Not applicable



MATERIAL SAFETY DATA SHEET

LASERMARK G

Version Number 1.1 Revision Date 01/29/2002 Page 4 of 6 Print Date 11/3/2011

	10. STABILITY AND REACTIVITY
Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
68187-54-2	C.I. Pigment Black 23	Irritant	Eyes, Skin.
12001-26-2	Mica	Systemic effects	Respiratory system.
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia



MATERIAL SAFETY DATA SHEET

LASERMARK G

ion Number 1.1 sion Date 01/29/2002			Print D	Page ate 11/3
		n accordance with app	ste classification, translicable federal, state/p	
	14. TRANSPOL	RT INFORMATION	[
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: Not regulated	for transportation.		
ICAO/IATA	: Not regulated	for transportation.		
IMO / IMDG	: Not regulated	for transportation.		
	15. REGULATO	ORY INFORMATIO	N	
US Regulations:				
OSHA Status	: Classified as I	hazardous based on co	mponents.	
TSCA Status	: All componen exempt.	ts of this product are l	isted on the TSCA inv	entory of
California Proposition 65	: This product of	loes not contain a sub	stance listed by Califo	rnia Prop
-	-	does not contain a sub	stance listed by Califo	rnia Prop
65 SARA Title III Section 313 Tox Chemical Name	tic Chemicals:	CAS-No.	Weight %	rnia Proț
65 SARA Title III Section 313 Tox	tic Chemicals:			rnia Proț]
65 SARA Title III Section 313 Tox Chemical Name	tic Chemicals:	CAS-No.	Weight %	rnia Prop
65 SARA Title III Section 313 Tox Chemical Name ANTIMONY CO	tic Chemicals:	CAS-No.	Weight %	rnia Prop
65 SARA Title III Section 313 Tox Chemical Name ANTIMONY CO Canadian Regulations:	ic Chemicals:	CAS-No.	Weight %	rnia Prop
65 SARA Title III Section 313 Tox Chemical Name ANTIMONY CO Canadian Regulations: WHMIS Classification	ic Chemicals:	CAS-No.	Weight %	rnia Prop
65 SARA Title III Section 313 Tox Chemical Name ANTIMONY CO Canadian Regulations: WHMIS Classification WHMIS Ingredient Disc CAS-No. 68187-54-2 12001-26-2	ic Chemicals:	CAS-No.	Weight %	rnia Prop
65 SARA Title III Section 313 Tox Chemical Name ANTIMONY CO Canadian Regulations: WHMIS Classification WHMIS Ingredient Disc CAS-No. 68187-54-2 12001-26-2 7631-86-9	ic Chemicals:	CAS-No.	Weight %	rnia Prop
65 SARA Title III Section 313 Tox Chemical Name ANTIMONY CO Canadian Regulations: WHMIS Classification WHMIS Ingredient Disc CAS-No. 68187-54-2 12001-26-2 7631-86-9 DSL	ic Chemicals:	CAS-No. 68187-54-2	Weight %	rnia Prop



MATERIAL SAFETY DATA SHEET

LASERMARK G

Version Number 1.1 Revision Date 01/29/2002			Page 6 of 6 Print Date 11/3/2011
Europe EINECS	:	Not determined.	
Japan ENCS	:	Not determined.	
Korea KECI	:	Listed.	
Philippines PICCS	:	Listed.	
		16 OTHER INFORMATION	

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.