

MATERIAL SAFETY DATA SHEET

GRAY

Version Number 1.0 Revision Date 01/23/2002 Page 1 of 6 Print Date 11/3/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902	
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).	
Product name	:	GRAY	
Product code	:	CC10008770	
Chemical Name	:	Mixture	
CAS-No.	:	Mixture	
Product Use	:	Industrial Applications	

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Rutile, antimony chromium buff	68186-90-3	1 - 5
Silica, amorphous	7631-86-9	1 - 5
Titanium dioxide	13463-67-7	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact	
Acute exposure		
Inhalation Ingestion	Resin particles, like other inert materials, can be mechanically irritating.May be harmful if swallowed.	
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.	
Skin	: Experience shows no unusual dermatitis hazard from routine handling.	
Chronic exposure	: Refer to Section 11 for Toxicological Information.	



MATERIAL SAFETY DATA SHEET

GRAY

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, dry powder, foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

MATERIAL SAFETY DATA SHEET



GRAY

ion Number 1.0 sion Date 01/23/2002			Prir	Page 3 nt Date <u>11/3/2</u>	
Storage		eep containers dry and tightly and contamination. Keep in a		ure absorption	
8. 1	EXPOSURE	CONTROLS / PERSONAL	PROTECTION		
Respiratory protection	: N	o personal respiratory protect	tive equipment normall	y required.	
Eye/Face Protection	: S	afety glasses with side-shield	s.		
Hand protection	: P:	rotective gloves.			
Skin and body protection	: L	ong sleeved clothing.			
Additional Protective Measures	: S	: Safety shoes.			
General Hygiene Considerations		andle in accordance with goo Vash hands before breaks and			
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
Exposure limit(s)					
Components	Value	Exposure time	Exposure type	List:	
Rutile, antimony chromium buff	0.5 mg/m3	Time Weighted Average (TWA):	Total dust. as Cr	ACGIH	
	0.5 mg/m3	PEL:	Total dust. as Cr	OSHA Z1	
	0.5 mg/m3	Time Weighted Average (TWA):	Dust. as Sb	ACGIH	
	0.5 mg/m3	PEL:	Total dust. as Sb	OSHA Z1	
Silica, amorphous	20 mppcf	PEL:	Total dust.	OSHA	
	20 mppcf	PEL:	Total dust.	Z3	
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH	
	15 mg/m3	PEL:	Total dust.	OSHA Z1	
	9. PHYSIC	CAL AND CHEMICAL PR	OPERTIES		
Form	: Solid	l Evapo	oration rate : N	ot applicable.	
Appearance	: Pelle		fic Gravity : N	ot determined	
Color	: GRE		•	ot established	
				ot applicable	
Odor				ot applicable	
Odor Melting point/range					
Odor		applicable pH	: N	ot applicable	

GRAY

MATERIAL SAFETY DATA SHEET



Version Number 1.0 Page 4 of 6 Print Date 11/3/2011 Revision Date 01/23/2002 Stability : Stable. Hazardous Polymerization : Will not occur. Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat. Incompatible Materials : Incompatible with strong acids and oxidizing agents. : Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen Hazardous decomposition (NOx), other hazardous materials, and smoke are all possible. products

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
68186-90-3	Rutile, antimony	Irritant	Eyes, Skin.
	chromium buff		
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Additional Health Hazard Information:

Rutile, antimony chromium buff 68186-90-3 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastics the product can be recycled. Where possibl recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal,



MATERIAL SAFETY DATA SHEET

rsion Number 1.0 vision Date 01/23/2002			Print	Page 5 of Date <u>11/3/20</u> 3
	state/provincial	and local regulation	s.	
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.			nsportation
	14. TRANSPOR	T INFORMATION		
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: Not regulated f	or transportation.		
ICAO/IATA	: Not regulated f	or transportation.		
IMO / IMDG	: Not regulated f	or transportation.		
	15. REGULATOI	RY INFORMATIO	N	
US Regulations:				
-				
OSHA Status	: Classified as ha	azardous based on co	mponents.	
TSCA Status	: All components exempt.	s of this product are l	isted on the TSCA in	ventory or are
California Proposition 65	: This product do	pes not contain a subs	stance listed by Calif	ornia Prop 65.
SARA Title III Section 313 To	xic Chemicals:			
Chemical Name		CAS-No.	Weight %	
	CHROMIUM III COMPOUNDS ANTIMONY COMPOUNDS		1.43	
Canadian Regulations:				
WHMIS Classification	: D2B			
	closure List			
WHMIS Ingredient Disc				
WHMIS Ingredient Disc CAS-No. 1333-86-4 68186-90-3 7631-86-9				



MATERIAL SAFETY DATA SHEET

GRAY

Version Number 1.0 Revision Date 01/23/2002		Page 6 of 6 Print Date 11/3/2011	
Australia AICS	: Listed.		
China IECS	: Listed.		
Europe EINECS	: Not determined.		
Japan ENCS	Not determined.		
Korea KECI	: Listed.		
Philippines PICCS	: Listed.		
16. OTHER INFORMATION			

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.