

MATERIAL SAFETY DATA SHEET

RITZ SILVER

Version Number 1.0 Revision Date 01/24/2002 Page 1 of 6 Print Date 11/3/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	RITZ SILVER
Product code	:	CC10008790
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Aluminum	7429-90-5	1 - 5
Titanium dioxide	13463-67-7	5 - 10
Mica	12001-26-2	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion	Resin particles, like other inert materials, can be mechanically irritating.May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.





ion Number 1.0 sion Date 01/24/2002	Page 2 Print Date 11/3/2
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, dry powder, foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

MATERIAL SAFETY DATA SHEET

RITZ SILVER



Version Number 1.0 Revision Date 01/24/2002		Page 3 of 6 Print Date 11/3/2011
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXP(DSUR	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Aluminum	10 mg/m3	Time Weighted Average	Dust.	ACGIH
		(TWA):		
	5 mg/m3	Time Weighted Average	Welding fume. as Al	ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust. as Al	OSHA Z1
	5 mg/m3	PEL:	Respirable dust. as Al	OSHA Z1
Mica	3 mg/m3	Time Weighted Average	Total dust.	ACGIH
		(TWA):		
	20 mppcf	PEL:	Total dust.	OSHA
Titanium dioxide	10 mg/m3	Time Weighted Average	Total dust.	ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- Solid
 Pellets
 GREY
 Very faint
 Not determined
 Not applicable
 Insoluble
- Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH
- Not applicable.
 Not determined
 Not established
 Not applicable
 Not applicable
 Not applicable
 Not applicable



MATERIAL SAFETY DATA SHEET

RITZ SILVER

Version Number 1.0 Revision Date 01/24/2002 Page 4 of 6 Print Date 11/3/2011

	10. STABILITY AND REACTIVITY
Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7429-90-5	Aluminum	Irritant	Skin, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
12001-26-2	Mica	Systemic effects	Respiratory system.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia



MATERIAL SAFETY DATA SHEET

RITZ SILVER

sion Date 01/24/2002			Print D	Page 5 Date 11/3/2
		accordance with ap	aste classification, tran plicable federal, state/j	
	14. TRANSPOR	T INFORMATION	N	
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: Not regulated f	or transportation.		
ICAO/IATA	: Not regulated f	or transportation.		
IMO / IMDG	: Not regulated f	or transportation.		
	15. REGULATO	RY INFORMATIC	N	
US Regulations:				
OSHA Status	: Classified as ha	zardous based on co	omponents.	
TSCA Status			listed on the TSCA inv	entory or are
California Propositio	n : This product do	as not contain a sub	stance listed by Califo	rnia Prop 65
65	ii . This product de		statee by came	iniu i top oo
_		es not contain a suc		
65 SARA Title III Section 313	Toxic Chemicals:	CAS-No.	Weight %]
65 SARA Title III Section 313 Chemical Nat ALUMINUM	Toxic Chemicals:]
65 SARA Title III Section 313 Chemical Nat ALUMINUM Canadian Regulations:	Toxic Chemicals: me I (FUME OR DUST)	CAS-No.	Weight %]
65 SARA Title III Section 313 Chemical Nat ALUMINUM	Toxic Chemicals: me I (FUME OR DUST)	CAS-No.	Weight %]
65 SARA Title III Section 313 Chemical Nat ALUMINUM Canadian Regulations:	Toxic Chemicals: me I (FUME OR DUST) on : D2B	CAS-No.	Weight %]
65 SARA Title III Section 313 Chemical Nat ALUMINUM Canadian Regulations: WHMIS Classification	Toxic Chemicals: me I (FUME OR DUST) on : D2B	CAS-No.	Weight %]
65 SARA Title III Section 313 Chemical Nat ALUMINUM Canadian Regulations: WHMIS Classification WHMIS Ingredient D CAS-No. 7429-90-5 12001-26-2	Toxic Chemicals: me I (FUME OR DUST) on : D2B	CAS-No.	Weight %]
65 SARA Title III Section 313 Chemical Nat ALUMINUM Canadian Regulations: WHMIS Classification WHMIS Ingredient D CAS-No. 7429-90-5 12001-26-2 68186-90-3	Toxic Chemicals: me I (FUME OR DUST) on : D2B Disclosure List	CAS-No.	Weight %]
65 SARA Title III Section 313 (Chemical Nat ALUMINUM Canadian Regulations: WHMIS Classification WHMIS Ingredient D CAS-No. 7429-90-5 12001-26-2 68186-90-3 DSL	Toxic Chemicals: me I (FUME OR DUST) on : D2B Disclosure List	CAS-No.	Weight %]



MATERIAL SAFETY DATA SHEET

RITZ SILVER

Version Number 1.0 Page 6 of 6 Revision Date 01/24/2002 Print Date 11/3/2011 Europe EINECS : Not determined. Japan ENCS Not determined. : Korea KECI : Listed. Philippines PICCS : Listed.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.