

MATERIAL SAFETY DATA SHEET

# **YELLOW 116C FROST**

Version Number 1.0 Revision Date 01/20/2002 Page 1 of 5 Print Date 11/3/2011

# 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	YELLOW 116C FROST
Product code	:	CC10008929
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Barium sulfate	7727-43-7	30 - 60

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	<ul> <li>Resin particles, like other inert materials, can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Resin particles, like other inert materials, are mechanically irritating to eyes.</li> </ul>
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

# **YELLOW 116C FROST**

Version Number 1.0 Revision Date 01/20/2002 Page 2 of 5 Print Date 11/3/2011

		4. FIRST AID MEASURES
Inhalation       : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice.		
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	: :	Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, dry powder, foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage		Keep containers dry and tightly closed to avoid moisture absorption



Page 3 of 5

MATERIAL SAFETY DATA SHEET

# YELLOW 116C FROST

Version Number 1.0 Revision Date 01/20/2002

evision Date 01/20/2002				Pri	int Date	e 11/3/2011
	aı	nd contamination. Keep	in a di	ry, cool place.		
8. E	XPOSURE	CONTROLS / PERSO	NAL	PROTECTION		
Respiratory protection	: N	o personal respiratory p	rotectiv	ve equipment normal	ly requi	ired.
Eye/Face Protection	: S	afety glasses with side-s	hields.			
Hand protection	: P	rotective gloves.				
Skin and body protection	: L	ong sleeved clothing.				
Additional Protective Measures	: S	afety shoes.				
General Hygiene Considerations		andle in accordance with ash hands before breaks				y practice.
Engineering measures		eat only in areas with appropriate exhaust ventil			on. Pro	vide
Exposure limit(s)						
Components	Value	Exposure time		Exposure type		List:
Barium sulfate	10 mg/m3	Time Weighted Aver (TWA):	age	Total dust.	1	ACGIH
	5 mg/m3 15 mg/m3	PEL: PEL:		Respirable fraction Total dust.		SHA Z1 SHA Z1
· · · · · · · · · · · · · · · · · · ·						
	9. PHYSIC	CAL AND CHEMICAI	L PRO	PERTIES		
Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	: Very : Not c	ts S LOW I faint S determined S applicable I	Specifi Bulk de Vapor	c Gravity : M ensity : M pressure : M density : M		ermined blished licable licable
	10. S	TABILITY AND REA	CTIV	ITY		
Stability		table.				
Hazardous Polymerization	1 : W	/ill not occur.				
Conditions to avoid		eep away from oxidizin ecomposition, do not ov		-	`o avoid	thermal
Incompatible Materials	: Ir	acompatible with strong	acids a	and oxidizing agents.		



MATERIAL SAFETY DATA SHEET

# **YELLOW 116C FROST**

Version Number 1.0 Revision Date 01/20/2002 Page 4 of 5 Print Date 11/3/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

## 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

Γ

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7727-43-7	Barium sulfate	Irritant	Respiratory system.
		Systemic effects	Eyes, Respiratory system.

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. D.O.T. / CA T.D.G.	: Not regulated for transportation.
Classification (Non-bulk ground)	
Classification (Non-bulk	: Not regulated for transportation.



MATERIAL SAFETY DATA SHEET

# **YELLOW 116C FROST**

Version Number 1.0 Revision Date 01/20/2002 Page 5 of 5 Print Date 11/3/2011

	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on the TSCA inventory or are exempt.
California Proposition 65	: This product does not contain a substance listed by California Prop 65.
Canadian Regulations:	
WHMIS Classification	: D2B
DSL	: Listed.
National Inventories:	
Australia AICS	: Listed.
China IECS	: Listed.
Europe EINECS	: Not determined.
Japan ENCS	: Not determined.
Korea KECI	: Listed.
Philippines PICCS	: Listed.

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.