

MATERIAL SAFETY DATA SHEET

PMS 3935C YELLOW GRANITE

Version Number 1.0 Revision Date 01/28/2002 Page 1 of 5 Print Date 11/3/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PMS 3935C YELLOW GRANITE
Product code	:	CC10009373
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Mica	12001-26-2	10 - 30
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation Ingestion Eyes Skin	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes. Experience shows no unusual dermatitis hazard from routine handling. 		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		
Medical Conditions Aggravated by Exposure:	: None known.		



MATERIAL SAFETY DATA SHEET

PMS 3935C YELLOW GRANITE

Version Number 1.0 Revision Date 01/28/2002 Page 2 of 5 Print Date 11/3/2011

		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion	::	Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, dry powder, foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
Hazards	<	
	6. A(CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption



MATERIAL SAFETY DATA SHEET

PMS 3935C YELLOW GRANITE

Version Number 1.0 Revision Date 01/28/2002

Water solubility

Page 3 of 5 Print Date 11/3/2011

	a	nd contamination. Keep in a d	lry, cool place.			
8. 1	EXPOSURE	CONTROLS / PERSONAL	PROTECTION			
Respiratory protection	: N	No personal respiratory protective equipment normally required.				
Eye/Face Protection	: S	afety glasses with side-shields				
Hand protection	: P	rotective gloves.				
Skin and body protection	: L	ong sleeved clothing.				
Additional Protective Measures	: S	afety shoes.				
General Hygiene Considerations		Iandle in accordance with good Vash hands before breaks and a		safety practice		
Engineering measures		leat only in areas with appropriate exhaust ventilation		Provide		
Exposure limit(s)						
Exposure limit(s) Components	Value	Exposure time	Exposure type	List:		
	Value 3 mg/m3	Exposure time Time Weighted Average (TWA):	Exposure type Total dust.	List: ACGIH		
Components		Time Weighted Average				
Components	3 mg/m3	Time Weighted Average (TWA): PEL: Time Weighted Average	Total dust.	ACGIH		
Components Mica	3 mg/m3 20 mppcf	Time Weighted Average (TWA): PEL:	Total dust. Total dust.	ACGIH OSHA		
Components Mica	3 mg/m3 20 mppcf 10 mg/m3 15 mg/m3	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA):	Total dust. Total dust. Total dust. Total dust.	ACGIH OSHA ACGIH		
Mica Titanium dioxide Form Appearance	3 mg/m3 20 mppcf 10 mg/m3 15 mg/m3 9. PHYSIC : Solic : Pelle	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRC d Evapor ets Specifi	Total dust. Total dust. Total dust. Total dust. DPERTIES ration rate : Not ic Gravity : Not	ACGIH OSHA ACGIH OSHA Z1		
Components Mica Titanium dioxide Form Appearance Color	3 mg/m3 20 mppcf 10 mg/m3 15 mg/m3 9. PHYSIC : Solic : Pelle : YEL	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO the Evapore Ets Specific LOW Bulk d	Total dust. Total dust. Total dust. Total dust. DPERTIES ration rate : Not ic Gravity : Not lensity : Not	ACGIH OSHA ACGIH OSHA Z1		
Components Mica Titanium dioxide Form Appearance	3 mg/m3 20 mppcf 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : YEL : Very : Not of	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO d Evapor ets Specification LOW Bulk d v faint Vapor	Total dust. Total dust. Total dust. Total dust. Total dust. OPERTIES ration rate : Not ic Gravity : Not lensity : Not pressure : Not density : Not	ACGIH OSHA ACGIH OSHA Z1		

10. STABILITY AND REACTIVITY

: Insoluble

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.



MATERIAL SAFETY DATA SHEET

PMS 3935C YELLOW GRANITE

Version Number 1.0 Revision Date 01/28/2002 Page 4 of 5 Print Date 11/3/2011

Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
12001-26-2	Mica	Systemic effects	Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: Not regulated for transportation.
ICAO/IATA	: Not regulated for transportation.
	4/5



MATERIAL SAFETY DATA SHEET

PMS 3935C YELLOW GRANITE

Version Number 1.0 Revision Date 01/28/2002 Page 5 of 5 Print Date 11/3/2011

IMO / IMDG	:	Not regulated for transportation.
	15	S. REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on the TSCA inventory or are exempt.
California Proposition 65	:	This product does not contain a substance listed by California Prop 65.
Canadian Regulations:		
WHMIS Classification	:	D2B
WHMIS Ingredient Disc	losu	ire List
CAS-No. 12001-26-2		
DSL	:	Listed.
National Inventories:		
Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Listed.
Philippines PICCS	:	Listed.
		16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.