

MATERIAL SAFETY DATA SHEET

WHITE UV

Version Number 1.0 Revision Date 01/26/2002 Page 1 of 6 Print Date 11/3/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	WHITE UV
Product code	:	CC10009475
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetramethyl-4-piperidinyl)-, polymer with 2,4,6-trichloro-1,3,5-triazine, reaction products	70624-18-9	1 - 5
Titanium dioxide	13463-67-7	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion	Resin particles, like other inert materials, can be mechanically irritating.May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.





WHITE UV	
Version Number 1.0 Revision Date 01/26/2002	Page 2 of 6 Print Date 11/3/2011
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, dry powder, foam.
Special Fire Fighting Procedures Unusual Fire/Explosion	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
Hazards	
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat

MATERIAL SAFETY DATA SHEET



sion Date 01/26/2002			Prir	Page 3 nt Date 11/3/2
	01	nly in areas with appropriate ex	xhaust ventilation.	
Storage		eep containers dry and tightly nd contamination. Keep in a d		ure absorption
8. E	XPOSURE	CONTROLS / PERSONAL	PROTECTION	
Respiratory protection	: N	: No personal respiratory protective equipment normally required.		
Eye/Face Protection	: S	afety glasses with side-shields		
Hand protection	: P:	rotective gloves.		
Skin and body protection	: L	ong sleeved clothing.		
Additional Protective Measures	: Safety shoes.			
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice Wash hands before breaks and at the end of workday.			
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.			
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Components Titanium dioxide	Value 10 mg/m3	Exposure time Time Weighted Average	Exposure type Total dust.	List: ACGIH
Components Titanium dioxide				ACGIH
Components Titanium dioxide	10 mg/m3 15 mg/m3	Time Weighted Average (TWA):	Total dust. Total dust.	ACGIH
Titanium dioxide	10 mg/m3 15 mg/m3 9. PHYSIC	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO	Total dust. Total dust. PERTIES	ACGIH OSHA Z1
Titanium dioxide	10 mg/m3 15 mg/m3	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO	Total dust. Total dust. PPERTIES ration rate : N	ACGIH
Titanium dioxide	10 mg/m3 15 mg/m3 9. PHYSIC : Solid	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO L Evapor ts Specifi TE Bulk d	Total dust. Total dust. PERTIES ration rate : N ic Gravity : N ensity : N	ACGIH OSHA Z1
Titanium dioxide Form Appearance Color Odor	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : WHI : Very	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO ts Specifi TE Bulk d faint Vapor	Total dust. Total dust. PERTIES ration rate : N ratic Gravity : N ensity : N pressure : N	ACGIH OSHA Z1 (ot applicable. (ot determined (ot established (ot applicable
Titanium dioxide Form Appearance Color Odor Melting point/range	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : WHI : Very : Not c	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO ts Specifi TE Bulk d faint Vapor letermined Vapor	Total dust. Total dust. PERTIES ration rate : N ic Gravity : N ensity : N pressure : N density : N	ACGIH OSHA Z1 (ot applicable. (ot determined (ot established (ot applicable (ot applicable
Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point:	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : WHI : Very : Not c : Not a	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO ts Specifi TE Bulk d faint Vapor letermined Vapor applicable pH	Total dust. Total dust. PERTIES ration rate : N ic Gravity : N ensity : N pressure : N density : N	ACGIH OSHA Z1 (ot applicable. (ot determined (ot established (ot applicable
Titanium dioxide Form Appearance Color Odor Melting point/range	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : WHI : Very : Not c	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO ts Specifi TE Bulk d faint Vapor letermined Vapor applicable pH	Total dust. Total dust. PERTIES ration rate : N ic Gravity : N ensity : N pressure : N density : N	ACGIH OSHA Z1 (ot applicable. (ot determined (ot established (ot applicable (ot applicable
Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point:	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : WHI : Very : Not a : Insol	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO ts Specifi TE Bulk d faint Vapor letermined Vapor applicable pH	Total dust. Total dust. PERTIES ration rate : N ic Gravity : N ensity : N pressure : N density : N : N	ACGIH OSHA Z1 (ot applicable. (ot determined (ot established (ot applicable (ot applicable
Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point:	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : WHI : Very : Not c : Insol 10. S	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO ts Specifi TE Bulk d faint Vapor letermined Vapor applicable pH uble	Total dust. Total dust. PERTIES ration rate : N ic Gravity : N ensity : N pressure : N density : N : N	ACGIH OSHA Z1 ot applicable. fot determined fot established fot applicable fot applicable
Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : WHI : Very : Not c : Not a : Insol 10. S : Si	Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO ts Specifi TE Bulk d faint Vapor determined Vapor applicable pH uble	Total dust. Total dust. PERTIES ration rate : N ic Gravity : N ensity : N pressure : N density : N : N	ACGIH OSHA Z1 (ot applicable. (ot determined (ot established (ot applicable (ot applicable



MATERIAL SAFETY DATA SHEET

WHITE UV

Version Number 1.0	Page 4 of 6
Revision Date 01/26/2002	Print Date 11/3/2011
Incompatible Materials	: Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
70624-18-9	1,6-Hexanediamine,	Highly Toxic	Refer to MSDS for Toxicity
	N,N'-bis(2,2,6,6-tetrameth		Data
	yl-4-piperidinyl)-,polymer		
	with		
	2,4,6-trichloro-1,3,5-triazi		
	ne, reaction products		
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
70624-18-9	1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetrameth yl-4-piperidinyl)-,polymer with 2,4,6-trichloro-1,3,5-triazi ne, reaction products	LC50 Oral LD50	112 mg/m3 9,910 mg/kg	rat rat

12. ECOLOGICAL INFORMATION

Persistence and degradability	Not readily biodegradable.	
Environmental Toxicity	Chemicals are not readily available as they are bound f the polymer.	within the matrix
Bioaccumulation Potential	Chemicals are not readily available as they are bound f the polymer.	within the matrix
Additional advice	No data available.	
	DISPOSAL CONSIDERATIONS	
Product	Like most thermoplastics the product can be recycled ecycling is preferred to disposal or incineration. The	-

MATERIAL SAFETY DATA SHEET



WHITE UV	
Version Number 1.0 Revision Date 01/26/2002	Page 5 of Print Date 11/3/201
	waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: Not regulated for transportation.
ICAO/IATA	: Not regulated for transportation.
IMO / IMDG	: Not regulated for transportation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on the TSCA inventory or are exempt.
California Proposition 65	: This product does not contain a substance listed by California Prop 65.
Canadian Regulations:	
WHMIS Classification	: D1A
DSL	: Listed.
National Inventories:	
Australia AICS	: Listed.
China IECS	: Listed.
Europe EINECS	: Not determined.
Japan ENCS	: Not determined.
Korea KECI	: Not determined.
	: Not determined.



MATERIAL SAFETY DATA SHEET

WHITE UV

Version Number 1.0 Revision Date 01/26/2002 Page 6 of 6 Print Date 11/3/2011

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.