

MATERIAL SAFETY DATA SHEET

016GY75 COOL GREY 2

Version Number 1.0 Revision Date 02/28/2002 Page 1 of 5 Print Date 11/3/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	016GY75 COOL GREY 2
Product code	:	CC10009811
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous	7631-86-9	5 - 10
Titanium dioxide	13463-67-7	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

016GY75 COOL GREY 2

Version Number 1.0 Revision Date 02/28/2002 Page 2 of 5 Print Date 11/3/2011

Inhalation :		Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.			
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.			
Eyes	:	: Rinse immediately with plenty of water, also under the eyelids, for least 15 minutes. If eye irritation persists, seek medical attention.			
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.			
		5. FIRE-FIGHTING MEASURES			
Flash point	:	Not applicable			
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting	: : :	Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, dry powder, foam. Fullface self-contained breathing apparatus (SCBA) used in positive			
Procedures Unusual Fire/Explosion Hazards	:	pressure mode should be worn to prevent inhalation of airborne contaminants. None			
	6. A	CCIDENTAL RELEASE MEASURES			
Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.					
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.			
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.			
		7. HANDLING AND STORAGE			
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.			
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption			



MATERIAL SAFETY DATA SHEET

016GY75 COOL GREY 2

Version Number 1.0 Revision Date 02/28/2002 Page 3 of 5 Print Date 11/3/2011

8. F	EXPOSURE	CONTROLS / PERSO	NAL PROTECTION			
Respiratory protection	: N	lo personal respiratory pro	otective equipment norm	ally required.		
Eye/Face Protection		Safety glasses with side-shields.				
Hand protection		rotective gloves.				
-		-				
Skin and body protection	: L	ong sleeved clothing.				
Additional Protective Measures	: S	afety shoes.				
General Hygiene Considerations		landle in accordance with Vash hands before breaks				
Engineering measures		leat only in areas with app ppropriate exhaust ventila		ion. Provide		
Exposure limit(s)						
Components	Value	Exposure time	Exposure type	List:		
Silica, amorphous	20 mppcf	PEL:	Total dust.	OSHA		
	20 mppcf	PEL:	Total dust.	Z3		
Titanium dioxide	10 mg/m3	Time Weighted Avera (TWA):	ge Total dust.	ACGIH		
	15 mg/m3	PEL:	Total dust.	OSHA Z1		
	9. PHYSIC	CAL AND CHEMICAL	PROPERTIES			
Form	: Solic	i E	vaporation rate :	Not applicable.		
Appearance	: Pelle			Not determined		
Color	: GRE			Not established		
Odor	: Very	r faint V	apor pressure :	Not applicable		
Melting point/range				Not applicable		
Boiling Point:			H :	Not applicable		
Water solubility	: Insol	luble				
	10. 8	STABILITY AND REA	CTIVITY			
Stability	: S	table.				
	n : V	Vill not occur.				
Hazardous Polymerization						



MATERIAL SAFETY DATA SHEET

016GY75 COOL GREY 2

sion Number 1.0 vision Date 02/28/2002	2			Page 4 of 5 Print Date 11/3/2011	
Incompatible Materials	:	Incompatible wi	ith strong acids and o	xidizing agents.	
Hazardous decomposition products	on :			xide (CO), oxides of nitrogen d smoke are all possible.	
	11. 7	TOXICOLOGIC	CAL INFORMATIO	N	
health data for the indiv	idual compo	onents which com	prise the mixture.	re effects listed are based on existing have the following characteristics:	
CAS-No.	Chem	ical Name	Effect	Target Organ	
7631-86-9	Silica, amo		Irritant	Eyes, Respiratory system.	
13463-67-7	Titanium di		Systemic effects	Respiratory system.	
<u> </u>	10				
	12	. ECOLOGICA	L INFORMATION		
Persistence and degrada	bility :	Not readily biod	legradable.		
Environmental Toxicity	:	Chemicals are not of the polymer.	ot readily available as	s they are bound within the matrix	
Bioaccumulation Potent	tial :	Chemicals are no of the polymer.	ot readily available as	s they are bound within the matrix	
Additional advice	:	No data availab	le.		
	13	3. DISPOSAL C	ONSIDERATIONS		
Product		: Like most thermoplastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.			
Contaminated packagin	g :	has the responsi	bility for proper wast accordance with appl	. The generator of waste material e classification, transportation icable federal, state/provincial	
	1	4. TRANSPORT	TINFORMATION		
U.S. D.O.T. / CA T.D.C Classification (Non-bull ground)		Not regulated for	or transportation.		
ICAO/IATA	:	Not regulated for	or transportation.		
			/5		



MATERIAL SAFETY DATA SHEET

016GY75 COOL GREY 2

ision Date 02/28/2002		Print Date 11/3/
IMO / IMDG	:	Not regulated for transportation.
	15	. REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on the TSCA inventory or a exempt.
California Proposition 65	:	This product does not contain a substance listed by California Prop 6
Canadian Regulations:		
WHMIS Classification	:	D2B
WHMIS Ingredient Disc	losu	re List
CAS-No. 1333-86-4 7631-86-9		
DSL	:	Listed.
National Inventories:		
Australia AICS	:	Listed.
China IECS	:	Not determined.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Not determined.
Philippines PICCS	:	Not determined.
		16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.