

### MATERIAL SAFETY DATA SHEET

## AMBER, UV

Version Number 1.0 Revision Date 02/05/2002

Page 1 of 5 Print Date 11/3/2011

## **1. PRODUCT AND COMPANY IDENTIFICATION**

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902	
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).	
Product name	:	AMBER, UV	
Product code	:	CC10009856	
Chemical Name	:	Mixture	
CAS-No.	:	Mixture	
Product Use	:	Industrial Applications	

### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

There are no known hazardous ingredients in this product.

## 3. HAZARDS IDENTIFICATION

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes Skin	<ul> <li>Resin particles, like other inert materials, can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Resin particles, like other inert materials, are mechanically irritating to eyes.</li> <li>Experience shows no unusual dermatitis hazard from routine handling.</li> </ul>
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES

## MATERIAL SAFETY DATA SHEET



MBER, UV	
sion Number 1.0 vision Date 02/05/2002	Page 2 Print Date 11/3/2
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Plash point	. Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature	<ul><li>Not applicable</li><li>Not applicable</li><li>Not relevant</li></ul>
Suitable extinguishing media	: Carbon dioxide blanket, Water spray, dry powder, foam.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.



## MATERIAL SAFETY DATA SHEET

# AMBER, UV

Version Number 1.0 Revision Date 02/05/2002 Page 3 of 5 Print Date 11/3/2011

	OSURE CONTROLS /	PERSONAL PROTECTION			
Respiratory protection	: No personal respiratory protective equipment normally required.				
Eye/Face Protection	: Safety glasses with side-shields.				
Hand protection	: Protective gloves.	Protective gloves.			
Skin and body protection	: Long sleeved clot	Long sleeved clothing.			
Additional Protective Measures	: Safety shoes.	Safety shoes.			
General Hygiene Considerations		: Handle in accordance with good industrial hygiene and safety practice Wash hands before breaks and at the end of workday.			
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
Exposure limit(s)					
There are no known hazardou	is ingredients in this produ	uct.			
9.	PHYSICAL AND CHE	CMICAL PROPERTIES			
Form	: Solid	Evaporation rate : Not applicable.			
Appearance Color	: Pellets : YELLOW	Specific Gravity: Not determinedBulk density: Not established			
Odor	: Very faint				
	: Not determined	Vapor pressure:Not applicableVapor density:Not applicable			
Melting point/range Boiling Point:	: Not applicable	pH : Not applicable			
Water solubility	: Insoluble				
water solutinity	· monuolo				
	10. STABILITY AN	ND REACTIVITY			
Stability	: Stable.				
Stability Hazardous Polymerization	: Stable. : Will not occur.				
-	: Will not occur.	oxidizing agents and open flame. To avoid therma			
Hazardous Polymerization	<ul> <li>Will not occur.</li> <li>Keep away from o decomposition, do</li> </ul>				
Hazardous Polymerization Conditions to avoid	<ul> <li>Will not occur.</li> <li>Keep away from of decomposition, do</li> <li>Incompatible with</li> <li>Carbon dioxide (0)</li> </ul>	o not overheat.			



MATERIAL SAFETY DATA SHEET

# AMBER, UV

Version Number 1.0 Revision Date 02/05/2002 Page 4 of 5 Print Date 11/3/2011

There are no known hazardous ingredients in this product.

	12. ECOLOGICAL INFORMATION		
Persistence and degradability	: Not readily biodegradable.		
Environmental Toxicity	: Chemicals are not readily available as they are bound within the of the polymer.		
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.		
Additional advice	: No data available.		
	13. DISPOSAL CONSIDERATIONS		
Product	: Like most thermoplastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.		
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.		
	14. TRANSPORT INFORMATION		
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: Not regulated for transportation.		
ICAO/IATA	: Not regulated for transportation.		
IMO / IMDG	: Not regulated for transportation.		
	15. REGULATORY INFORMATION		
US Regulations:			
OSHA Status	: Product is non-hazardous		
TSCA Status	: All components of this product are listed on the TSCA inventory or are exempt.		
California Proposition 65	: This product does not contain a substance listed by California Prop 65		
Canadian Regulations:			
	4/5		



### MATERIAL SAFETY DATA SHEET

## AMBER, UV

Version Number 1.0 Revision Date 02/05/2002 Page 5 of 5 Print Date 11/3/2011

	WHMIS Classification	:	Not controlled.
	DSL	:	Listed.
Natio	onal Inventories:		
	Australia AICS	:	Listed.
	China IECS	:	Listed.
	Europe EINECS	:	Not determined.
	Japan ENCS	:	Listed.
	Korea KECI	:	Listed.
	Philippines PICCS	:	Not determined.

## **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.