

### MATERIAL SAFETY DATA SHEET

### PEBBLE

Version Number 1.0 Revision Date 02/26/2002 Page 1 of 6 Print Date 11/3/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902	
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).	
Product name	:	PEBBLE	
Product code	:	CC10010736	
Chemical Name	:	Mixture	
CAS-No.	:	Mixture	
Product Use	:	Industrial Applications	

#### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Carbon black	1333-86-4	0.1 - 1
C.I. Pigment Yellow 53	8007-18-9	10 - 30
Titanium dioxide	13463-67-7	60 - 100

### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See sections 3 and 11 for special precautions.

### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation Ingestion Eyes Skin	<ul> <li>Resin particles, like other inert materials, can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Particulates, like other inert materials can be mechanically irritating.</li> <li>Experience shows no unusual dermatitis hazard from routine handling.</li> </ul>
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



# MATERIAL SAFETY DATA SHEET

# PEBBLE

ion Number 1.0 sion Date 02/26/2002	Page 2 Print Date 11/3/2
	4. FIRST AID MEASURES
	4. FIKST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
	11
Flammable Limits	
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Autoignition temperature	: Not relevant
Suitable extinguishing media	: Carbon dioxide blanket, Water spray, dry powder, foam.
Spacial Fire Fighting	Eulifean calf contained broathing apparetus (SCDA) used in positive
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive
Procedures	pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: none
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption





Page 3 of 6

# PEBBLE

Version Number 1.0 Revision Date 02/26/2002

Print Date 11/3/2011 and contamination. Keep in a dry, cool place. 8. EXPOSURE CONTROLS / PERSONAL PROTECTION Respiratory protection No personal respiratory protective equipment normally required. If : dusty conditions occur wear appropriate respiratory protection. **Eye/Face Protection** : Safety glasses with side-shields. Hand protection Protective gloves. : Skin and body protection : Long sleeved clothing. Additional Protective Safety shoes. : Measures General Hygiene : Handle in accordance with good industrial hygiene and safety practice. Considerations Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
C.I. Pigment Yellow 53	0.2 mg/m3	Time Weighted Average (TWA):	as Ni	ACGIH
	1 mg/m3	PEL:	as Ni	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
Carbon black	on black 3.5 mg/m3 Time		Total dust. as carbon black	ACGIH
	3.5 mg/m3	PEL:	Total dust. as carbon black	OSHA Z1
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1

### 9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- Solid
  powder, granular
  TAN
  Very faint
  Not determined
  Not applicable
  Insoluble
- Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH
- Not applicable.
  Not determined
  Not applicable
  Not applicable
  Not applicable
  Not applicable



### MATERIAL SAFETY DATA SHEET

# PEBBLE

Version Number 1.0 Revision Date 02/26/2002 Page 4 of 6 Print Date 11/3/2011

	10. STABILITY AND REACTIVITY
Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: To avoid thermal decomposition, do not overheat. Keep away from oxidizing agents and open flame.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.
8007-18-9	C.I. Pigment Yellow 53	Irritant	Eyes, Skin.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

#### LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1333-86-4	Carbon black	no	2B	no
8007-18-9	C.I. Pigment Yellow 53	no	1	2

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.



MATERIAL SAFETY DATA SHEET

## PEBBLE

Version Number 1.0 Revision Date 02/26/2002 Page 5 of 6 Print Date 11/3/2011

2 - The component is reasonably anticipated to be a human carcinogen.

#### Additional Health Hazard Information:

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

lily biodegradable. ecological impact is not known or expected under normal use. erently biodegradable. available. <b>SAL CONSIDERATIONS</b> possible recycling is preferred to disposal or incineration. The or of waste material has the responsibility for proper waste ation, transportation and disposal in accordance with ele federal, state/provincial and local regulations. mg is preferred when possible. The generator of waste material responsibility for proper waste classification, transportation osal in accordance with applicable federal, state/provincial
erently biodegradable. available. SAL CONSIDERATIONS ossible recycling is preferred to disposal or incineration. The or of waste material has the responsibility for proper waste ation, transportation and disposal in accordance with de federal, state/provincial and local regulations. ng is preferred when possible. The generator of waste material responsibility for proper waste classification, transportation
available. <b>SAL CONSIDERATIONS</b> possible recycling is preferred to disposal or incineration. The or of waste material has the responsibility for proper waste ation, transportation and disposal in accordance with the federal, state/provincial and local regulations. Ing is preferred when possible. The generator of waste material responsibility for proper waste classification, transportation
SAL CONSIDERATIONS oossible recycling is preferred to disposal or incineration. The or of waste material has the responsibility for proper waste ation, transportation and disposal in accordance with de federal, state/provincial and local regulations. Ing is preferred when possible. The generator of waste material responsibility for proper waste classification, transportation
possible recycling is preferred to disposal or incineration. The or of waste material has the responsibility for proper waste ation, transportation and disposal in accordance with de federal, state/provincial and local regulations. and is preferred when possible. The generator of waste material responsibility for proper waste classification, transportation
or of waste material has the responsibility for proper waste ation, transportation and disposal in accordance with ele federal, state/provincial and local regulations. Ing is preferred when possible. The generator of waste material responsibility for proper waste classification, transportation
l regulations.
SPORT INFORMATION
lated for transportation.
lated for transportation.
lated for transportation.
ATORY INFORMATION



### MATERIAL SAFETY DATA SHEET

Version Number 1.0 Revision Date 02/26/2002		Page 6 of 6 Print Date 11/3/2011
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on the TSCA inventory or are exempt.
California Proposition 65	:	WARNING! This product contains a chemical known in the State of California to cause cancer.
SARA Title III Section 313 Tox	ic C	Chemicals:

Chemical Name	CAS-No.	Weight %
NICKEL COMPOUNDS	8007-18-9	28.57
ANTIMONY COMPOUNDS		

Canadian Regulations:

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.	
8007-18-9	
1333-86-4	

DSL

: Listed.

National Inventories:

Australia AICS	: Listed.
China IECS	: Listed.
Europe EINECS	: Listed.
Japan ENCS	: Not determined.
Korea KECI	: Listed.
Philippines PICCS	: Listed.

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.