

MATERIAL SAFETY DATA SHEET

SLEEK TRANSP ORANGE

Version Number 1.0 Revision Date 03/27/2002 Page 1 of 5 Print Date 11/4/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name Product code Chemical Name CAS-No. Product Use	:	SLEEK TRANSP ORANGE CC10012594 Mixture Mixture Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous	7631-86-9	1 - 5
Titanium dioxide	13463-67-7	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion		
Acute exposure			
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.		
Ingestion	: May be harmful if swallowed.		
Eyes	: No known effects.		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		
Medical Conditions Aggravated by Exposure:	: None known.		



MATERIAL SAFETY DATA SHEET

SLEEK TRANSP ORANGE

Version Number 1.0 Revision Date 03/27/2002 Page 2 of 5 Print Date 11/4/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. Seek medical attention after significant exposure.
Ingestion	: Do not induce vomiting without medical advice. Seek medical attention if necessary.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Greater than 200 Deg F
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Not applicable. Not applicable. Not applicable. Carbon dioxide blanket, dry powder, foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
	5. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binde universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption



MATERIAL SAFETY DATA SHEET

SLEEK TRANSP ORANGE

Version Number 1.0 Revision Date 03/27/2002 Page 3 of 5 Print Date 11/4/2011

0.1		nd contamination.				
8.1	SAPOSURE	CONTROLS / PE	CRSONAL .	PROTECTION		
Respiratory protection	: U	Under normal handling conditions a respirator is not required.				
Eye/Face Protection	: S	Safety glasses with side-shields.				
Hand protection	: P	Protective gloves.				
Skin and body protection	: L	ong sleeved clothir	ng.			
Additional Protective Measures	: S	afety shoes.				
General Hygiene: Handle in accordance with good industrial hygiene and safety practice.ConsiderationsWash hands before breaks and at the end of workday.						
Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.						
Exposure limit(s)						
Components	Value	Exposure t	ime	Exposure typ	be	List:
Silica, amorphous	20 mppcf	PEL:		Total dust.	-	OSHA
Silica, amorphous	20 mppcf	PEL:		Total dust.		Z3
Titanium dioxide	10 mg/m3	Time Weighted (TWA)	-	Total dust.		ACGIH
Titanium dioxide	15 mg/m3	PEL:		Total dust.		OSHA Z1
			ICAL PRO	PERTIES		
	9. PHYSIC	CAL AND CHEM	ICHE I KO			
Form					Not	determined
Form	: liqui	d	Evapor	ration rate :		determined
Appearance	: liqui : visco	d ous, liquid	Evapor Specifi	ration rate : c Gravity :	Not	determined
Appearance Color	: liqui : visco : ORA	d ous, liquid NGE	Evapor Specifi Bulk de	ration rate : c Gravity : ensity :	Not Not	determined applicable.
Appearance Color Odor	: liqui : visco : ORA : Very	d ous, liquid NGE faint	Evapor Specifi Bulk de Vapor	ration rate : c Gravity : ensity : pressure :	Not Not Not	determined applicable. determined
Appearance Color Odor Melting point/range	: liqui : visco : ORA : Very : Not a	d ous, liquid NGE faint applicable	Evapoi Specifi Bulk de Vapor Vapor	ration rate : c Gravity : ensity :	Not Not Not Not	determined applicable. determined determined
Appearance Color Odor	: liqui : visco : ORA : Very : Not a : Not a	d ous, liquid NGE faint	Evapor Specifi Bulk de Vapor	ration rate : c Gravity : ensity : pressure :	Not Not Not Not	determined applicable. determined
Appearance Color Odor Melting point/range Boiling Point:	: liqui : visco : ORA : Very : Not a : Not a : imm	d ous, liquid NGE faint applicable applicable	Evapor Specifi Bulk de Vapor Vapor pH	ration rate : c Gravity : ensity : pressure : density :	Not Not Not Not	determined applicable. determined determined
Appearance Color Odor Melting point/range Boiling Point:	: liqui : visco : ORA : Very : Not a : imm 10. S	d ous, liquid NGE faint applicable applicable iscible	Evapor Specifi Bulk de Vapor Vapor pH	ration rate : c Gravity : ensity : pressure : density :	Not Not Not Not	determined applicable. determined determined
Appearance Color Odor Melting point/range Boiling Point: Water solubility	: liqui : visco : ORA : Very : Not a : Not a : imm 10. S : S	d ous, liquid NGE faint applicable applicable iscible	Evapor Specifi Bulk de Vapor Vapor pH	ration rate : c Gravity : ensity : pressure : density :	Not Not Not Not	determined applicable. determined determined
Appearance Color Odor Melting point/range Boiling Point: Water solubility Stability	: liqui : visco : ORA : Very : Not a : Not a : imm 10. S : S n : W	d ous, liquid NGE faint applicable applicable iscible STABILITY AND table.	Evapor Specifi Bulk d Vapor Vapor pH	ration rate : c Gravity : ensity : pressure : density : ITY	Not Not Not Not	determined applicable. determined determined



MATERIAL SAFETY DATA SHEET

SLEEK TRANSP ORANGE

Version Number 1.0 Revision Date 03/27/2002 Page 4 of 5 Print Date 11/4/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

12. ECOLOGICAL INFORMATION

Environmental Toxicity	: Adverse ecological impact is not known or expected under normal use
Bioaccumulation Potential	: Does not bioaccumulate
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: Not regulated for transportation.
ICAO/IATA	: Not regulated for transportation.
IMO / IMDG	: Not regulated for transportation.
	15. REGULATORY INFORMATION



MATERIAL SAFETY DATA SHEET

SLEEK TRANSP ORANGE

Version Number 1.0 Revision Date 03/27/2002	Page 5 of 5 Print Date <i>11/4/2011</i>
US Regulations:	
OSHA Status :	Classified as hazardous based on components.
TSCA Status :	All components of this product are listed on the TSCA inventory or are exempt.
California Proposition : 65	This product does not contain a substance listed by California Prop 65.
Canadian Regulations:	
WHMIS Classification :	D2B
WHMIS Ingredient Disclos	ure List
CAS-No. 103-23-1 7631-86-9	
DSL :	Listed.
National Inventories:	
Australia AICS :	Not determined.
China IECS :	Listed.
Europe EINECS :	Not determined.
Japan ENCS :	Not determined.
Korea KECI :	Not determined.
Philippines PICCS :	Not determined.
	16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.