

MATERIAL SAFETY DATA SHEET

LIGHT GREEN 5595C

Version Number 1.0 Revision Date 03/22/2002 Page 1 of 5 Print Date 11/4/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	LIGHT GREEN 5595C
Product code	:	CC10012762
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous	7631-86-9	5 - 10
Titanium dioxide	13463-67-7	60 - 100

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation Ingestion Eyes Skin	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Particulates, like other inert materials can be mechanically irritating. Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

LIGHT GREEN 5595C

Version Number 1.0 Revision Date 03/22/2002 Page 2 of 5 Print Date 11/4/2011

		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion	: : :	Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, dry powder, foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. none
Hazards		
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption



MATERIAL SAFETY DATA SHEET

LIGHT GREEN 5595C

Version Number 1.0 Revision Date 03/22/2002 Page 3 of 5 Print Date 11/4/2011

8. E	XPOSURI	E CONTROLS / PERSO	NAL PROTECTION	
Respiratory protection		No personal respiratory pa dusty conditions occur we		
Eye/Face Protection	:	Safety glasses with side-s	hields.	
Hand protection	:	Protective gloves.		
Skin and body protection	:	Long sleeved clothing.		
Additional Protective Measures	:	Safety shoes.		
General Hygiene Considerations		Handle in accordance with Wash hands before breaks		
Engineering measures		Heat only in areas with ap appropriate exhaust ventil		ation. Provide
Exposure limit(s)				
Components	Value	Exposure time	Exposure typ	be List:
Silica, amorphous	20 mppcf	PEL:	Total dust.	
	20 mppcf		Total dust.	Z3
Titanium dioxide	10 mg/m3	Time Weighted Aver (TWA):	age Total dust.	ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	0 DUVS	ICAL AND CHEMICAI	DDODEDTIES	
	9.1115	ICAL AND CHEMICAI		
Form	: Sol	id I	Evaporation rate :	Not applicable.
Appearance	: pov	wder, granular	Specific Gravity :	Not applicable.
Color	: GR	EEN I	Bulk density :	Not determined
Odor			Vapor pressure :	Not applicable
Melting point/range	: Not	t determined	Vapor density :	Not applicable
Boiling Point:	: Not	t applicable j	oH :	Not applicable
Water solubility	: Inse	oluble		
	10.	STABILITY AND REA	CTIVITY	
	:	Stable.		
Stability				
Stability Hazardous Polymerization		Will not occur.		



MATERIAL SAFETY DATA SHEET

LIGHT GREEN 5595C

Version Number 1.0 Page 4 of 5 Revision Date 03/22/2002 Print Date 11/4/2011 Incompatible Materials : Incompatible with strong acids and oxidizing agents. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen Hazardous decomposition : (NOx), other hazardous materials, and smoke are all possible. products

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Adverse ecological impact is not known or expected under normal use.
Bioaccumulation Potential	: Not inherently biodegradable.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: Not regulated for transportation.
ICAO/IATA	: Not regulated for transportation.
IMO / IMDG	: Not regulated for transportation.



MATERIAL SAFETY DATA SHEET

LIGHT GREEN 5595C

Version Number 1.0 Revision Date 03/22/2002 Page 5 of 5 Print Date 11/4/2011

	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on the TSCA inventory or are exempt.
California Proposition 65	: This product does not contain a substance listed by California Prop 65
Canadian Regulations:	
WHMIS Classification	: D2B
WHMIS Ingredient Disc	losure List
CAS-No. 7631-86-9	
DSL	: Listed.
National Inventories:	
Australia AICS	: Not determined.
China IECS	: Not determined.
Europe EINECS	: Not determined.
Japan ENCS	: Not determined.
Korea KECI	: Not determined.
Philippines PICCS	: Not determined.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.