

MATERIAL SAFETY DATA SHEET

RED M2210A

Version Number 1.1 Revision Date 03/21/2002 Page 1 of 5 Print Date 11/4/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	RED M2210A
Product code	:	CC10012767
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous	7631-86-9	1 - 5
Titanium dioxide	13463-67-7	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See Sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

RED M2210A

sion Date 03/21/2002	Print Date 11/4/2
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, dry powder, foam.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption



MATERIAL SAFETY DATA SHEET

RED M2210A

ion Number 1.1 sion Date 03/21/2002				Print	Page Date 11/4,
	a	nd contamination. Keep in	a dry, cool place.		
8. 1	EXPOSURE	CONTROLS / PERSONA	AL PROTECTIO	DN	
Respiratory protection	: N	lo personal respiratory prot	ective equipment	normally 1	required.
Eye/Face Protection	: S	afety glasses with side-shie	elds.		
Hand protection	: P	rotective gloves.			
Skin and body protection	: L	ong sleeved clothing.			
Additional Protective Measures	: S	afety shoes.			
General Hygiene Considerations		landle in accordance with g Vash hands before breaks an			afety practio
Engineering measures		: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.			
Exposure limit(s)					
Components	Value	Exposure time	Exposure		List:
Silica, amorphous	20 mppcf	PEL:	Total d		OSHA
Titanium dioxide	20 mppcf 10 mg/m3	PEL: Time Weighted Average (TWA):	e Total d		Z3 ACGIH
	15 mg/m3	PEL:	Total d	ust.	OSHA Z
	9. PHYSI(CAL AND CHEMICAL P	ROPERTIES		
Form	: Solic		aporation rate		applicable.
Appearance Color	: Pelle : RED	1	ecific Gravity lk density		determined established
Odor	: KED		por pressure		applicable
Melting point/range			por density		applicable
Boiling Point:		applicable pH			applicable
Water solubility	: Insol			. 100	approacto
	10. 8	STABILITY AND REAC	ΓΙVITY		
Stability	: S	table.			
Stability Hazardous Polymerizatio		table. Vill not occur.			



MATERIAL SAFETY DATA SHEET

RED M2210A			
Version Number 1.1 Revision Date 03/21/2002			Page 4 of 5 Print Date 11/4/2011
Incompatible Materials	: Incompatible v	vith strong acids and o	oxidizing agents.
Hazardous decomposition products			xide (CO), oxides of nitrogen ad smoke are all possible.
	11. TOXICOLOGI	CAL INFORMATIO	DN
	en evaluated as a whole for idual components which com		are effects listed are based on existing
<u>Toxicity Overview</u> This product contains th	e following components wh	ich in their pure form	have the following characteristics:
CAS-No.	Chemical Name	Effect	Target Organ
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
		,	
	12. ECOLOGIC	AL INFORMATION	
Persistence and degrada Environmental Toxicity		not readily available a	s they are bound within the matrix
Bioaccumulation Potent		not readily available a	s they are bound within the matrix
Additional advice	: No data availa	ble.	
	13. DISPOSAL	CONSIDERATIONS	
Product	recycling is pro waste material transportation	eferred to disposal or i has the responsibility	t can be recycled. Where possible ncineration. The generator of for proper waste classification, ance with applicable federal,
Contaminated packaging	has the response	sibility for proper was accordance with appl	•. The generator of waste material te classification, transportation icable federal, state/provincial
	14. TRANSPOR	TINFORMATION	
U.S. D.O.T. / CA T.D.G Classification (Non-bulk ground)	•	for transportation.	
ICAO/IATA	: Not regulated :	for transportation.	

4/5



MATERIAL SAFETY DATA SHEET

sion Number 1.1 ision Date 03/21/2002		Page 5 Print Date 11/4/2
IMO / IMDG	:	Not regulated for transportation.
	15.	REGULATORY INFORMATION
US Regulations:		
OSHA Status	: (Classified as hazardous based on components.
TSCA Status		All components of this product are listed on the TSCA inventory or ar exempt.
California Proposition 65	: ′	This product does not contain a substance listed by California Prop 65
Canadian Regulations:		
WHMIS Classification	:]	D2B
WHMIS Ingredient Disc	losur	e List
CAS-No. 7631-86-9		
DSL	:	Listed.
National Inventories:		
Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Listed.
Philippines PICCS	:	Listed.
<u> </u>		16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.