

### MATERIAL SAFETY DATA SHEET

## SILVER

Version Number 1.0 Revision Date 03/26/2002 Page 1 of 6 Print Date 11/4/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	SILVER
Product code	:	CC10012951
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Aluminum	7429-90-5	1 - 5
Titanium dioxide	13463-67-7	5 - 10
Mica	12001-26-2	10 - 30

### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See Sections 3 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion	<ul><li>Resin particles, like other inert materials, can be mechanically irritating.</li><li>May be harmful if swallowed.</li></ul>
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.





ion Number 1.0 sion Date 03/26/2002		Page 2 Print Date 11/4/2
Medical Conditions Aggravated by Exposure:	None known.	
	4. FIRST AID N	IEASURES
Inhalation		n case of accidental inhalation of fumes from abustion. When symptoms persist or in all cases o l advice.
Ingestion		niting without medical advice. When symptoms es of doubt seek medical advice.
Eyes		with plenty of water, also under the eyelids, for an off eye irritation persists, seek medical attention.
Skin	Wash off with soap medical attention.	p and plenty of water. If skin irritation persists see
	5. FIRE-FIGHTIN	G MEASURES
Flash point	Not applicable	
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	Fullface self-conta	anket, Water spray, dry powder, foam. ined breathing apparatus (SCBA) used in positive uld be worn to prevent inhalation of airborne
	CCIDENTAL REL	EASE MEASURES
Personal precautions		personal protection during cleanup, such as boots and coveralls.
Environmental precautions		ased into the environment. The product should not r drains, water courses or the soil.
Methods for cleaning up	plastic, cardboard	by sweeping or vacuum. Package all material in or metal containers for disposal. Refer to Section 1 proper disposal methods.
	7. HANDLING A	ND STORAGE
Handling	Take measures to j only in areas with	prevent the build up of electrostatic charge. Heat

### MATERIAL SAFETY DATA SHEET



# SILVER

ersion Number 1.0 evision Date 03/26/2002		Page 3 of e Print Date 11/4/201
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXI	POSUF	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

Components	Value	Exposure time	Exposure type	List:
Aluminum	10 mg/m3	Time Weighted Average	Dust.	ACGIH
		(TWA):		
	5 mg/m3	Time Weighted Average	Welding fume. as Al	ACGIH
		(TWA):		
Aluminum	15 mg/m3	PEL:	Total dust. as Al	OSHA Z1
	5 mg/m3	PEL:	Respirable dust. as Al	OSHA Z1
Mica	3 mg/m3	Time Weighted Average	Total dust.	ACGIH
		(TWA):		
Mica	20 mppcf	PEL:	Total dust.	OSHA
Titanium dioxide	10 mg/m3	Time Weighted Average	Total dust.	ACGIH
		(TWA):		
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1

### 9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- Solid
  Pellets
  GREY
  Very faint
  Not determined
  Not applicable
  Insoluble
- Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH
- Not applicable.
  Not determined
  Not established
  Not applicable
  Not applicable
  Not applicable



### MATERIAL SAFETY DATA SHEET

# SILVER

Version Number 1.0 Revision Date 03/26/2002 Page 4 of 6 Print Date 11/4/2011

10. STABILITY AND REACTIVITY		
Stability	: Stable.	
Hazardous Polymerization	: Will not occur.	
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.	
Incompatible Materials	: Incompatible with strong acids and oxidizing agents.	
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.	

### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7429-90-5	Aluminum	Irritant	Skin, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
12001-26-2	Mica	Systemic effects	Respiratory system.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material



### MATERIAL SAFETY DATA SHEET

# SILVER

on Number 1.0 ion Date 03/26/2002			Print	Pag Date 11
		sibility for proper wan accordance with applations.		
	14. TRANSPOI	RT INFORMATION	Ň	
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: Not regulated	for transportation.		
ICAO/IATA	: Not regulated	for transportation.		
IMO / IMDG	: Not regulated	for transportation.		
	15. REGULATO	RY INFORMATIO	N	
US Regulations:	0002010			
-				
OSHA Status	: Classified as h	azardous based on co	omponents.	
TSCA Status	: All componen exempt.	ts of this product are	listed on the TSCA i	nventory o
California Proposition	: This product d	loes not contain a sub	stance listed by Cali	fornia Prop
65	1			-
-	-			-
65 SARA Title III Section 313 To Chemical Nam	oxic Chemicals:	CAS-No.	Weight %	
65 SARA Title III Section 313 To Chemical Nam	oxic Chemicals:			
65 SARA Title III Section 313 To Chemical Nam ALUMINUM	oxic Chemicals:	CAS-No.	Weight %	
65 SARA Title III Section 313 To Chemical Nam	oxic Chemicals: e (FUME OR DUST)	CAS-No.	Weight %	
65 SARA Title III Section 313 To Chemical Nam ALUMINUM Canadian Regulations: WHMIS Classification	oxic Chemicals: e (FUME OR DUST) n : D2B	CAS-No.	Weight %	
65 SARA Title III Section 313 To Chemical Nam ALUMINUM Canadian Regulations:	oxic Chemicals: e (FUME OR DUST) n : D2B	CAS-No.	Weight %	
65 SARA Title III Section 313 To Chemical Nam ALUMINUM Canadian Regulations: WHMIS Classification WHMIS Ingredient Dis CAS-No. 7429-90-5 1333-86-4 12001-26-2	oxic Chemicals: e (FUME OR DUST) n : D2B	CAS-No.	Weight %	
65 SARA Title III Section 313 To Chemical Nam ALUMINUM Canadian Regulations: WHMIS Classification WHMIS Ingredient Dis CAS-No. 7429-90-5 1333-86-4 12001-26-2 18282-10-5	oxic Chemicals: e (FUME OR DUST) n : D2B sclosure List	CAS-No.	Weight %	
65 GARA Title III Section 313 To Chemical Nam ALUMINUM Canadian Regulations: WHMIS Classification WHMIS Ingredient Dis CAS-No. 7429-90-5 1333-86-4 12001-26-2 18282-10-5 DSL	oxic Chemicals: e (FUME OR DUST) n : D2B sclosure List	CAS-No.	Weight %	



### MATERIAL SAFETY DATA SHEET

# SILVER

Version Number 1.0 Revision Date 03/26/2002		Page 6 of 6 Print Date <i>11/4/2011</i>
Europe EINECS	: Not determined.	
Japan ENCS	: Not determined.	
Korea KECI	: Listed.	
Philippines PICCS	: Listed.	
	16. OTHER INFORMATION	

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.