

MATERIAL SAFETY DATA SHEET

UV YELLOW M2208B 1225C

Version Number 1.1 Revision Date 03/26/2002 Page 1 of 5 Print Date 11/4/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	UV YELLOW M2208B 1225C
Product code	:	CC10013154
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous	7631-86-9	1 - 5
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See Sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

UV YELLOW M2208B 1225C

Version Number 1.1 Revision Date 03/26/2002 Page 2 of 5 Print Date 11/4/2011

		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	: : :	Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, dry powder, foam.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	:	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption



MATERIAL SAFETY DATA SHEET

UV YELLOW M2208B 1225C

ersion Number 1.1 evision Date 03/26/2002			Print	Page 3 of 5 Date 11/4/2011
	aı	nd contamination. Keep in a	a dry, cool place.	
8. H	XPOSURE	CONTROLS / PERSONA	L PROTECTION	
Respiratory protection	: N	o personal respiratory prote	ctive equipment normally	required.
Eye/Face Protection	: S	: Safety glasses with side-shields.		
Hand protection	: P	rotective gloves.		
Skin and body protection	: L	ong sleeved clothing.		
Additional Protective Measures	: S	afety shoes.		
General Hygiene Considerations		andle in accordance with go ash hands before breaks an		afety practice.
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.			Provide
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Silica, amorphous	20 mppcf	PEL:	Total dust.	OSHA
Titanium dioxide	20 mppcf 10 mg/m3	PEL: Time Weighted Average	Total dust. Total dust.	Z3 ACGIH
	15 mg/m3	(TWA): PEL:	Total dust.	OSHA Z1
	9. PHYSIC	CAL AND CHEMICAL P	ROPERTIES	
Form	: Solid			applicable.
Appearance Color	: Pelle		5	determined
Odor			5	established applicable
Melting point/range			1	applicable
Boiling Point:		applicable pH		applicable
Water solubility	: Insol			approvere
	10. S	STABILITY AND REACT	TVITY	
Stability	: S	table.		
Hazardous Polymerization	n : W	/ill not occur.		
Conditions to avoid		eep away from oxidizing ag ecomposition, do not overhe		avoid thermal



MATERIAL SAFETY DATA SHEET

UV YELLOW M2208B 1225C

sion Date 03/26/2002	Ζ		Print Date 11/4/2	
Incompatible Materials	: Incompatible v	with strong acids and o	oxidizing agents.	
Hazardous decompositi products			oxide (CO), oxides of nitrogen nd smoke are all possible.	
	11. TOXICOLOG	ICAL INFORMATIO	DN	
health data for the indiv Toxicity Overview	vidual components which co	mprise the mixture.	are effects listed are based on existence of the second se	
CAS-No.	Chemical Name	Effect	Target Organ	
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.	
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.	
	12. ECOLOGIC	AL INFORMATION	I	
Densistance and decred				
Persistence and degrada	ability : Not readily bio	degradable.		
Environmental Toxicity		: Chemicals are not readily available as they are bound within the matrix of the polymer.		
Bioaccumulation Poten	tial : Chemicals are of the polymer		s they are bound within the matri	
Additional advice	: No data availa	ble.		
	13. DISPOSAL	CONSIDERATIONS	5	
Product	: Like most thermoplastics the product can be recycled. possible, recycling is preferred to disposal or incineration generator of waste material has the responsibility for pro- classification, transportation and disposal in accordance applicable federal, state/provincial and local regulations		sposal or incineration. The esponsibility for proper waste posal in accordance with	
Contaminated packagin	has the respon and disposal in	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.		
	14. TRANSPOR	RT INFORMATION		
U.S. D.O.T. / CA T.D. Classification (Non-bul ground)	e	for transportation.		
ICAO/IATA	: Not regulated	for transportation.		



MATERIAL SAFETY DATA SHEET

UV YELLOW M2208B 1225C

sion Number 1.1 ision Date 03/26/2002		Page 5 Print Date 11/4/2
IMO / IMDG	:	Not regulated for transportation.
	15	5. REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on the TSCA inventory or ar exempt.
California Proposition 65	:	This product does not contain a substance listed by California Prop 65
Canadian Regulations:		
WHMIS Classification	:	D2B
WHMIS Ingredient Disc	losu	ure List
CAS-No. 7631-86-9		
DSL	:	Listed.
National Inventories:		
Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Not determined.
Philippines PICCS	:	Listed.
		16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.