

MATERIAL SAFETY DATA SHEET

GRAY

Version Number 1.1 Revision Date 04/05/2002 Page 1 of 6 Print Date 11/4/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	GRAY
Product code	:	CC10013301
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Carbon black	1333-86-4	0.1 - 1
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See Sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eves.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

GRAY

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits	
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Autoignition temperature	: Not relevant
Suitable extinguishing media	: Carbon dioxide blanket, Water spray, dry powder, foam.
Special Fire Fighting	: Fullface self-contained breathing apparatus (SCBA) used in positive
Procedures	pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption



MATERIAL SAFETY DATA SHEET

GRAY

Carbon black 3.5 mg/m3 PEL: Total dust. as carbon black OSHA Z Titanium dioxide 10 mg/m3 Time Weighted Average (TWA): Total dust. ACGIH	sion Number 1.1 ision Date 04/05/2002			Print I	Page 3 Date 11/4/2
Respiratory protection : No personal respiratory protective equipment normally required. Eye/Face Protection : Safety glasses with side-shields. Hand protection : Protective gloves. Skin and body protection : Long sleeved clothing. Additional Protective : Safety shoes. Measures : Handle in accordance with good industrial hygiene and safety practic Considerations General Hygiene : Handle in accordance with good industrial hygiene and safety practic Considerations Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Total dust. as carbon ACGIH (TWA): Carbon black 3.5 mg/m3 PEL: Total dust. as carbon OSHA Z black Titanium dioxide 10 mg/m3 Time Weighted Average Total dust. ACGIH (TWA): Titanium dioxide 10 mg/m3 PEL: Total dust. ACGIH (TWA): Titanium dioxide 15 mg/m3 PEL: Total dust. ACGIH (TWA): PHYSICAL AND CHEMICAL PROPERTIES : Pellets Specific Gravity : Not	and contamination. Keep in a dry, cool place.				
Eye/Face Protection : Safety glasses with side-shields. Hand protection : Protective gloves. Skin and body protection : Long sleeved clothing. Additional Protective : Safety shoes. Measures : Safety shoes. General Hygiene : Handle in accordance with good industrial hygiene and safety practic Considerations : Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Carbon black 3.5 mg/m3 Titanium dioxide 10 mg/m3 Time Weighted Average Total dust. as carbon OSHA Z Titanium dioxide 10 mg/m3 Time Weighted Average Total dust. ACGIH (TWA): Total dust. OSHA Z Diack OSHA Z Form : Solid Evaporation rate : Not applicable. Appearance : Pellets Specific Gravity : Not determined Color : GREY Bulk density : Not applicab	8. F	XPOSURE	CONTROLS / PERSONAL	PROTECTION	
Hand protection : Protective gloves. Skin and body protection : Long sleeved clothing. Additional Protective :: Safety shoes. Measures : Safety shoes. General Hygiene :: Handle in accordance with good industrial hygiene and safety practic Considerations :: Wash hands before breaks and at the end of workday. Engineering measures :: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) :: Components Value : Exposure time : Exposure type List: Carbon black 3.5 mg/m3 Time Weighted Average Total dust. as carbon ACGIH Carbon black 3.5 mg/m3 PEL: Total dust. ACGIH Titanium dioxide 10 mg/m3 Time Weighted Average Total dust. ACGIH Titanium dioxide 15 mg/m3 PEL: Total dust. ACGIH Operance :: Pellets Specific Gravity : Not applicable. Appearance :: Pellets Specific Gravity : Not established Odor : GREY Bulk density : Not applicable Belting point/range : Not d	Respiratory protection	: N	o personal respiratory protecti	ve equipment normally r	equired.
Skin and body protection : Long sleeved clothing. Additional Protective : Safety shoes. Measures : Handle in accordance with good industrial hygiene and safety practice Considerations : Handle in accordance with good industrial hygiene and safety practice Considerations : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Components Value Exposure time Exposure type List: Carbon black 3.5 mg/m3 Time Weighted Average Total dust. as carbon OSHA Z Diack 3.5 mg/m3 PEL: Total dust. ACGIH Titanium dioxide 10 mg/m3 Time Weighted Average Total dust. ACGIH Titanium dioxide 15 mg/m3 PEL: Total dust. ACGIH Operance : Solid Evaporation rate : Not applicable. Appearance : Pellets Specific Gravity : Not applicable. <tr< td=""><td>Eye/Face Protection</td><td>: Sa</td><td>afety glasses with side-shields</td><td></td><td></td></tr<>	Eye/Face Protection	: Sa	afety glasses with side-shields		
Additional Protective Measures : Safety shoes. General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practic Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Alue : Exposure time : Exposure type : List: Diack Carbon black 3.5 mg/m3 PEL: Total dust. as carbon OSHA Z Titanium dioxide 10 mg/m3 Time Weighted Average Total dust. OSHA Z Form : Solid Evaporation rate : Not applicable. Appearance : Pellets Specific Gravity : Not established Odor : Very faint Vapor density : Not applicable. Melting point/range : Not depplicable pH : Not applicable PH : Not applicable	Hand protection	: P	rotective gloves.		
Measures	Skin and body protection	: L	ong sleeved clothing.		
Considerations Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) Components Value Exposure time Exposure type List: Carbon black 3.5 mg/m3 Time Weighted Average Total dust. as carbon ACGIH Carbon black 3.5 mg/m3 PEL: Total dust. as carbon OSHA Z black Titanium dioxide 10 mg/m3 Time Weighted Average Total dust. ACGIH (TWA): black PHYSICAL AND CHEMICAL PROPERTIES Form Solid Evaporation rate Not applicable. Appearance Pellets Specific Gravity Not determined Vapor pressure Not applicable Melting point/range Not dapplicable PH stability Insoluble Insoluble Insoluble		: Sa	afety shoes.		
appropriate exhaust ventilation at machinery. Exposure limit(s) Components Value Exposure time Exposure type List: Carbon black 3.5 mg/m3 Time Weighted Average Total dust. as carbon ACGIH Carbon black 3.5 mg/m3 PEL: black Dack Carbon black 3.5 mg/m3 PEL: Total dust. as carbon OSHA Z Titanium dioxide 10 mg/m3 Time Weighted Average Total dust. ACGIH Titanium dioxide 10 mg/m3 Time Weighted Average Total dust. ACGIH Titanium dioxide 15 mg/m3 PEL: Total dust. ACGIH (TWA): Total dust. OSHA Z Dependence 15 mg/m3 PEL: Total dust. ACGIH (TWA): Total dust. OSHA Z PHYSICAL AND CHEMICAL PROPERTIES OSHA Z Form : Solid Evaporation rate : Not applicable. Appearance : Pellets Specific Gravity : Not established Odor : Very faint Vapor pre					afety practice
Components Value Exposure time Exposure type List: Carbon black 3.5 mg/m3 Time Weighted Average (TWA): Total dust. as carbon black ACGIH black Carbon black 3.5 mg/m3 PEL: Total dust. as carbon black OSHA Z black Titanium dioxide 10 mg/m3 Time Weighted Average (TWA): Total dust. ACGIH black Titanium dioxide 15 mg/m3 PEL: Total dust. ACGIH black Very family PEL: Total dust. OSHA Z Description 15 mg/m3 PEL: Total dust. OSHA Z Very family PHYSICAL AND CHEMICAL PROPERTIES OSHA Z Form : Solid Evaporation rate : Not applicable. Appearance : Pellets Specific Gravity : Not determined Color : GREY Bulk density : Not applicable Melting point/range : Not determined Vapor density : Not applicable Boiling Point: : Not applicable	Engineering measures				Provide
Carbon black 3.5 mg/m3 Time Weighted Average (TWA): Total dust. as carbon black ACGIH black Carbon black 3.5 mg/m3 PEL: Total dust. as carbon black OSHA Z black Titanium dioxide 10 mg/m3 Time Weighted Average (TWA): Total dust. as carbon black OSHA Z Titanium dioxide 15 mg/m3 PEL: Total dust. ACGIH (TWA): Titanium dioxide 15 mg/m3 PEL: Total dust. OSHA Z OSHA Z PHYSICAL AND CHEMICAL PROPERTIES Form : Solid Evaporation rate : Not applicable. Appearance : Pellets Specific Gravity : Not determined Odor : GREY Bulk density : Not applicable Melting point/range : Not determined Vapor density : Not applicable Boiling Point: : Not applicable pH : Not applicable IO. STABILITY AND REACTIVITY Stability : Stable. Hazardous Polymerization : Will not occur.	Exposure limit(s)				
Carbon black 3.5 mg/m3 Time Weighted Average (TWA): Total dust. as carbon black ACGIH black Carbon black 3.5 mg/m3 PEL: Total dust. as carbon black OSHA Z black Titanium dioxide 10 mg/m3 Time Weighted Average (TWA): Total dust. as carbon black OSHA Z Titanium dioxide 10 mg/m3 Time Weighted Average (TWA): Total dust. ACGIH Titanium dioxide 15 mg/m3 PEL: Total dust. ACGIH Form : Solid Evaporation rate : Not applicable. Appearance : Pellets Specific Gravity : Not determined Odor : GREY Bulk density : Not applicable Melting point/range : Not determined Vapor density : Not applicable Boiling Point: : Not applicable pH : Not applicable Hazardous Polymerization : Stable. : Hazardous Polymerization : Will not occur.	Components	Value	Exposure time	Exposure type	List:
Carbon black 3.5 mg/m3 PEL: Total dust. as carbon black OSHA Z black Titanium dioxide 10 mg/m3 Time Weighted Average (TWA): Total dust. ACGIH Titanium dioxide 15 mg/m3 PEL: Total dust. OSHA Z Titanium dioxide 15 mg/m3 PEL: Total dust. OSHA Z OSHA Z OSHA Z Titanium dioxide 15 mg/m3 PEL: Total dust. ACGIH Total dust. OSHA Z OSHA Z OSHA Z Titanium dioxide 15 mg/m3 PEL: Total dust. ACGIH Titanium dioxide 15 mg/m3 PEL: Total dust. OSHA Z Odor : : Not applicable Melting point: : Not applicable PH			Time Weighted Average	Total dust. as carbon	ACGIH
Image: constraint of the constra	Carbon black	3.5 mg/m3			OSHA Z1
Titanium dioxide15 mg/m3PEL:Total dust.OSHA Z9. PHYSICAL AND CHEMICAL PROPERTIESForm: SolidEvaporation rate: Not applicable.Appearance: PelletsSpecific Gravity: Not determinedColor: GREYBulk density: Not establishedOdor: Very faintVapor pressure: Not applicableMelting point/range: Not determinedVapor density: Not applicableBoiling Point:: Not applicablepH: Not applicableWater solubility: InsolubleInsolubleInsolubleStabilityHazardous Polymerization: Will not occur.	Titanium dioxide	10 mg/m3	8 8	Total dust.	ACGIH
Form : Solid Evaporation rate : Not applicable. Appearance : Pellets Specific Gravity : Not determined Color : GREY Bulk density : Not established Odor : Very faint Vapor pressure : Not applicable Melting point/range : Not determined Vapor density : Not applicable Boiling Point: : Not applicable pH : Not applicable Water solubility : Insoluble Insoluble Insoluble Id. STABILITY AND REACTIVITY Stability : Stable. Hazardous Polymerization : Will not occur. : Will not occur.	Titanium dioxide	15 mg/m3		Total dust.	OSHA Z1
Form : Solid Evaporation rate : Not applicable. Appearance : Pellets Specific Gravity : Not determined Color : GREY Bulk density : Not established Odor : Very faint Vapor pressure : Not applicable Melting point/range : Not determined Vapor density : Not applicable Boiling Point: : Not applicable pH : Not applicable Water solubility : Insoluble Insoluble Insoluble Id. STABILITY AND REACTIVITY Stability : Stable. Hazardous Polymerization : Will not occur.		0 PHVSI	TAL AND CHEMICAL PRO)DFDTIFS	
Appearance:PelletsSpecific Gravity:Not determinedColor:GREYBulk density:Not establishedOdor:Very faintVapor pressure:Not applicableMelting point/range:Not determinedVapor density:Not applicableBoiling Point::Not applicablepH:Not applicableWater solubility:InsolubleStability:Stable.Hazardous Polymerization:Will not occur		7,111,010			
Color: GREYBulk density: Not establishedOdor: Very faintVapor pressure: Not applicableMelting point/range: Not determinedVapor density: Not applicableBoiling Point:: Not applicablepH: Not applicableWater solubility: InsolubleInsoluble: Not applicableStabilityStability: Stable.Hazardous Polymerization: Will not occur.					
Odor: Very faintVapor pressure: Not applicableMelting point/range: Not determinedVapor density: Not applicableBoiling Point:: Not applicablepH: Not applicableWater solubility: InsolubleInsolubleId. STABILITY AND REACTIVITYStability: Stable.Hazardous Polymerization: Will not occur.					
Melting point/range : Not determined Vapor density : Not applicable Boiling Point: : Not applicable pH : Not applicable Water solubility : Insoluble Insoluble : Not applicable Stability : Stable. : Stable. : Will not occur.					
Boiling Point: : Not applicable pH : Not applicable Water solubility : Insoluble : Not applicable IO. STABILITY AND REACTIVITY Stability : Stable. Hazardous Polymerization : Will not occur.					
Water solubility : Insoluble 10. STABILITY AND REACTIVITY Stability : Stable. Hazardous Polymerization : Will not occur.					
IO. STABILITY AND REACTIVITY Stability : Stable. Hazardous Polymerization : Will not occur.	6				
Stability:Stable.Hazardous Polymerization:Will not occur.	Water solubility	: Insol	uble		
Hazardous Polymerization : Will not occur.		10. S	TABILITY AND REACTIV	/ITY	
	Stability	: S1	table.		
Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid therma	Hazardous Polymerization	n : W	/ill not occur.		
	Conditions to avoid	: K	eep away from oxidizing ager	its and open flame. To a	void thermal



MATERIAL SAFETY DATA SHEET

GRAY

Version Number 1.1 Revision Date 04/05/2002		Page 4 of 6 Print Date 11/4/2011
		decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
11. TOXICOLOGICAL INFORMATION		

as not been avaluated as a whole for health effects. Exposure effects listed are base

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1333-86-4	Carbon black	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:



MATERIAL SAFETY DATA SHEET

GRAY

Version Number 1.1	Page 5 of 6
Revision Date 04/05/2002	Print Date 11/4/2011

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: Not regulated for transportation.
ICAO/IATA	: Not regulated for transportation.
IMO / IMDG	: Not regulated for transportation.
	15. REGULATORY INFORMATION
US Regulations:	
es regulations.	



MATERIAL SAFETY DATA SHEET

GRAY		
Version Number 1.1 Revision Date 04/05/2002		Page 6 of 6 Print Date <i>11/4/2011</i>
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on the TSCA inventory or are exempt.
California Proposition 65	:	This product does not contain a substance listed by California Prop 65.
Canadian Regulations:		
WHMIS Classification	:	D2B
WHMIS Ingredient Disc	lost	ire List
CAS-No. 1333-86-4 68186-90-3		
DSL	:	Listed.
National Inventories:		
Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Listed.
Philippines PICCS	:	Listed.
		16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.