

MATERIAL SAFETY DATA SHEET

YELLOW

Version Number 1.0 Revision Date 04/02/2002 Page 1 of 6 Print Date 11/4/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	YELLOW
Product code	:	CC10013695
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetramethyl-4-piperidinyl)-, polymer with 2,4,6-trichloro-1,3,5-triazine, reaction products	70624-18-9	1 - 5
Calcium carbonate	1317-65-3	1 - 5
Titanium dioxide	13463-67-7	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See Sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.



MATERIAL SAFETY DATA SHEET

ELLOW	
rsion Number 1.0 vision Date 04/02/2002	Page 2 o Print Date 11/4/20
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, dry powder, foam.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE

MATERIAL SAFETY DATA SHEET



rsion Number 1.0 vision Date 04/02/2002		Page 3 of 6 Print Date 11/4/2013
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXF	POSUI	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	10 mg/m3	Time Weighted Average	Total dust.	ACGIH
		(TWA):		
Calcium carbonate	5 mg/m3	PEL:	Respirable dust.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color Odor Melting point/range Boiling Point: Water solubility

: Solid : Pellets : YELLOW : Very faint : Not determined : Not applicable : Insoluble

Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pН

Not applicable. : Not determined Not established : : Not applicable : Not applicable : Not applicable

:

10. STABILITY AND REACTIVITY

Stability

: Stable.



MATERIAL SAFETY DATA SHEET

YELLOW

Version Number 1.0 Revision Date 04/02/2002		Page 4 of 6 Print Date <i>11/4/2011</i>
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ	
70624-18-9	1,6-Hexanediamine,	Highly Toxic	Refer to MSDS for Toxicity	
	N,N'-bis(2,2,6,6-tetrameth		Data	
	yl-4-piperidinyl)-,polymer			
	with			
	2,4,6-trichloro-1,3,5-triazi			
	ne, reaction products			
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.	
		Systemic effects	Eyes, Skin, Respiratory system.	
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.	

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
70624-18-9	1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetrameth yl-4-piperidinyl)-,polymer with 2,4,6-trichloro-1,3,5-triazi ne, reaction products	LC50 Oral LD50	112 mg/m3 9,910 mg/kg	rat rat

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the matrix of the polymer.





YELLOW Version Number 1.0 Page 5 of 6 Print Date 11/4/2011 Revision Date 04/02/2002 Additional advice : No data available. 13. DISPOSAL CONSIDERATIONS Like most thermoplastics the product can be recycled. Where Product : possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Contaminated packaging Recycling is preferred when possible. The generator of waste material : has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. **14. TRANSPORT INFORMATION** U.S. D.O.T. / CA T.D.G. : Not regulated for transportation. Classification (Non-bulk ground) ICAO/IATA Not regulated for transportation. : IMO / IMDG Not regulated for transportation. : **15. REGULATORY INFORMATION US Regulations: OSHA Status** Classified as hazardous based on components. · All components of this product are listed on the TSCA inventory or are **TSCA Status** : exempt. California Proposition : This product does not contain a substance listed by California Prop 65. 65 Canadian Regulations: WHMIS Classification : D1A WHMIS Ingredient Disclosure List CAS-No. 7631-86-9 DSL : Listed. National Inventories:

PolyOne.

MATERIAL SAFETY DATA SHEET

YELLOW

Version Number 1.0 Revision Date 04/02/2002			Page 6 of 6 11/4/2011
Australia AICS	:	Listed.	
China IECS	:	Listed.	
Europe EINECS	:	Not determined.	
Japan ENCS	:	Not determined.	
Korea KECI	:	Not determined.	
Philippines PICCS	:	Not determined.	
	_	16. OTHER INFORMATION	

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.