

### MATERIAL SAFETY DATA SHEET

# 3M RED

Version Number 1.0 Revision Date 04/18/2002 Page 1 of 5 Print Date 11/4/2011

# 1. PRODUCT AND COMPANY IDENTIFICATION

### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	3M RED
Product code	:	CC10014255
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous	7631-86-9	1 - 5
Titanium dioxide	13463-67-7	1 - 5

### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See Sections 3 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	<ul> <li>Resin particles, like other inert materials, can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Resin particles, like other inert materials, are mechanically irritating to eyes.</li> </ul>
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



# MATERIAL SAFETY DATA SHEET

# 3M RED

ision Date 04/18/2002	Print Date 11/4/2
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not relevant</li> <li>Carbon dioxide blanket, Water spray, dry powder, foam.</li> </ul>
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>None</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption



# MATERIAL SAFETY DATA SHEET

# 3M RED

sion Number 1.0 ision Date 04/18/2002			Print	Page 3 t Date 11/4/2	
	a	nd contamination. Keep in a c	dry, cool place.		
8. F	XPOSURE	CONTROLS / PERSONAL	PROTECTION		
Respiratory protection	: N	lo personal respiratory protect	ive equipment normally	required.	
Eye/Face Protection	: S	afety glasses with side-shields	š.		
Hand protection	: P	rotective gloves.			
Skin and body protection	: L	ong sleeved clothing.			
Additional Protective Measures	: S	afety shoes.			
General Hygiene Considerations		Iandle in accordance with good Vash hands before breaks and		safety practic	
Engineering measures		: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.			
Exposure limit(s)					
Components	Value	Exposure time	Exposure type	List:	
Silica, amorphous	20 mppcf	PEL:	Total dust.	OSHA	
Silica, amorphous	20 mppcf	PEL:	Total dust.	Z3	
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH	
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z	
	9. PHYSIC	CAL AND CHEMICAL PRO	OPERTIES		
Form	: Solid	i Evapo	oration rate : No	ot applicable.	
Appearance	: Pelle	1		ot determined	
Color	: RED	Bulk d	density : No	ot established	
Odor				ot applicable	
Melting point/range				t applicable	
Boiling Point:		applicable pH	: No	ot applicable	
Water solubility	: Insol	uble			
	10. 8	STABILITY AND REACTIV	VITY		
Stability	: S	table.			
Hazardous Polymerization	n : W	Vill not occur.			
				avoid therma	



# MATERIAL SAFETY DATA SHEET

/ersion Number 1.0 Revision Date 04/18/2002			Page 4 of 5 Print Date 11/4/2011
Incompatible Materials	: Incompatible	with strong acids and	
Hazardous decompositio	-	-	oxide (CO), oxides of nitrogen
products			nd smoke are all possible.
	11. TOXICOLOG	ICAL INFORMATI	ON
	n evaluated as a whole for dual components which co		ure effects listed are based on existing
<u>Toxicity Overview</u> This product contains th	e following components wl	hich in their pure form	have the following characteristics:
CAS-No.	Chemical Name	Effect	Target Organ
7631-86-9 13463-67-7	Silica, amorphous Titanium dioxide	Irritant Systemic effects	Eyes, Respiratory system. Respiratory system.
		Systemic enceus	Tesphatory system
	12. ECOLOGIC	AL INFORMATION	N
Persistence and degradal Environmental Toxicity		not readily available a	as they are bound within the matrix
Bioaccumulation Potent	al : Chemicals are of the polymer		as they are bound within the matrix
Additional advice	: No data availa	ıble.	
	13. DISPOSAL	CONSIDERATIONS	5
Product	possible, recyc generator of w classification,	cling is preferred to di vaste material has the	act can be recycled. Where sposal or incineration. The responsibility for proper waste sposal in accordance with and local regulations.
Contaminated packaging	has the respon	sibility for proper was n accordance with app	e. The generator of waste material ste classification, transportation blicable federal, state/provincial
	14. TRANSPOR	RT INFORMATION	
U.S. D.O.T. / CA T.D.G Classification (Non-bulk ground)	e	for transportation.	
ICAO/IATA	: Not regulated	for transportation.	



### MATERIAL SAFETY DATA SHEET

# 3M RED

sion Number 1.0 rision Date 04/18/2002	Page Print Date 11/	
IMO / IMDG	: Not regulated for transportation.	
	15. REGULATORY INFORMATION	
US Regulations:		
OSHA Status	: Classified as hazardous based on components.	
TSCA Status	: All components of this product are listed on the TSCA inventory or exempt.	are
California Proposition 65	: This product does not contain a substance listed by California Prop	65
Canadian Regulations:		
WHMIS Classification	: D2B	
WHMIS Ingredient Disc	sure List	
CAS-No. 7631-86-9	]	
DSL	: Listed.	
National Inventories:		
Australia AICS	: Listed.	
China IECS	: Listed.	
Europe EINECS	: Not determined.	
Japan ENCS	: Not determined.	
Korea KECI	: Listed.	
Philippines PICCS	: Listed.	
	16. OTHER INFORMATION	—

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.