

MATERIAL SAFETY DATA SHEET

TRANSPARENT GRAY

Version Number 1.0 Revision Date 04/12/2002 Page 1 of 6 Print Date 11/4/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	TRANSPARENT GRAY
Product code	:	CC10014324
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Carbon black	1333-86-4	0.1 - 1

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See Sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

TRANSPARENT GRAY

Version Number 1.0 Revision Date 04/12/2002 Page 2 of 6 Print Date 11/4/2011

Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting	: :	Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, dry powder, foam. Fullface self-contained breathing apparatus (SCBA) used in positive
Procedures Unusual Fire/Explosion Hazards	:	pressure mode should be worn to prevent inhalation of airborne contaminants. None
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption



MATERIAL SAFETY DATA SHEET

TRANSPARENT GRAY

Version Number 1.0 Revision Date 04/12/2002 Page 3 of 6 Print Date 11/4/2011

0.1	WDOGUDE		EDCONAT	DDOTECTION	
ð. f	EXPOSURE	CONTROLS / P	EKSONAL	PROTECTION	
Respiratory protection	: No personal respiratory protect			ve equipment normally r	equired.
Eye/Face Protection	: Safety glasses with side-shields.				
Hand protection	: P	rotective gloves.			
Skin and body protection	: L	ong sleeved clothi	ing.		
Additional Protective Measures	: S	afety shoes.			
General Hygiene Considerations				l industrial hygiene and sa at the end of workday.	afety practice
Engineering measures		leat only in areas v ppropriate exhaust		iate exhaust ventilation. at machinery.	Provide
Exposure limit(s)					
Components	Value	Exposure	time	Exposure type	List:
Carbon black	3.5 mg/m3	Time Weighted		Total dust. as carbon	ACGIH
	-	(TWA)		black	
Carbon black	3.5 mg/m3	PEL:		Total dust. as carbon black	OSHA Z1
	9. PHYSIC	CAL AND CHEM	IICAL PRO	DPERTIES	
Form	: Solic	1	Evano	ration rate : Not	applicable.
Appearance	: Pelle				determined
Color	: GRE		Bulk d	2	established
Odor		[,] faint			applicable
Melting point/range	•	determined		-	applicable
Boiling Point:	: Not a	applicable	pH		applicable
Water solubility	: Insol				
	10. 8	STABILITY ANI) REACTIV	VITY	
Stability	: S	table.			
Hazardous Polymerization	n : V	Vill not occur.			
Conditions to avoid		keep away from ox ecomposition, do		ts and open flame. To a	void thermal



MATERIAL SAFETY DATA SHEET

TRANSPARENT GRAY

Version Number 1.0 Revision Date 04/12/2002 Page 4 of 6 Print Date 11/4/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1333-86-4	Carbon black	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.



MATERIAL SAFETY DATA SHEET

TRANSPARENT GRAY

Version Number 1.0 Revision Date 04/12/2002 Page 5 of 6 Print Date 11/4/2011

Persistence and degradability	: Not readily biodegradable.	
Environmental Toxicity	: Chemicals are not readily available as they are bound within the mat of the polymer.	riz
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the mat of the polymer.	riz
Additional advice	: No data available.	
	13. DISPOSAL CONSIDERATIONS	-
Product	: Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.	
Contaminated packaging	: Recycling is preferred when possible. The generator of waste mater has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.	ia
	14. TRANSPORT INFORMATION	
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: Not regulated for transportation.	
ICAO/IATA	: Not regulated for transportation.	
IMO / IMDG	: Not regulated for transportation.	
	15. REGULATORY INFORMATION	
US Regulations:		
OSHA Status	: Classified as hazardous based on components.	
	-	
TSCA Status	: All components of this product are listed on the TSCA inventory or a exempt.	u (
California Proposition 65	: This product does not contain a substance listed by California Prop	55
Canadian Regulations:		



MATERIAL SAFETY DATA SHEET

TRANSPARENT GRAY

Version Number 1.0 Print Date 11/4/2011 Revision Date 04/12/2002 WHMIS Classification : Not controlled. WHMIS Ingredient Disclosure List CAS-No. 1333-86-4 DSL : Listed. National Inventories: Australia AICS : Listed. : Listed. China IECS Europe EINECS Not determined. : Japan ENCS Not determined. : Korea KECI : Listed. **Philippines PICCS** : Listed. **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Page 6 of 6